

# ViewSonic® PJ250 Projector

Micro-portable, light and bright



## Business focus-palm-size 1kg projector.

ViewSonic's PJ250 projector is light and bright, making it the **ROAD-WARRIOR'S BEST FRIEND**. This 1kg XGA projector offers 1,000 lumens and 2000:1 contrast ratio for crystal-clear images. Capable of displaying digital and analogue signals for integrated data, video and audio, the PJ250 offers the **ULTIMATE IN FLEXIBILITY**, for any presentation setting on the road or in the office. Wherever you need to be, the PJ250 projector is your ideal companion. And ViewSonic's industry leading warranty program gives you the confidence you expect in any circumstances.

## Micro-Portable Series

### → Light as a feather at less than 1kg

Fits easily in a briefcase when you are on the road.

### → Bright in any setting with 1,000 lumens

### → True 1024x768 XGA resolution

Produces clear, crisp images including detailed spreadsheets.

### → Vivid video images and photos

Beautiful life-like pictures with an incredible 2000:1 contrast ratio.

### → Easy set-up and auto tuning

One-touch set-up button for fast, easy sync and sharp focus.

### → Supports digital signals including HDTV

Capable of displaying DVI and HDTV signals as well as other video and data sources.<sup>3</sup>

### → Soft carrying case included

For easy travelling and extra protection.

*Easy-to-use remote included.*



# Light idea

# ViewSonic® PJ250 Projector

Micro-portable, light and bright



1. Power button  
2. Menu  
3. Auto sync  
4. IR port (front/back)  
5. Leg adjust button  
6. Focus ring

PJ250 Distance Calculator	
Image Size (Diagonal in inches/cm)	Throw Distance (in inches/cm)
36/91	47/119
40/102	52/132
60/152	78/198
80/203	104/264
100/254	130/330
120/305	166/422
150/381	195/495
180/457	234/594
200/508	260/660

Accuracy of the calculations are +/- 5%.  
For additional calculations visit [ViewSonicEurope.com](http://ViewSonicEurope.com).

## Optional Accessories

- Replacement lamp
- DVI cable
- DVD component cable
- HDTV component cable

## MICRO-PORTABLE PROJECTOR

DLP	Type	0.7" XGA DLP™
	Pixel Format	1024 Horizontal x 768 Vertical (XGA), SXGA 1.280x1024 compressed
	Lens	Manual focus
DISPLAY	Size	0.89m - 5.08m (20"–245"), (measured diagonally)
	Throw Distance	1.2m - 6.87m (47"–260")
	Lamp	120W, 2000 hour rating
	Brightness	1,000 Lumens
	Contrast Ratio	2000:1
	Aspect Ratio	4:3, 16:9
AUDIO	Speakers	1 x 0.5 watts
INPUT SIGNAL	Video	RGB analogue, digital NTSC M, NTSC 4.43, PAL (B, D, G, H, I, M, N), SECAM (B, D, G, K, L), 480i/p, HDTV 720p, 1080i
	Sync	horizontal and vertical
	Frequency	F <sub>H</sub> :15–85kHz; F <sub>V</sub> :50–120Hz
COMPATIBILITY	PC	Analogue: VGA to SXGA (scaled), Digital: VGA to XGA (scaled)
	Mac®1	Analogue: to SXGA Digital: to XGA
CONNECTOR	RGB	15-pin HD, D-sub cable with adapter
	DVI	High density 29-pin DVI-I (option)
	Video	RCA
	S-Video	SVHS DIN Connector
	Audio	2.5mm Mini Stereo Plug
	Remote Mouse In	Din 8-pin
POWER	Voltage	100-120V/200-240V, 50-60Hz (universal)
	Consumption	180 watts (typ)
USER CONTROLS	Physical	Standby on/off, menu, enter/resync, source (data, video, and S-video), mute, volume (+, -)
	Remote	Standby on/off, source, laser, page up (PU), page down (PD), volume, keystone, zoom, mute, freeze, menu
	OSD	Display [brightness, contrast, picture adjustment, fine picture, H/V position, colour, tint, sharpness, reset, gamma, colour temp, colour system, colour space, aspect, filter, projection (vertical and horizontal flip), keystone correction (H/V keystone), picture-in-picture], Setup [language, auto source, auto power off, on screen, menu position, YpbPr, background, white balance], Info [status, default, lamp timer reset, resolution, frequency, lamp timer]
OPERATING CONDITIONS	Temperature	5° C to 30° C (41° F to 95° F)
	Humidity	30% to 85% (non-condensation)
DIMENSIONS	Physical (W x D x H)	180mm x 141mm x 45mm (excluding lens and leg)
WEIGHT	Net	1.0kg
REGULATIONS		CE, TUV/GS, UL, C-UL, FCC-CLASS A, CB, NOM, PCT, SASSO, BSMI, PSB/S-MARK, C-TICK, CCC, EMC REPORT
OTHER		Front and rear projection, 10 user modes. Included in box: power cord, DVI adapter, D-sub cable to DVI, composite video cable, S-video cable, remote control with batteries, lens cap, soft carrying case, Quick Start guide, user guide.
WARRANTY		Three-year limited warranty <sup>2</sup>



**ViewSonic®**  
See the difference.™

**ViewSonic Europe Limited/UK**  
ViewSonic House  
Fleming Way, Crawley  
West Sussex, RH10 9GA  
United Kingdom

Tel: +44 (0) 12 93 64 39 00  
Fax: +44 (0) 12 93 64 39 10

**ViewSonic Germany**  
Hanns-Martin-Schleyer-Straße 18A  
47877 Willich  
Germany

Tel: +49 (0) 21 54 91 88 0  
Fax: +49 (0) 21 54 91 88 10

**ViewSonic France**  
Parc des Barbannières  
1 allée des Bas Tilliers  
92230 Gennevilliers  
France

Tel: +33 (0) 1 41 47 49 00  
Fax: +33 (0) 1 41 47 49 10

**ViewSonic Corporation**  
381 Brea Canyon Road  
Walnut  
California 91789-0708  
USA

Tel: +1 909 869 7976  
Fax: +1 909 869 7958

**ViewSonic Benelux**  
**ViewSonic Denmark**  
**ViewSonic Finland**  
**ViewSonic Italy**  
**ViewSonic MEA**  
**ViewSonic Norway**  
**ViewSonic Spain**  
**ViewSonic Sweden**

Tel: +33 (0) 1 41 47 49 00  
Tel: +45 70 22 11 71  
Tel: +358 (9) 54 06 40 70  
Tel: +39 0289 079 340  
Tel: +971 (0) 4 88 11 871  
Tel: +47 (0) 22 88 17 60  
Tel: +34 (0) 91 63 05 339  
Tel: +46 (0) 8 50 71 30 00

<sup>1</sup> May require optional Mac adapter. <sup>2</sup> For further information see ViewSonic WebSite. <sup>3</sup> Optional cable required.

Specifications subject to change without notice. Selection, offers and programs may vary by country; see your ViewSonic representative for complete details. Corporate names, trademarks stated herein are the property of their respective companies. Copyright © 2003 ViewSonic Corporation. All rights reserved. PJ250 03/03-UK

For more product information, visit us on the web at [www.ViewSonicEurope.com](http://www.ViewSonicEurope.com)

specifications