

ViewSonic®

PJ501 Projector

Ultra-Portable SVGA Projector



- **1,500 lumens in only 5.4 lbs.**
Step up to super – bright images.
- **Native SVGA resolution**
Native SVGA (800x600) resolution for clear, crisp images.
- **Whisper-mode operations**
For extended lamp life and low noise output.
- **Displays HDTV signals**
Including 480i, 480p, 575i, 720p and 1080i.
- **Easy set-up and auto tuning**
One-touch setup button for fast, easy sync and sharp focus.
- **User-replaceable extended-life lamp**
Extended lamp life beyond 2,000 hours.**
- **Supporting 4:3 and 16:9 aspect ratios**
Offering increased flexibility for multiple formats.
- **Three-year limited warranty**
Covered by a three-year limited warranty and one-year Express Exchange® program.
- **Industry-leading one-year lamp warranty**
Extended life-lamp, warranted for a full year.*

Step up to a bright, ultra-portable, quiet projector.

Ideal for mobile professionals, the ViewSonic PJ501 projector offers high brightness at 1,500 lumens in a lightweight 5.4-pound package. You'll present a better image with native SVGA resolution compressing to XGA resolution. 4:3 and 16:9 aspect ratios, a short focal length, and zoom function add the versatility you need for all your presentations. Plus, the component video feature for superior video quality and whisper-mode setting for long lamp life make the ViewSonic PJ501 projector the dependable choice for the mobile presenter in the office and on the road.



ViewSonic®
See the difference.®

ViewSonic®

PJ501 Projector



- **Digital keystone correction**

Squares up the picture even when projecting at an angle.

- **Soft carry case**

Soft carry case included for easy travel.
Optional rugged hard case is also available.

- **Free 24/7 customer support†**

- **GSA Compliant**

- **Optional accessories**

Hard carrying case
Spare lamp
Ceiling/wall mount kit

ULTRA-PORTABLE SVGA PROJECTOR

| | | |
|----------------------|----------------------------|--|
| LCD | Type | 3-panel 0.7" TFT active matrix LCD |
| | Resolution | SVGA 800x600, compressed to 1024x768 |
| | Pixel Format | 800 Horizontal x 600 Vertical |
| | Lens | Manual zoom/focus (manual x 1.2) |
| DISPLAY | Size | 30"– 233" (measured diagonally) |
| | Throw Distance | 0.76m – 5.92m |
| | Lamp | 150W UHB Compact, 2,000** hour rating |
| | Brightness | 1,500 Lumens |
| | Contrast Ratio | 400:1 |
| | Keystone Correction | ±10 degrees |
| AUDIO | Aspect Ratio | 4:3, 16:9 |
| | Speaker | 1W monospeaker |
| INPUT SIGNAL | Video | RGB analog, NTSC, NTSC 4.43, PAL, PAL-M, PAL-N, PAL60, SECAM, 480i, 480p, 575i, 720p, 1080i |
| | Sync | Separated and Composite |
| | Frequency | F _H :15-78kHz; F _V :56-120Hz |
| COMPATIBILITY | PC | From VGA up to XGA |
| | Mac†† | Up to XGA (may require Mac Adapter) |
| CONNECTOR | RGB Input | 15-pin HD, D-sub (x1) |
| | Composite Video | RCA (x1) |
| | S-Video | Mini-Din 4 pin (x1) |
| | Component | RCA (x3) |
| | Audio In | RCA (x1) |
| | Audio Out | 3.5mm stereo mini jack (optional) |
| POWER | Control | 15-pin D-sub (RS232 optional) |
| | Voltage | 100–120 V AC / 220–240 V AC, 50–60Hz (universal) |
| USER CONTROLS | Consumption | 210W (typ), 130W (eco-mode) |
| | Basic | Standby on/off, menu (left, right, up, down), input, reset, mute, indicator (lamp, power, temp) |
| | Remote | Standby on/off, video, RGB, menu, position, menu select (left, right, up, down), reset, freeze, magnify (+, -, off), volume (up, down), mute, timer, auto, blank |
| | OnView® | Brightness, contrast, V. position, H. position, H. phase, H. size, color balance (red), color balance (blue), aspect ratio, auto, RGB, keystone, blank, mirror, start up, volume, menu color, timer, language, auto off, Sync on G |
| OPERATING CONDITIONS | Temperature | 32° F – 95° F (0° C – 35° C) |
| | Humidity | 10% – 85% (non-condensing) |
| DIMENSIONS | Physical | 277mm (W) x 211mm (D) x 61mm (H) (10.9" x 8.3" x 2.4") |
| | Net | 2.50 kg (5.4 lbs.) |
| WEIGHT | Gross | 3.24 kg (7.1 lbs.) |
| | REGULATIONS | UL, FCC-B, c-UL, CE, TUV/GS, CB Report, PCT |
| WARRANTY | WARRANTY | Three-year limited warranty on parts and labor. 1-year warranty on lamp.* |
| | OTHER | Mirror reverse image, upside down image, digital keystone correction, DDC 1/2B |



ViewSonic Corporation's QMS & EMS have been registered to ISO 9001 & ISO 14001, respectively, by the British Standards Institution.



ViewSonic®
See the difference.®

381 Brea Canyon Road, Walnut, CA 91789 • Phone (800) 888-8583 or (909) 444-8888 • Fax (909) 839-7922 • E-mail: SalesInfo@ViewSonic.com • ViewSonic.com

*Lamp warranty subject to terms and conditions, verification and approval. Applies to manufacturers installed lamp only. All accessory lamps purchased separately are warranted for 90 days. ** Running whisper-mode extends life beyond 2,000 hours.
† Excluding major U.S. holidays. †† Adapter may be required. Analog adapter available from ViewSonic. Specifications subject to change without notice. Selection, offers and programs may vary by country. See your ViewSonic representative for complete details.
Corporate names, trademarks stated herein are the property of their respective companies. Copyright© 2002 Viewsonic Corporation. All rights reserved PJ501 [10788-00B-10/02] PJ501-1