

PJD5122

LIGHT, BRIGHT AND PORTABLE PROJECTOR

Easy to use, Easy to afford

ViewSonic's PJD5122 is a great little projector that offers outstanding value and performance. This SVGA resolution projector supports high definition signals and projects 2700 lumens for clear, bright images in most lighting conditions. At only 2.3 kg it is light and compact, making it ideal for the mobile presenter. Texas Instruments' BrilliantColor™ technology delivers brilliant, true-color and high contrast images for viewing presentations, charts, or video. With extensive connectivity, including two RGB inputs and one RGB output, the PJD5122 is an excellent multifunctional data/video projector. Eco-mode reduces fan noise for less distraction during important presentations and even extends the lamp life up to 4000 hours*. For increased security a PIN lock feature allows you to set a password to prevent unauthorized use. The PJD5122 is perfect for tabletop, ceiling mounting or taking on the road.



VIEWSONIC
PRODUCTS, PROGRAMS,
AND SERVICES

Bright in virtually any setting

Packs 2,700 ANSI lumens in just 2.3 kg, and with a high 3000:1 contrast ratio (with DCR), your presentations are guaranteed to be vibrant even in the brightest office environment.

Eco-mode extends lamp life

Extend the life of your lamp up to 4000 hours* and reduce noise output.

BrilliantColor™ technology

Latest BrilliantColor™ Technology delivers stunning all-digital clarity with life-like color, sharp graphics and outstanding video. The sophisticated 6-segment color wheel enriches the yellow color performance that is key to accurate and vivid color reproduction.

Set to Present

With 8 preset picture modes, including whiteboard, blackboard and cinema it is easy to put together a great presentation.

Off to Go feature

The direct off feature allows the busy presenter to simply unplug the projector and go without waiting for the usual cool down phase. This feature also protects the lamp from sudden power blackouts.

3D DLP® Link Ready

With the advanced 3D DLP technology, PJD5122 can convert 60Hz video signals from standard DVD players into the amazing 120Hz format.

** Running ECO-mode, exclusively can extend lamp life.

ViewSonic®
See the difference™



PJD5122

Easy to use, Easy to afford



Optional Accessories

3D Goggle	PGD-150
Replacement lamp	RLC-055
Wireless presentation gateway	WPG-350
Ceiling mount	WMK-025

Projection Distance		4:3 Screen Size	
		Wide	
M	Feet	M	Inch
1.0	3.3	1.5	60
1.3	4.2	1.9	75
1.5	5.0	2.3	90
1.8	5.8	2.7	105
2.0	6.7	3.0	120
2.3	7.5	3.4	135
2.5	8.3	3.8	150
3.0	10.0	4.6	180
3.8	12.5	5.7	225
5.1	16.7	7.6	300
6.4	20.8	9.5	375
7.6	25.0	11.4	450



ViewSonic Corporation's QMS & EMS have been registered to ISO 9001 & ISO 14001, respectively, by the British Standards Institution.



Model Name		PJD5122
Display	Type	0.55" Digital Micromirror Device (DLP™)
	Resolution	SVGA 800×600 (Native)
	Lens	1.1× Manual optical zoom / Manual optical focus
	Keystone	Vertical digital keystone correction: ± 40 degrees
	Throw Distance	1.1 - 11.3m
	Throw Ratio	1.86:1-2.04:1
	Lamp	220watt
	Lamp Life (Normal / Eco Mode)	4000 / 6000* hours
	Brightness (Maximum)	2700 Lumens
	Contrast Ratio (Typical)	3000:1
	Colour Depth	24 bits, 16.7M Colours (8+8+8)
	Colour Wheel	6-Seg RGBCYW / 7200rpm
	Colour Gamut	81 % NTSC 1931 CIE
Audio	Speaker	5Wx1
Input Signal	Computer and video	NTSC M (3.58 MHz), 4.43MHz, PAL (B, D, G, H, I, M, N, 60), SD 480i and 576i (24fps, 25fps and 30fps), ED 480p and 576p (24fps, 25fps and 30fps), HD 720p, 1080i (24fps, 25fps and 30fps)
	Frequency	Fh: 31-100KHz, Fv: 48-120Hz
Compatibility	PC	XGA to UXGA
	Mac	Up to 1600×1200 (may require Mac Adapter)
Connector	RGB	Input: 2×15-pin D-sub, Output: 1×15-pin D-sub
	Composite Input	1 × RCA jack
	S-Video Input	1 x 4-pin mini DIN
	Audio Input	1 x 3.5mm mini jack
	Audio Output	1 x 3.5mm mini jack
	Control	1×RS-232 (8 Pin Mini-Din)
Power	Voltage	100~240VAC (Auto Switching), 50/60Hz (universal)
	Power Consumption	280W (Typical) / <1W (Stand-by mode)
Language		English/ Dutch/French/ Spanish/ Italian/ Korean/ Thai/Portuguese/ T. Chinese/ S. Chinese/ Japanese/ Russian/Germany/ Swedish/ Turkish/ Finnish /Polish/ Czech
Controls	Basic	Power, keystone/arrow keys, left/blank, menu/exit, right/panel key lock, auto, mode/enter, source
	OSD	(1) Display:Screen color/ Aspect ratio/ Keystone/ Position/ Phase/ H. Size/Digital Zoom/ 3D sync/ 3D sync invert/ Color management (2) Picture:Preset Mode/ Brightest/ Daylight/Game/ ViewMatch/Cinema/User 1/ User 2 Reference Mode: Brightest/ Daylight/ ViewMatch/Cinema/Game/Brightness /Contrast /Color /Tint / Sharpness / Brilliant Color /Color Temp. /Save Settings (3) Source: Quick Auto Search / Language/ Projector Position / Auto Power Off /Blank Time / Panel Key lock/ Timer Controller /Splash Screen/ Message (4) System Setup (Advanced):Quick Cooling / High Altitude Mode /DCR /Active VGA Out/ Audio Settings /Menu Settings / Closed Caption / Lamp Settings / Security Setting / Reset All Settings (5) Information
Operating	Temperature	0°C-40°C
Condition	Humidity	10%-90% (non-condensing)
Noise Level	Normal / Eco Mode	34dB / 28dB
Dimensions	Physical (W×H×D)	264 × 96.4 × 225 (mm)
Weight	Net	2.3 kg
Regulations		CB, UL, cUL, FCC (including ICES-003), CE,UL-Argentina, NOM, TUV-GS, GOST-R,SASO, Ukraine, PSB, C-Tick, Korean-eK, CCC, Hygiene, WEEE, RoHS
Packing Contents		ViewSonic projector, power cable, VGA cable, remote control with batteries, lens cap, Quick Start Guide, ViewSonic Wizard CD (with User Guide)

ViewSonic®
See the difference™

For more product information, visit us at ap.viewsonic.com

VS1 2010/06/28 V2