

PJD5152

PORTABLE SHORT THROW SVGA DLP PROJECTOR WITH BRILLIANTCOLOR™ TECHNOLOGY

Show your big ideas with our compact Projector

ViewSonic's mighty PJD5152 sets the stage for a new generation of versatile projectors equipped with BrilliantColor™ technology and an extreme short throw ratio – producing a 50" image at a distance of only 3 feet away. With its short throw lens, the PJD5152 saves space by allowing you to place it at the front of your table and still display large, crisp images. Weighing in at just 5.5 pounds with 2,600 ANSI lumens and a 3000:1 contrast ratio (with DCR), it's easy to give multimedia lessons in the classroom or dynamic presentations in the boardroom. Multiple preset presentation modes, an increased 40 degree digital vertical keystone correction and optical zoom ensure the best possible image regardless of location. With up to 6,000 hours of lamp life*, low cost replacement lamps, filter-less design and a non-degrading DLP® light engine, the PJD5152 is one of the lowest total cost of ownership projectors in the industry.



VERSATILE, IMPACT ANYWHERE

- > **Short-throw lens for large, stunning images in small spaces**
The short throw lens enables large images to be projected from short distances in small rooms with short throw distances. A screen size of 50" is possible from just 3 feet
- > **Bright in virtually any setting**
Packs 2,600 ANSI lumens in just 5.5 pounds, and with a high 3000:1 contrast ratio (with DCR), your presentations are guaranteed to be vibrant even in the brightest office environment.
- > **BrilliantColor™ technology**
Latest BrilliantColor™ Technology delivers stunning all-digital clarity with life-like color, sharp graphics and outstanding video. The sophisticated 6-segment color wheel enriches the yellow color performance that is key to accurate and vivid color reproduction.
- > **Eco-mode extends lamp life**
Extend the life of your lamp up to 6,000 hours* and reduce noise output.
- > **Off to Go feature**
The direct off feature allows the busy presenter to simply unplug the projector and go without waiting for the usual cool down phase. This feature also protects the lamp from sudden power blackouts.
- > **3D DLP® Link ready**
Supports up to 120Hz frame rate



ViewSonic®
See the difference® 

PJD5152

PORTABLE SHORT THROW SVGA DLP PROJECTOR WITH BRILLIANTCOLOR™



Optional Accessories

- > Replacement Lamp RLC-055
- > Universal Ceiling Mount Kit WMK-005
- > Wireless G Presentation Gateway WPG-350
- > Extended Express Exchange® PRJ-EE-05-03

Projection Distance		4:3 Screen Size			
		Wide		Tele	
M	Feet	M	Inches	M	Inches
0.7	2.3	1.0	40	1.2	48
1.1	3.6	1.5	60	1.8	72
1.5	4.9	2.0	80	2.4	96
1.8	5.9	2.5	100	3.0	120
2.8	9.2	3.8	150	4.6	180
3.2	10.6	4.6	180	5.5	216



ViewSonic Corporation's OMS & EMS have been registered to ISO 9001 & ISO 14001, respectively, by TUV NORD.

DISPLAY	Type	0.55" Digital Micromirror Device (DLP™)
	Resolution	800x600 (Native) SVGA
	Lens	1.2x optical zoom / Manual optical focus
	Keystone	Vertical digital keystone correction: +/- 40 degrees
	Size	40"-180" / 1m-4.57m
	Throw Distance	27"-127" / 0.69m-3.2m
	Throw Ratio	0.9:1-1.08:1
	Lamp	220W
	Lamp Life (Normal / Eco-mode)	4000 / 6000* hours
	Brightness	2600 Lumens
	Contrast Ratio	2000:1 (typ), 3000:1 (dynamic)
	Aspect Ratio	4:3 (native) and 16:9
	Color Gamut	85% NTSC 1931 CIE
INPUT SIGNAL	Computer and Video	
	NTSC M (3.58 MHz), 4.43MHz, PAL (B, D, G, H, I, M, N, 60), SECAM, SD 480i and 576i (24fps, 25fps and 30fps), ED 480p and 576p (24fps, 25fps and 30fps), HD 720p, 1080i (24fps, 25fps and 30fps)	
COMPATIBILITY	Frequency	Fh: 31-100KHz, Fv: 48-120Hz
	PC	VGA to SXGA
CONNECTOR	Mac®	Up to 832x624 (may require Mac adapter)
	RGB Input	15-pin mini D-sub (x2)
AUDIO	RGB Output	15-pin mini D-sub
	Component	15-pin mini D-Sub (shared with RGB) (x2)
	Composite Input	RCA jack
	S-video Input	4-pin mini-DIN
	Audio Input	3.5mm mini jack
	Audio Output	3.5mm mini jack
	Control	RS-232 (8-pin mini-DIN)
	Speaker	5W
	Amplifier	1W
POWER	Voltage	100~240VAC (Auto Switching), 50/60Hz (universal)
	Consumption	280W (typ) / <1W (stand-by mode)
CONTROLS	Basic	Standby/On, input, menu
	OSD	Display: Screen color, aspect ratio, keystone position, phase, H. size, digital zoom, 3D sync, 3D sync input Picture: Preset mode (brightness, standard (video), daylight, ViewMatch™ (PC), cinema, user 1/user 2), brightness, contrast, color, tint, sharpness, BrilliantColor™, color temperature, save settings Source: Quick auto search System Setting (Basic): Language, projector position, auto power off, blank timer, panel key lock, timer controller, splash screen System Setting (Advanced): Quick cooling, high altitude mode, dynamic contrast ratio, active VGA out, audio settings, menu settings, closed caption, lamp settings, security setting, reset all settings Information: Current system status (source, preset mode, resolution, color system, equivalent lamp hour)
OPERATING CONDITIONS	Temperature	32°F-104°F (0°C-40°C)
	Humidity	10%-90% (non-condensing)
	Altitude	0-6,000 ft (1,800m), operational up to 10,000 ft (3048m)
NOISE LEVEL	Normal / Eco-mode	32dB / 26dB
	Physical	10.4" x 3.8" x 8.86" (264mm x 96.4mm x 225mm)
DIMENSIONS (W x H x D)	Packaging	13.8" x 8.1" x 11.2" (350mm x 205mm x 285mm)
	Net	5.5 lb. (2.5 kg)
WEIGHT	Gross	8.8 lb. (4.0 kg)
REGULATIONS	CB, RoHS, WEEE, UL/cUL, FCC-B, ICES-003, IRAM (Argentina), NOM, PSB, C-tick, EK, CE, TUV/GS, GOST-R, Hygienic, SASO UKrSEPRO, CCC	
PACKAGE CONTENTS	ViewSonic projector, power cable, VGA cable, remote control with batteries, lens cap, soft case, Quick Start Guide, ViewSonic Wizard CD (with User Guide)	
WARRANTY	3-year limited warranty on parts, 1-year limited warranty on lamp, 1st year Express Exchange® service.	

Sales: (888) 881-8781 . SalesInfo@ViewSonic.com . ViewSonic.com

*Running eco-mode exclusively can extend lamp life. See ViewSonic.com for full Express Exchange details. Specifications subject to change without notice. Selection, offers and programs may vary by country; see your ViewSonic representative for complete details. Corporate names, trademarks stated herein are the property of their respective companies. Copyright © 2010 ViewSonic Corporation. All rights reserved [14949-01B-06/10] PJD5152-1

ViewSonic®
See the difference® 

For more product information, visit us on the web at ViewSonic.com