# PJD6210-3D

### VERSATILE, PORTABLE XGA DLP<sup>®</sup> PROJECTOR 120HZ AND 3D-READY

## Digital clarity in a portable projector.

ViewSonic's PJD6210-3D DLP<sup>®</sup> projector delivers amazingly clear images with the digital clarity of DLP's BrilliantColor<sup>™</sup> technology. It's ideal for use in the office or bring it home for bigger than life home entertainment. With 2,700:1 dynamic contrast, and 2,200 lumens (max) this powerful projector displays crisp text and vivid images. ViewMatch<sup>™</sup> technology adjusts colors perfectly so you enjoy rich, vibrant colors regardless of the setting. This projector is a lightweight powerhouse that offers multiple inputs, including support for 720p and 1080i HDTV signals. Eco-mode extends lamp life and reduces fan noise as low as 32dB. Enjoy easy set up with auto source detection and auto sync. When you're done, just unplug it and go. The PJD6210-3D DLP projector delivers excellent performance and value for small business and home entertainment applications.

### VERSATILE PRESENTATIONS ANYWHERE

#### > Bright in virtually any setting

Packs 2200 ANSI lumens in just 2.4 kg, and with a high 2700:1 contrast ratio, your presentations are guaranteed to be vibrant - even with a lot of ambient light.

> BrilliantColor<sup>™</sup> technology

Latest BrilliantColor™ technology delivers stunning all-digital clarity with life-like color, sharp graphics and outstanding video. The sophisticated 5-segment color (RGBWY) wheel provides greater color accuracy than standard DLP projectors with a 4-segment color wheel.

#### > Lowest "Total Cost of Projection"

Top cover lamp replacement ensures easy and cost-effective maintenance, while prices for replacement lamps are incredibly low. High performance is guaranteed by 3500 hours of lamp life or 4000 hours in eco mode! In addition, filter-less design means there is no need to clean or change filters.

#### > Protection and Personalisation

Assign a PIN code to prevent unauthorised use or theft, and customise your start-up screen to suit your needs.

#### > Ease of use

The PJD6210-3D comes with a suite of electronic features to make the setup process easy. Electronic keystone correction (+/-40 vertical degrees) maintains a squared image. In addition, this projector's automatic signal detection

reduces setup times, while a new button on the remote enables easy toggling between high brightness and brilliant color mode.



VIEWSONIC Products, Programs, and Services





PJD6210

## PJD6210-3D VERSATILE, PORTABLE XGA DLP® PROJECTOR - 120HZ AND 3D-READY









#### **Optional Accessories**

> Replacement Lamp

Projection Distance		4:3 Screen Size			
		Wide		Tele	
M	Feet	M	Inches	Μ	Inches
1.5	4.92	0.99	38.85	0.89	35
1.8	5.90	1.18	46.62	1.07	42
2	6.56	1.32	51.80	1.19	47
3	9.84	1.97	77.70	1.79	70
5	16.40	3.29	129.51	2.98	117
10	32.80	6.58	259.01	5.95	234

DISPLAY	Туре	0.55" Digital Micromirror Device (DLP™)		
	Resolution	XGA 1024x768 (native) / SXGA 1280×1024 (compressed)		
	Lens	1.1× manual optical zoom / manual optical focus		
	Keystone	Vertical digital keystone correction: +/- 40 degrees		
	Size	30"–300" / 0.8m–7.6m (diagonal)		
	Throw Distance	1.2m–10m / 3.9ft–32.8ft		
	Throw Ratio	1.97:1–16:1		
	Lamp	180 watt		
	Lamp Life (Normal / Eco-mode)	3500 / 4000* hours		
	Brightness	2200 Lumens		
	Contrast Ratio	2000:1 (typ), 2700:1 (dynamic)		
	Aspect Ratio	4:3 (native) and 16:9		
INPUT SIGNAL	Computer and Video	RGB analog, NTSC M (3.58 MHz), NTSC 4.43MHz,		
		PAL (B, D, G, H, I, M, N, 60), SECAM, SDTV/EDTV (480i/p,		
		576i/p), HDTV (720p, 1080i/p)		
	Frequency	Fh: 31–100KHz, Fv: 50–120Hz		
COMPATIBILITY	PC	Analog: VGA up to SXGA scaled		
	Mac®	Analog: up to XGA scaled (may require Mac Adapter)		
CONNECTOR	RGB Input	1 × 15-pin mini D-sub		
CONNECTOR	Composite Input	1 × RCA jack		
	Control	1 × RS-232 (9-pin D-sub)		
POWER	Voltage	90~240VAC (auto switching), 50/60Hz (universal)		
	Consumption	230W (typ) / 9W (stand-by mode)		
LANGUAGE	Consumption	English / Dutch / French / Spanish / Italian / Korean / Thai /		
		Portuguese / Traditional Chinese / Simplified Chinese /		
		Japanese / Russian / German / Swedish / Turkish / Finnish / Polish		
CONTROLS	Basic	Standby/on, input, menu		
CONTROLS	OSD	Picture: Brightness, contrast, color setting, keystone,		
	030	aspect ratio, image, white intensity, gamma		
		Computer Image: Frequency, tracking, H. position, V. position		
		Video Image: Saturation, sharpness, Tint		
		Setting: Manual position, projection, signal type, lamp hou lamp hour reset, power saving, auto source, eco-mode,		
		high altitude, OSD timeout		
		Advance: Blank screen, brilliant color, password, factory reset		
OTHER FEATURES		Bright in virtually in any setting with 2,200 lumens		
		5-segment color wheel, 2700:1 high dynamic contrast ratio,		
000000000		eco-mode		
OPERATING	Temperature	41°F–95°F (5°C–40°C)		
CONDITIONS	Humidity	10%-80% (non-condensing)		
	Altitude	0 to + 6,000 ft		
NOISE LEVEL	Normal / Eco-mode	34dB / 32dB		
DIMENSIONS	Physical	10.7 × 4.3 × 8.5 (in) / 273 × 108 × 215 (mm)		
(W x H x D)	Packaging	12.8 × 12.0 × 7.2 (in) / 325 × 305 × 183 (mm)		
WEIGHT	Net	5.3 lb (2.4 kg)		
REGULATIONS		CB, RoHS, WEEE, UL/cUL, FCC-B, ICES-003, IRAM		
		(Argentina), NOM, PSB, C-tick, EK, CE, TUV/GS, GOST-R,		
		Hygienic, SASO UKrSEPRO, CCC		
PACKAGE CON	TENTS	ViewSonic projector, power cable, VGA cable, remote		
		control with built-in laser, lens cap, Quick Start Guide,		
		ViewSonic Wizard CD (with User Guide)		
WARRANTY		ViewSonic Wizard CD (with User Guide) 3-year limited warranty on parts, 1-year limited warranty on lamp, 1st year Express Exchange <sup>®</sup> service.		



#### Sales: (888) 881-8781 . SalesInfo@ViewSonic.com . ViewSonic.com

RLC-046

\*Running eco-mode exclusively can extend lamp life. See ViewSonic.com for full Express Exchange details. Specifications subject to change without notice. Selection, offers and programs may vary by country; see your ViewSonic representative for complete details. Corporate names, trademarks stated herein are the property of their respective companies. Copyright © 2009 ViewSonic Corporation. All rights reserved [14496-00B-08/09] PJD6210-3D-1



## For more product information, visit us on the web at ViewSonic.com