

PJD6221

NETWORKABLE PORTABLE PROJECTOR

120HZ AND 3D-READY

Digitally clear, dynamic presentations.

The PJD6221 is a DLP® powerhouse that delivers sharp and bright images for virtually any environment. It's 3D ready with support for up to 120Hz frame rates. BrilliantColor™ technology produces more vibrant colors, while the high brightness and contrast ratio make this projector shine in the classroom or meeting room. RJ-45 connectivity enables remote network control, while extensive input options, including two RGB inputs and one RGB output, and integrated 2-watt stereo speakers deliver a truly dynamic multimedia experience. This projector even features closed captioning for the hearing impaired. The PJD6221 is ideal for use in classrooms and corporate settings.



SHINE BRIGHT, ANYWHERE

> Network control through RJ-45

Schedule, manage and monitor the projector remotely and receive e-mail alerts of projector lamp status. Use the unique integrated clock to perform commands even when the host PC is powered down.

> BrilliantColor™ technology

Latest BrilliantColor technology delivers stunning all-digital clarity with life-like color, sharp graphics and outstanding video. The sophisticated 6-segment color wheel enhances the yellow color performance that is key to accurate and vivid color reproduction.

> Closed captioning

Integrated closed captioning decoder for the hearing impaired.

> DLP® technology

Stunning all digital clarity delivers lifelike color, sharp graphics and outstanding video.

> Eco-mode extends lamp life

Extend the life of your lamp up to 5,000 hours** and reduce noise output.

> Off-to-Go feature

This feature allows the busy presenter to simply unplug the projector and go without waiting for the usual cool down phase. This feature also protects lamp life from sudden power blackout.



VIEWSONIC
PRODUCTS, PROGRAMS,
AND SERVICES



ViewSonic®
See the difference® 

PJD6221

NETWORKABLE PORTABLE PROJECTOR – 120HZ AND 3D-READY



Optional Accessories

- > Replacement Lamp RLC-050
- > Universal Ceiling Mount Kit WMK-005
- > Wireless G Presentation Gateway WPG-350
- > Soft Case PJ-CASE-001
- > Extended Express Exchange® PRJ-EE-08-03

Projection Distance		4:3 Screen Size			
		Wide		Tele	
M	Feet	M	Inches	M	Inches
1.5	4.92	1.17	46.14	0.99	39
1.8	5.90	1.41	55.36	1.18	47
2	6.56	1.56	61.52	1.32	52
3	9.84	2.34	92.27	1.97	78
5	16.40	3.91	153.79	3.29	130
10	32.80	7.81	307.58	6.58	259



Available at: **NETWORK Spectrum®**

Call: 301-733-0657

Email: sales@networkspectrum.com

Other products available at:

www.networkspectrum.com/gsaschedule/

DISPLAY

Type	0.55" Digital Micromirror Device (DLP™)
Resolution	XGA 1024x768 (Native) / SXGA 1280x1024 (compressed)
Lens	1.2x Manual optical zoom / Manual optical focus
Keystone	Vertical digital keystone correction: +/- 40 degrees
Size	30"-300" / 0.8m-7.6m
Throw Distance	1.2m-10m / 3.9ft. - 32.8ft.
Throw Ratio	1.6:1-1.9:1
Lamp	180 watt
Lamp Life (Normal / Eco-mode)	3500 / 5000* hours
Brightness	2,700 Lumens
Contrast Ratio	2800:1 (dynamic)
Aspect Ratio	4:3 (native) and 16:9
Color Depth	24 bits, 16.7M colors (8+8+8)
Color Wheel	6-Seg RGBCYW / 7200rpm
Color Gamut	85% NTSC 1931 CIE

INPUT SIGNAL

Computer and Video	NTSC M (3.58 MHz), 4.43MHz, PAL (B, D, G, H, I, M, N, 60), SD 480i and 576i (24fps, 25fps and 30fps), ED 480p and 576p (24fps, 25fps and 30fps), HD 720p, 1080i (24fps, 25fps and 30fps)
Frequency	Fh: 31-100KHz, Fv: 50-120Hz

COMPATIBILITY

PC	VGA to SXGA
Mac®	Up to 1152x864 (scaled)

CONNECTOR

RGB Input	15-pin mini D-sub (x2)
RGB Output	15-pin mini D-sub
Composite Input	RCA jack
S-video Input	4-pin mini-DIN
Audio Input	3.5mm mini jack (x2)
Audio Output	3.5mm mini jack
Control	RS-232 (9-pin D-sub) / RJ-45
USB	Type B (mouse control)

AUDIO

Speaker

2W

POWER

Voltage

90-240VAC (Auto Switching), 50/60Hz (universal)

Consumption

235W (typ) / <1W (stand-by mode)

CONTROLS

Basic

Power, keystone/arrow keys, left/blank, menu/exit, right/panel key lock, auto, mode/enter, source

OSD

Picture: brightest, contrast, color setting, keystone, aspect ratio, image, white intensity, gamma, 3D sync, 3D sync invert

Computer Image: Frequency, tracking, H. position, V. position

Video Image: Saturation, sharpness, tint

Setting: Menu position, projection, signal type, lamp hour, lamp hour reset, filter mode, filter hours, filter hours reset, power saving, auto source, eco-mode, high altitude, OSD timeout

Advance: blank screen, password, screen capture, start up screen

Text shot: digital zoom, dynamic contrast ratio, close caption, BrilliantColor

OPERATING CONDITIONS

Temperature	32°F-104°F (0°C-40°C)
Humidity	10%-90% (non-condensing)
Altitude	0-6,000 ft (1,800m), operational up to 10,000 ft (3,048m)

NOISE LEVEL

Normal / Eco-mode

31dB / 29dB

DIMENSIONS

Physical

11 x 4.5 x 8.6 (in) / 280 x 114 x 218 (mm)

(W x H x D)

Packaging

13.6 x 8.7 x 12 (in) / 345 x 305 x 220 (mm)

WEIGHT

Net

5.86 lb (2.66 kg)

REGULATIONS

CB, RoHS, WEEE, UL/cUL, FCC-B, ICES-003, IRAM (Argentina), NOM, PSB, C-tick, EK, CE, TUV/GS, GOST-R, Hygienic, SASO UKrSEPRO, CCC

PACKAGE CONTENTS

ViewSonic projector, power cable, VGA cable, remote control with batteries, lens cap, Quick Start Guide, ViewSonic Wizard CD (with User Guide)

WARRANTY

3-year limited warranty on parts, 1-year limited warranty on lamp, 1st year Express Exchange® service.

ViewSonic®
See the difference® 