

# VA2010wb

**20" WIDESCREEN LCD  
MONITOR VALUE SERIES**  
WITH 5MS VIDEO RESPONSE

## Large widescreen, big entertainment

ViewSonic's large 20" VA2010wb widescreen LCD ensures more space on the desktop and more detailed, fine images. Its high native 1680 x 1050 resolution and the wide aspect ratio gives you the comfort to work with two applications simultaneously as well as being perfectly suited to view HD format videos or to play intensive games. An ultra-high 1000:1 contrast ratio and very fast 5ms response time guarantees razor-sharp, ghost-free, vibrant images and perfect video performance with saturated colours. OptiSync technology provides digital and analogue inputs for multiple options and best signal connectivity. All this comes in a stylish midnight grey, slim bezel design. The ViewSonic VA2010wb is the budget-friendly, easy choice for gamers, demanding video applications and home/small office users.

**It's not just another digital widescreen. It's a ViewSonic.**



### DIGITAL HIGH CONTRAST WIDESCREEN

- > **Fast 5ms video response delivers superior picture clarity**
- > **OPTISYNC® multiple analogue/digital inputs**  
Multi-mode input technology supports both digital (DVI) and analogue (VGA) signals for ultimate compatibility and configuration flexibility.
- > **Full 20" viewable widescreen with 1680 x 1050 resolution**  
Displays a full, flat 20" viewable area with crisp, razor-sharp text and graphics.
- > **Ultra-high contrast ratio and brightness**  
1000:1 contrast ratio (typ.) and 300cd/m<sup>2</sup> brightness (typ.) deliver bright, vivid and saturated colours for realistic and natural images.
- > **Wide viewing angles**  
Ensures edge-to-edge consistent image performance by minimising contrast and colour shifts ideal for multiple viewers.
- > **Stylish slim-bezel design**  
An ultra-thin bezel lets you see more without taking up valuable desktop real estate.
- > **OnView® controls for superior screen adjustability**  
Screen adjustments can be made precisely via an easy-to-use on-screen menu.
- > **sRGB compliant**
- > **PC and Mac® compatible**
- > **TCO'03 and ENERGY STAR® qualified**



**VIEWSONIC**  
PRODUCTS, PROGRAMS,  
AND SERVICES

# VA2010wb

## 20" WIDESCREEN LCD MONITOR VALUE SERIES WITH 5MS VIDEO RESPONSE



ViewSonic Corporation's QMS & EMS have been registered to ISO 9001 & ISO 14001, respectively, by the British Standards Institution.

<b>LCD</b>	Type	20" Wide TN colour TFT active matrix WSXGA+ LCD
	Display Area	43.3cm horizontal x 27.1cm vertical, 51.1cm diagonal
	Pixel Pitch	0.258mm
	Optimum Resolution	1680 x 1050@60Hz
	Pixel Clock	165MHz
	Contrast Ratio	1000:1 (typ.)
	Viewing Angles	160° horizontal, 160° vertical (at 10:1) 170° horizontal, 170° vertical (at 5:1)
	Response Time	5ms (off-on-off) (typ.)
	Colour Support	16.2M colours (6-bit+2-bit FRC)
	Light Source	Long life, 40000 (min.)
	Brightness	300cd/m²
	Panel Surface	Anti-glare (3H)
<b>VIDEO INPUT</b>	Analogue	RGB analogue (0.7/1.0 Vp-p, 75 ohm)
	Digital	DVI-D (TMDS, 100 ohm)
	Frequency	F <sub>H</sub> : 24–82kHz, F <sub>V</sub> : 50–75Hz
	Synchronisation	H/V separate (TTL), composite, sync on green
<b>COMPATIBILITY</b>	PC	VGA up to 1680 x 1050 non-interlaced
	Mac¹	Power Mac™ up to 1680 x 1050 non-interlaced
<b>CONNECTOR</b>	Analogue	15-pin mini D-Sub (detachable cable)
	Digital	24-pin DVI-D (detachable cable)
	Power	3-pin AC plug (CEE22)
<b>POWER</b>	Voltage	AC 100–240V, 50/60Hz (auto switch), internal power supply
	Consumption	39 watt (typ.), <1 watt in power save mode
<b>ERGONOMICS</b>	Tilt	Down 5°, Up 20°
<b>CONTROLS</b>	Basic	Power, menu [1], up, down, select [2]
	OSD²	Auto image adjust, contrast, brightness, ViewMatch® colour adjust (sRGB, 9300K, 7500K, 6500K, 5400K, user RGB), information (resolution, H/V frequency, pixel clock, model number, serial number), manual image adjust (H/V position, H size, fine tune, sharpness), setup menu (language, resolution notice, OSD position, OSD timeout, OSD background), OSD/power lock, memory recall
<b>OPERATING CONDITIONS</b>	Temperature	0°C – 40°C
	Humidity	10% – 90% (non-condensation)
<b>DIMENSIONS</b>	W x H x D mm	481 x 399 x 155 (with stand)
		481 x 319 x 60 (without stand)
		553 x 468 x 210 (packaging)
<b>WEIGHT</b>	Net	4.9kg (with stand)
	Gross	6.3kg
<b>REGULATIONS</b>	CE, CB, TCO'03, TÜV/GS, TÜV/ERGO, ISO 13406-2 (pixel failure class II), GOST-R, Hygienic, UL, cUL, FCC-B (ICES), ICES-003B, SASO, ENERGY STAR, C-Tick, KTL/MIC, BSMI, PSB, MPR II, VCCI, TÜV-S, CCC, WEEE, RoHS	
<b>POWER MANAGEMENT</b>	Meets TCO'03 and ENERGY STAR standards	
<b>SECURITY</b>	Kensington security port	
<b>WALL MOUNT</b>	VESA FDMI 100mm x 100mm	
<b>PACKAGE CONTENT</b>	LCD Monitor, power cable, 15-pin VGA video cable, Quick Start Guide, ViewSonic Wizard CD-ROM (User Guide/drivers) (multi-language)	
<b>WARRANTY</b>	Please see: <a href="http://www.viewsoniceurope.com/UK/Support/warranty.htm">www.viewsoniceurope.com/UK/Support/warranty.htm</a>	

### ViewSonic Europe Limited/UK

Riverside House  
7th Floor  
2a Southwark Bridge Road  
London, SE1 9HA  
United Kingdom

Tel: +44 (0) 207 921 2200  
Fax: +44 (0) 207 921 2201

### ViewSonic Germany

Hanns-Martin-Schleyer-Straße 18A  
1 allée des Bas Tilliers  
Germany

Tel: +49 (0) 21 54 91 88 0  
Fax: +49 (0) 21 54 91 88 10

### ViewSonic France

Parc des Barbannières  
1 allée des Bas Tilliers  
92230 Gennevilliers  
France

Tel: +33 (0) 1 41 47 49 00  
Fax: +33 (0) 1 41 47 49 10

### ViewSonic Corporation

381 Brea Canyon Road  
Walnut  
California 91789-0708  
USA

Tel: +1 909 869 7976  
Fax: +1 909 869 7958

**ViewSonic Belux**  
**ViewSonic Denmark**  
**ViewSonic Finland**  
**ViewSonic Italy**  
**ViewSonic MEA**  
**ViewSonic Netherlands**  
**ViewSonic Norway**  
**ViewSonic Spain**  
**ViewSonic Sweden**

Tel: +32 (0)56 85 26 27  
Tel: +45 70 22 11 71  
Tel: +358 20 7120 860  
Tel: +39 02 73 95 50 22  
Tel: +971 (0) 4 88 11 871  
Tel: +31 (0)20 491 9254  
Tel: +47 (0) 22 88 17 60  
Tel: +34 (0) 91 63 05 339  
Tel: +46 (0) 8 50 71 30 00

¹ May require optional Mac adapter. ² Some features may not be available on all inputs.