

SHARP

LM64K112

Large Size Graphic Type LCD Module
(FA/POS/Measuring instruments)

Features

- 15 cm [6"] VGA format
- Transflective B/W display
- Thin structure (5.8 mm) & lightweight (145 g)
- Wide temperature range
(Topr: 0°C to +50°C, Tstg: -25°C to +70°C)

Specifications


Parameter		Unit
Display size	15 [6]	cm ["]
Dot format (H x V)	640 x 480	dot
Dot Pitch (H x V)	0.19 x 0.19	mm
Active area (H x V)	121.6 x 91.2	mm
Panel type	DFSTN	-
Panel mode	Transflective	-
Color	B/W	-
Contrast ratio	13 : 1/15 : 1*1	-
Response Time	500	ms

Parameter		Unit
Brightness	60	cd/m ²
Duty Ratio	1/240	-
Backlight type	1CCFT(E)	-
Power consumption	1 400	mW
Outline dimensions (W x H x D _(max.))	167.7 x 122.8 x 5.8	mm
Weight	145	g
Operating temperature	0 to +50	°C
Storage temperature	-25 to +70	°C

*1...Contrast ratio : Reflective / Transmissive

Outline Dimensions

unit : mm



In the absence of confirmation by device specification sheets, SHARP takes no responsibility for any defects that may occur in using any SHARP devices shown in catalogs, data books, etc. Contact SHARP in order to obtain the latest device specification sheets before using any SHARP device. Specifications are subject to change without notice for improvement.