



HF Reader System Series 6000

S6700 Multi-Protocol Transceiver IC



The S6700 Multi Protocol Transceiver IC enables a broad range of 13.56MHz RFID interrogator designs for portable and stationary readers. This low power consumption device supports multiple RF communication protocols, minimizes onboard power requirements and reduces parts count in a final reader product.

| Part number | RI-R6C-001A |
|--------------------------------------|---|
| Operating Frequency | 13.56MHz |
| Supported RF Communication Protocols | <ul style="list-style-type: none"> - Tag-it HF - ISO 15693-2 (e.g. Tag-it HF-I) - ISO 14443-2 (Type A) - Transparent (directly switched according to input pin) |
| Operating Voltage | 3.3V - 5V DC \pm 10% |
| Current Consumption | Transmit: < 200 mA Stand-by: - Oscillator on < 15 mA - Oscillator off < 50 μ A |
| Transmitter power | 200mW at 5V DC operating voltage |
| Transmitter modulation | ASK, 10% to 100% selectable through external components |
| Antenna Impedance | 50 Ohm at 13.56MHz |
| Receive channels | ASK 423.75kHz, ASK 847kHz, FSK 423.75kHz/484.29kHz selectable |
| Communication Interface | Serial interface, CMOS compatible |
| Operating Temperature | -40°C to +85°C |
| Storage Temperature | -55°C to +125°C |
| Package / Pincount | SSOP 20 |
| Packing / Delivery | Tape-on-Reel, 1500 units per reel |



Recommended application schematic

Pin description

| Pin | Symbol | Description |
|-----|----------|--|
| 1 | VDD_TX | Transmitter power supply |
| 2 | TX_OUT | Output transistor drain connection |
| 3 | R_MOD | External resistor to set 10% modulation depth mode |
| 4 | VSS_TC | Transmitter section ground |
| 5 | XTAL1 | Pin 1 of Xtal resonator |
| 6 | XTAL2 | Pin 2 of Xtal resonator, external clock input |
| 7 | VSS_DIG | Digital section ground |
| 8 | XTAL_CLK | Buffered output of Xtal oscillator |
| 9 | Not used | Grounded for normal operation |
| 10 | Not used | Grounded for normal operation |
| 11 | DOUT | Data output for serial link |
| 12 | VDD_DIG | Digital section power supply |
| 13 | DIN | Data input for serial link |
| 14 | M_ERR | Manchester Protocol error flag |
| 15 | SCLOCK | Serial link clock |
| 16 | Not used | Leave open for normal operation |
| 17 | VDD_RX | Receiver section power supply |
| 18 | Not used | Leave open for normal operation |
| 19 | VSS_RX | Receiver section ground |
| 20 | RX_IN | Receiver input |

For more information, contact the sales office or distributor nearest you. This contact information can be found on our web site at: <http://www.ti-rfid.com>

Texas Instruments reserves the right to change its products and services at any time without notice. TI provides customer assistance in various technical areas, but does not have full access to data concerning the uses and applications of customers products. Therefore, TI assumes no responsibility for customer product design or for infringement of patents and/or the rights of third parties, which may result from assistance provided by TI.