

# ViewSonic®

## PJ1065 Projector

### *High-Brightness Series*



- **Professional high-brightness 3,500-lumen projector**
- **Native 1024x768 XGA resolution**
- **Easy setup and auto tuning**  
One-touch setup button for fast, easy sync and sharp focus.
- **Whisper-mode operations**  
Whisper-mode for extended lamp life up to 4,000 hours\* and low noise output.
- **Displays HDTV signals**  
Including 480i, 480p, 575i, 720p, and 1080i.
- **Progressive scan video**  
Reduces flicker and artifacts for stable, clear video images.
- **Three-year limited warranty**  
Covered by a three-year limited warranty and first year Express Exchange® program.\*\*
- **Industry-leading one-year lamp warranty**  
Extended-life lamp, warranted for a full year.\*\*

### **3,500-lumen high-brightness multimedia projector.**

ViewSonic's multimedia PJ1065 XGA projector offers 3,500 lumens of brightness and a 1024x768 XGA resolution, making it the ideal choice for any setting including conference rooms, boardrooms and lecture halls. Multimedia presentations are a snap with a variety of data and video inputs capable of showing any type of electronic content. Progressive scan stabilizes video images creating a true, movie-like picture. The PJ1065 is also wall/ceiling mountable for a wider variety of installation settings. If you're looking for a high-performance, full-featured projector, look to the ViewSonic PJ1065.

- **Component video for enhanced video quality**  
View HDTV signals and other video signals at maximum performance levels.



**ViewSonic®**  
*See the difference.®*

# ViewSonic®

## PJ1065 Projector



- **Horizontal and vertical keystone correction**

Square your image from any angle.

- **Picture-in-picture capability**

View video and computer data simultaneously for spectacular multimedia presentations.

- **RGB-out capability**

Allows you to view projected images on a monitor, too.

- **Multiple RGB inputs for greater flexibility**

Connect two computers at once for dynamic presentation.

- **GSA compliant**

- **Free industry-leading 24/7 customer support†**

- **Accessories expand your options**

Hard carrying case w/cart function (PRJ-HCA-002)

Spare lamp (PRJ-RLC-002)

Ceiling/wall mount kit (PM-1065)

Express Exchange® service (EE-CR-02)



ViewSonic Corporation's QMS & EMS have been registered to ISO 9001 & ISO 14001, respectively, by the British Standards Institution.

### HIGH-BRIGHTNESS MULTIMEDIA PROJECTOR

LCD	<b>Type</b>	1.3" Polysilicon (x3) stripe pixel TFT active matrix
	<b>Pixel Format</b>	1024 horizontal x 768 vertical
	<b>Lens</b>	Power, zoom/focus (1:1.3x)
DISPLAY	<b>Size</b>	30"–300" (measured diagonally)
	<b>Focus Distance</b>	1.1–11.0M (3.6'–36.0')
	<b>Lamp</b>	275W UHB compact, 4,000 hour rating*
	<b>Brightness</b>	3,500 lumens
AUDIO	<b>Contrast Ratio</b>	500:1
	<b>Speakers</b>	Stereo
VIDEO INPUT	<b>Power</b>	1.2W x2
	<b>Analog</b>	RGB analog, NTSC, PAL-M, PAL-N, SECAM, HDTV
	<b>Sync</b>	Separated and composite
COMPATIBILITY	<b>Frequency</b>	Fh: 15~80kHz; Fv: 56~120Hz
	<b>PC</b>	Analog: from VGA up to SXGA Digital: from VGA up to SXGA
	<b>Mac®††</b>	Analog: up to SXGA (may require Mac Adapter) Digital: up to XGA (may require Mac Adapter)
CONNECTOR	<b>RGB Input</b>	15-pin HD, D-sub (x2)
	<b>RGB Output</b>	15-pin HD, D-sub (x1)
	<b>DVI Input</b>	HD 24 PDVI-D (x1)
	<b>Composite Video</b>	RCA (x1)
	<b>Component Video</b>	RCA Jack (x3)
	<b>S-Video</b>	Mini-Din 4 pin (x1) RCA (x2) and 3.5 mm (x1)
	<b>Audio (In/Out)</b>	In RCA (x2) and 3.5mm (x2); Out 3.5mm (x1)
	<b>Control</b>	15-pin D-sub (x1)
POWER	<b>USB</b>	USB upstream (x1)
	<b>Voltage</b>	90–132V AC/198–264V AC
	<b>Frequency</b>	50–60Hz (universal)
CONTROLS	<b>Consumption</b>	415W (typ)
	<b>Basic</b>	Standby on/off, menu (left, right, up, down), input, reset, mute, zoom, focus, indicator (lamp, power, temp)
	<b>Remote</b>	Standby on/off, video, laser, blank, RGB, disk pad, auto, mouse, menu, position, menu select (left, right, up, down), PIP, reset, freeze, magnify (+, -, off), volume (up, down), mute, focus (+, -), zoom (+, -)
OPERATING CONDITIONS	<b>OnView®</b>	Brightness, contrast, V. position, H. position, H. phase, H. size, color balance (red), color balance (blue), aspect ratio, auto, RGB, keystone, blank, mirror, start up, PIP, volume, menu color, language, auto off, sync on green
	<b>Temperature</b>	32°F–95°F (0°C–35°C)
	<b>Humidity</b>	10%–85% (non-condensing)
DIMENSIONS (W x H x D)	<b>Physical</b>	289mm x 139mm x 345mm (11.4" x 5.5" x 13.6")
	<b>Net</b>	6.5 kgs. (14.3 lbs.)
WEIGHT	<b>Gross</b>	13.7 kgs. (30.2 lbs.)
	<b>REGULATIONS</b>	UL, FCC-B, c-UL, CE, TUV/GS, CB Report, VCCI, BSMI, PCT
OTHER	<b>WARRANTY</b>	Mirror reverse image, upside down image, digital keystone correction, DDC 1/2B
		Three-year limited warranty on parts and labor, first year Express Exchange® service, one-year warranty on lamp.**



**ViewSonic®**  
See the difference.®

381 Brea Canyon Road, Walnut, CA 91789 • Phone (800) 888-8583 or (909) 444-8888 • Fax (909) 839-7922 • E-mail: SalesInfo@ViewSonic.com • ViewSonic.com

\*Running whisper-mode exclusively can extend lamp life up to 4,000 hours. \*\*Lamp warranty subject to terms and conditions, verification and approval. Applies to manufacturer's installed lamp only. All accessory lamps purchased separately are warranted for 90 days. For Express Exchange program details, visit ViewSonic.com. †Excluding major U.S. holidays. ††Adapter may be required. Analog adapter available from ViewSonic. Specifications subject to change without notice. Selection, offers and programs may vary by country; see your ViewSonic representative for complete details. Corporate names, trademarks stated herein are the property of their respective companies. Copyright © 2003 ViewSonic Corporation. All rights reserved. [10159-068-01/03] PJ1065-2