ViewSonic® VPW425 Plasma TV Monitor

With NextVision™ Technology



Captivate audiences with vibrant high-definition images.

The ViewSonic VPW425 plasma TV monitor with built-in TV tuner brings stunning video signals into your boardroom or home. Revolutionary NextVision technology brings images to life with stunning brightness and depth. And XtremeView performance with viewing angles up to 160° delivers vivid images with unmatched picture quality. Picture-in-picture and split-screen picture-on-picture capabilities make it easy to view multiple windows at once. Professional-grade features and progressive scan allow you to tailor images to your particular application. Built-in virtual surround sound speakers round out the multimedia experience with a clean, professional look. Get the powerful, slim (3.7" depth) plasma display with a professional flare — the ViewSonic VPW425.

Bright color-rich NextVision technology

Revolutionary advances in plasma technology deliver even more vivid and stunning brightness to your viewing experience.

Ultra-slim design

3.7" depth for virtually no footprint; superb for any location.

XtremeView[™] performance

Up to 160° viewing angles both horizontally and vertically.

• 852x480 SVGA resolution

Compatible with SVGA up to UXGA.

- Picture-in-picture, picture-onpicture and split-screen capability
- Accurate true color and images
 Distortion-free display.
- Built-in TV tuner
- Built-in speakers and virtual surround sound for a rich audio experience
- S-video, component and DVI for exceptional image quality
- Progressive scan for enhanced video performance



ViewSonic® VPW425 Plasma TV Monitor

POWER

With NextVision™ Technology



Display Area
Aspect Ratio
Viewing Angle
Pixel Pitch
Color Depth

36.2" (horizontal) x 20.4" (vértical), 41.5" diagonal
16:9
160° horizontal, 160° vertical
1.08mm (H) x 1.08mm (V)
8-bits/color (16.7 million colors)

INPUT CONNECTOR **Computer**Audio/Video

Audio/Video

1X audio mini jack

INPUT SIGNAL Frequency fH:31–91kHz; fv:50–85 Hz
Audio/Video Built-in TV tuner, built-in speakers, surround sound

capability **PC/Mac®***VGA, SVGA, XGA, SXGA

COMPATIBILITY

PC/Mac®*

Video

VGA, SVGA, XGA, SXGA

NTSC, NTSC 4.43 with progressive scan, optional PAL TV tuner available

Scanning Format 480i, 480p, 720p, 1080i
Voltage AC (100–240 VAC) +/– 10%

Frequency 50/60Hz Consumption 370W (typ)

USER CONTROL

Display Unit

Remote Control

Main power, on/off, input select, menu, adjustment
Power on/off, mute, display, menu, input select, volume,

video wide, zoom, panorama, aspect ratio, menu, adjustment, recall, PIP, POP, source, position, still,

 channel, TV tuning

 OPERATING CONDITION
 Temperature Humidity
 23–113° F (0–40° C)
 20–80% (non-condensing)

 DIMENSIONS (W x H x D)
 Physical
 1040mm x 650mm x 95mm (display only)

 40.9" x 25.6" x 3.7"

 (W x H x D)
 40.9" x 25.6" x 3.7"

 WEIGHT
 Net Gross
 77.2 lbs. (with stand)

 REGULATIONS
 UL. FCC-B. CSA

ACCESSORIES INCLUDED Power cord, remote control, batteries, display stand WARRANTY One-year limited warranty on parts and labor.



technical and customer support**

Free industry-leading 24/7

image shadowing, precise white balance adjustment, external RS-232C[†] control interface.

Optional Accessories

Flush Wall Mount Tilt Wall Mount Ceiling Wall Mount ATA Shipping Case





ViewSonic Corporation's QMS & EMS have been registered to ISO 9001 & ISO 14001, respectively, by the British Standards Institution.



