

1-800-52-ALPHA
[Home](#) > [Products](#) > [Tubing and Accessories](#) > [FIT® Wire Management](#) > [Sleeving](#) > **PIF2409**

Part #	Material	ID	Expanded ID	Temperature	Colors	Ratings
PIF2409	Fiberglass	0.118	0.148	-60 to 616	Natural	NEMA VS-1, UL 1441, UL VW-1

PART NO. PIF2409



[Check inventory](#) | [Email](#) [Request a Sample](#)

Alpha has a sleeving for your application with options that are great for flexible wire harnesses, heat protection, and defense against chemicals or abrasion.

Check out our new [Rugged Sleeving](#) line for the most hazardous applications.

CERTIFICATE OF COMPLIANCE

To Whom It May Concern:

Alpha Wire Part Number: PIF2409

PIF2409 , RoHS-Compliant Commencing With 10/1/2004 Production

*This document certifies that the Alpha part numbers cited above are manufactured in accordance with Directive 2002/95/EC of the European Parliament and of the Council of 27 January 2003, better known as the RoHS Directives, with regards to restrictions of the use of certain hazardous substances used in the manufacture of electrical and electronic equipment. The reader is referred to these Directives for the specific definitions and extents of these Directives . **No Exemptions are required for RoHS Compliance on this item.***

News [View Archive](#)

9.22.10
[Alpha Wire Extends Rugged Sleeving Line](#)
FIT® Rugged Sleeving products are designed for wire and cable applications that demand superior abrasion resistance, high operating temperatures, and/or resistance to oils, solvents, and chemicals.



7.14.10
[Alpha Wire Deploys Military-Grade Wire and Cable](#)
Premium cable and wire designed for the most hazardous conditions in the most unforgiving environments for steadfast military operation.

Subscribe to our Newsletter

SUBSCRIBE

Substance	Maximum Control Value
Lead	0.1% by weight (1000 ppm)
Mercury	0.1% by weight (1000 ppm)
Cadmium	0.01% by weight (100 ppm)
Hexavalent Chromium	0.1% by weight (1000 ppm)
Polybrominated Biphenyls (PBB)	0.1% by weight (1000 ppm)
Polybrominated Diphenyl Ethers (PBDE) ,	
Including Deca-BDE	0.1% by weight (1000 ppm)

The information provided in this document and disclosure is correct to the best of Alpha Wire's knowledge, information and belief at the date of its release. The information provided is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it will become part of. The intent of this document is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product .

Authorized Signatory for the Alpha Wire Company:



Dave Watson, Director of Engineering & QA

10/11/2010

