

MP721 DLP Projector

Features

- Texas Instruments DLP™ Projection System
- Native XGA (1024 x 768) resolution
- 2500 ANSI Lumens
- 2000:1 contrast ratio
- 54"@2m wide-angle lens
- 31" to 300" image size
- HDTV connectable up to 1080i
- Less than 24dB audible noise (Eco mode)
- 5 segment colour wheel
- Colour matching technology
- 9 sets of application modes
- Hot Key for "Mode" selection
- Blackboard mode
- Power saving "Auto Off"
- Up to 4000 hours lamp life (Eco mode)

The BenQ MP721 is designed to provide exquisite picture quality for your presentations, with a high brightness of 2500 ANSI lumens and a high 2000:1 contrast ratio. The MP721 delivers 1024 x 768 native resolution and includes a 5 segment colour wheel which balances true colour saturation while maximising colour accuracy for a crystal-clear, vivid image reproduction.

The MP721 comes equipped with a broad selection of features and adjustment options, including 9 unique built-in application modes, a presentation timer, panel key lock and power-saving auto-off. The projector also features an advanced cooling system which creates an effective sound baffle that is able to reduce the audible noise to a low 24dB, the level of sound lower than the human whisper, thus ensuring an undisturbed meeting environment.



Specifications[#]

Projection System

Digital Micromirror Device (DMD)

Native Resolution

Maximum Resolution Supported

Brightness

Contrast Ratio

Colour Reproduction

Image Size

Throw Ratio

Aspect Ratio

Projection Position

Lamp

Lamp Life

Audible Noise

Input Terminals

HDTV supported timings

Audio Output

Control Terminals

Video Systems

Dimensions (mm) (W x H x D)

Weight (kg)

Features

Standard Accessories

Optional Accessories

DLP™ Technology by Texas Instruments®

XGA DDR DMD™ x 1

XGA (1024 x 768)

1280x1024 supported

2500 ANSI Lumens

2000:1 (Full on/Full off)

Full 16.7 million colour palette

31" to 300"

54" @ 2m (54" @ 6.6 feet)

4:3 native / 16:9 selectable

Front / Rear / Table / Ceiling

200W NSH

Up to 3000/4000 hours (Normal/Economic mode)

<28/24dB (Normal/Economic mode)

D-Sub, DVI-I, Composite Video, S-Video, PC Audio,

Video L/R audio, Component Video via D-Sub

576i/p, 720p and 1080i

2 Watt Single Speaker

USB, 9 pin Din

NTSC, PAL, SECAM

278 x 100.3 x 220.2

2.67

Power on/off tone / Presentation Timer / Panel Key Lock

/ Auto Adjustment / Freeze / Blank / Auto Off / Quick

Cooling / Resolution Reminder / Blackboard mode /

Security password / Mute / Auto Source Detection /

HDTV compatible / Macintosh® Compatible / "Mode"

hot key / "Q?" hot key for FAQ / MyScreen

User's Manual / Quick Start Guide / CD Manual / Remote

Control / Battery for R/C / Soft Carry Case / VGA Cable /

Power Cord / Video Cable

Link Pro - 802.11a/b/g Wireless Module / Ceiling Mount /

Lamp

