BenQ MX850UST

Digital Projector





JUST PROJECTORS

4 West End Road Mortimer

Berkshire





















Display Technology	DLP® by Texas Instruments®			
Native Resolution	XGA (1024 x 768)	,		
Resolution Supported	VGA (640 x 480) to UXGA (1600 x 1200)			
Brightness	2500 ANSI Lumens			
Contrast Ratio	13,000:1 (Full on / Full off)			
Image Size	60" to 300"			
Throw Ratio	0.45 (81" @ 0.74 m)			
Zoom Ratio	Fixed			
Keystone correction	ID, Vertical +/- 15 degrees (manual)			
Lens	F = 2.65			
Lamp Life*	230W, 3500 / 5000 hours (Normal / Economic mode)			
Lamp Warranty	12 months or 2,000 cumulative hours whichever comes first			
Operational Noise	33 / 27 dB (Normal / Economic mode)			
Displayable Colours	Full 1.07 billion color palette			
Aspect Ratio	4:3 native, 5 aspect ratio selectable			
	31 ~ 102 kHz			
Horizontal Frequency				
Vertical Scan Rate	23 ~ 120 Hz	2 Minus kana in (Mini kata)		
Interface	Computer in (D-sub 15pin)			
	(shared with Component)	·		
	Monitor out (D-sub 15pin) x	, - , , , , , , , , , , , , , , , , , ,		
	Composite Video in (RCA) x			
	S-Video in (Mini DIN 4pin) x	, , ,		
	Audio in (Mini Jack) x 2	(USB Download & Page up/down)		
	Audio L/R in (RCA) x 2	DC 12V Trigger (3.5mm Jack) x 1		
	Audio out (Mini Jack) x 1	RS232 (DB-9pin) x I		
Compatibility	Video Compatibility	NTSC / PAL / SECAM		
	HDTV Compatibility	480i / 480p / 576i / 576p / 720p / 1080i / 1080p		
	PC: 120Hz Frame Sequential 3D for resolutions up to XGA 3D Compatibility PC: 60Hz Top-bottom 3D for resolutions up to SXGA+			
Dimensions (HxWxD)	236.9 x 339 x 322.8 mm			
Weight	Net weight: 5.3 kg. Gross weight: 6.5 kg.			
Auto Switching Power Supply	100 to 240 VAC, 50/60 Hz			
Power consumption	321W, Standby <1W			
On Screen Display Languages	Arabic / Bulgarian / Croatian / Czech / Danish / Dutch / English / Finnish / French / German / Greek /			
	Hindi / Hungarian / Indonesian / Italian / Japanese / Korean / Norwegian / Polish / Portuguese / Romanian			
	/ Russian / Simplified Chinese / Spanish / Swedish / Thai / Traditional Chinese / Turkish (28 Languages)			
Application Modes	Dynamic / Presentation / sRGB / Cinema / User 1 / User 2			
Application Modes	BrilliantColor™			
Functions		High Altitude Mode		
	Closed Captioning	Quick Auto Search		
	3D Color Management	Wall Color Correction		
	Digital Zoom (x2)	Blank		
	Freeze	Auto Off		
	HDTV Compatible	Security Password		
	SRS Certified	Security Bar + K-locker slot		
	Windows 7 Certified	Presentation Timer		
Accessories Included	Quick Start Guide	VGA (D-sub 15pin) Cable		
	User Manual CD	Power Cord		
	Remote Control w/ Battery			
Accessories Optional	Wall Mount (T/R 0.4)	Presentation Plus		
	3D Glasses	Spare Lamp Kit		
* I t 1:f t ::ll	ding on anying property of conditions			

^{*} Lamp life results will vary depending on environmental conditions and usage.

All specifications are subject to change without notice. Available models (specs inc.) may vary from different regions.

