

Model XJ-S32

2300 ANSI Lumens

Versatile

Brightness (2300 ANSI Lumens) and the industries slimmest projector, only 1.7" high and 3.9 lbs, combine for the ultimate projection solution. Small and bright enough for the road warrior, the 2x Short throw power zoom lens and RS-232 control functionality are ideal for corporate and educational installations.

Outstanding Image Quality

DLP Display Technology from Texas Instruments and XGA native resolution combine for superior brightness and image quality. Multimedia capable the Super Slim Projector can project data images up to UXGA (1600 x 1200) and HD video (480i/480P/720P/1080i/1080P).

Short Throw 2X Power Zoom and Focus Lens

Whether you are in a small office or a large boardroom the Super Slim's 2X power zoom lens gives you the flexibility to easily position the projector. Large screen projection is possible in any room and the short throw lens (1.4-2.8 throw ratio) can project an image from as close as 3' and up to 28' back. Image adjustment can be easily



control or via an
RS-232 control



RS-232 Control

No more compromising. The Super Slim projector now incorporates RS-232C control for easy system integration. The Super Slim's low profile and elegant design looks great in any Boardroom Conference or Classroom. Compatible with industry standard control systems the Super Slim projectors boast an available command set, which includes Power On/Off, Input select and Lens Zoom and Focus.

Key Features

- DLP Display Technology from Texas Instruments
- Native XGA (1024 x 768) Resolution, UXGA max
- Multimedia 1080i/P Compatible
- 3 years Parts and Labor Warranty (180 day warranty on lamp)
- Built-in 1watt Speaker
- Only 3.9 lbs and 1.7" thin.

SUPER SLIM
PROJECTOR

XJ-S32

BASIC SPECIFICATIONS		
*Brightness	Eco-Mode: OFF	2300 ANSI Lumens
	Eco-Mode: ON	1700 ANSI Lumens
*Contrast Ratio	Telephoto Mode	1800:1
Lamp	High-pressure Mercury Lamp	210W
Estimated Lamp Life		Up to 2,000 Hours
Keystone Correction	Auto	+30°
	Manual	±30°
Projection Lens Projection Screen Size		2X Power Zoom and Focus 15 ~ 300-inch
Projection Range	60-inch Screen	5.57 ft. to 11.15 ft.
	100-inch Screen	9.18 ft. to 18.37 ft.
	Minimum/Maximum	2.75 ft. / 28.2 ft.
	Projection Ratio	1.4-2.8:1
Projection System		DLP® System
Display Element	Device Type	0.55-inch DLP® Chip
	Native Resolution	XGA (1024 x 768) 786,432 Pixels
Computer Signal	Maximum	UXGA (1600 x 1200)
Compatibilty		(Compressed)
	Resolutions	SVGA, XGA, WXGA, SXGA, SXGA+, WXGA+, WSXGA+, UXGA
	Hor./Vert. Frequency	fH 31.5-91.1 kHz / fV 56-85 Hz
Video Signal Compatibilty	Video Systems	NTSC / PAL / PAL-N / PAL-M / PAL60 / SECAM
	DTV/HDTV	480i / 480P / 576i / 576P / 720P / 1080i / 1080p
Color Reproduction		Full Color (16.77 Million Colors)
Power Source		AC100~240V, 50/60Hz
Power Consumption	Operating	270W (Eco-Mode: 220W)
	Standby	1.2W (100~120V),
Usage Environment		1.8W (220~240V)
	Operating Temperature	41-95°F (5~35°C)
	Operating Humidity High Altitude Mode	Yes (for Operation 5000 ft. above
	High Attitude Mode	Sea Level)
INTERFACE TERMINALS		_
RGB/Component		Mini D-Sub 15 pin x 1
Video Input		Also use as YcbCr/YPbPr Input
Audio	Input	3.5mm Mini-jack
	Output	1 W Speaker 3.5mm Mini-jack
		(Shared with Audio Input)
Video	Input Terminals	Composite: 3.5mm Mini-jack
	mpat remmate	(Sharing Audio Terminal),
		YCbCr/YPbPr
Control	Terminal	RS-232C Adapter Cable (YK-5)
OTHERS		Required and Sold Separately
Dimensions		10.63" x 7.83" x 1.69" Including
		Projections
		(1.26" at Thinnest Point)
Weight		3.97 lbs.
Limited Warranty*		3 years Parts and Labor, 180 Day
		Lamp Warranty *See Warranty
		Statement Included with Product
Security Compatibility	Kensington Compatible	for Complete Details Yes
Security Compatibility	Power ON Password	Yes
Ceiling Mount	1 over out according	Yes
Full Function IR		Yes
Remote Control		
Remote Controller Range		16.40 ft. Maximum
Included Accessories		Wireless Remote Controller
		(YT-35), RGB Cable, AV Cable,
		AC Power Cord, Projector Soft
		Case, Accessory Soft Case,
Ontional Assessarias		Manual on CD-ROM
Optional Accessories		Replacement Lamp (Part # YL-3A) RS-232C Adapter (Part # YK-5)
Packing Information	UPC Code	0-79767-18310-3
. soming information	Carton Dimensions	11.5" W x 6.8" H x 15" D
	Carton Weight	8.2 Lbs.
(Shipping Weight)	3	







RS-232 Adapter (Optional and Sold Separately)



Ceiling Mount Commercially Available (Optional and Sold Separately)

visit: www.superslimprojector.com



CASIO is a registered trademark of CASIO Computer Co., Ltd. in Japan. DLP, the DLP logo and the DLP medallion are trademarks of Texas Instruments. XGA is a registered trademark of International Business Machines Corporation in the United States. Other product names or company names on this specification brochure are either trademarks or registered trademarks of their respective owners. Specifications subject to change without notice.