

Depend on the higher performance and Speed, Hisense SC188AT helps on the productivity. Higher quality cut your maintenance cost accordingly.



Hisense Scanner SC188AT



Highlights

- Outstanding Value
- Superior motion tolerance
- Multiline mastering scan pattern
- Engineered for reliability

Increase productivity with higher performance and Speed

Hisense SC188AT Scanner increases your accuracy and productivity. At a retailer checkout counter, in pharmacies, hospitals and warehouse environments, you need to capture and process data very quickly, SC188AT can help to speed through barcodes, even barcodes in poor condition effortlessly. Also, the scanner's high-quality construction cut your maintenance costs and reduce downtime.

In the meanwhile, Handheld Scanner is intuitive and increases productivity. Even novice users can speed up the checkout process and increase customer satisfaction in retail, warehouse and pharmacies environments.

High Reliability & Stability

Depend on the high quality, SC188AT offers you high reliability and stability performance. it will minimize your chances of downtime.

Hisense Scanner SC188AT with high performance Handheld Scanner is designed for using in retail, office and warehouse constantly. With reliability you can depend on, the scanner keeps running even after being dropped multiple times.

Also, Hisense will offer the maintenance plan and support strategy even for the durable products .

Hisense Scanner SC188ATFeatures

model	SC188AT(auto detection)
voltage	DC 5±0.25 V
power	425 mW (operation) ; 500 mW (transient max)
current	85 mA (operation) ; 100 mA (transient max)
Light source	Visible laser diode , 630-650 nm
Laser grade	E N60825-1 , class 1
Decode speed	100 cycle/ second
Scan angle	±60°、±6 5°、±42° (left-right、front-back、turn)
Minimum barcode width	0.08 mm (3mil)
Decode capability	UPC-A , UPC-E , EAN-13 , EAN-8 , ISBN/ISSN , 39 code , 32 code , MSI/Plessey , UK/Plessey , UCC/EAN 128 , GS1 DataBar
Prompt method	speaker , LED light
interface	PS2 /RS-232/USB
trigger	manual , auto detection (optional)
dimension	depth×length×height : 9.5cm×6.7cm×15.4cm
weight	148 g (no cable)
cable	2m
connector	RJ-45
case	ABS+PC
temperature	0°C ~ 45°C (operation) ; -40°C ~ 60°C (storage)
humidity	5 % ~ 90%
Anti-shock	From 4m drop to mattress
setup	Manual(scan the setting code in turn)
Program update	Online