IBM XIV Storage System



XCLI Utility User Manual

Version 10.2.1

IBM XIV Storage System



XCLI Utility User Manual

Version 10.2.1

Note

Before using this information and the product it supports, read the information in "Notices" on page 15.

This edition applies to version 10, release 2 modification 1, of IBM XIV Storage System, and to all subsequent releases and modifications until otherwise indicated in new editions.

This edition replaces GA32-0638-02.

© Copyright IBM Corporation 2009, 2010. US Government Users Restricted Rights – Use, duplication or disclosure restricted by GSA ADP Schedule Contract with IBM Corp.

Contents

Figures v
About this guide
Who should use this guide
Conventions used in this guide
Publications and related information
Getting information, help, and service
Ordering publications
Sending your comments
Chapter 1. Overview of the IBM XIV
Storage System command-line interface. 1
Interactive and basic modes \ldots \ldots \ldots \ldots \ldots 2

Chapter 2. Getting started with XC	CLI	•	. 3
Installing the XCLI			. 3
Starting the XCLI			. 4
Starting the XCLI on a Windows system			. 4
Starting the XCLI on a Linux system .			. 5
Exiting an interactive XCLI session			. 5
Interactive mode features			. 5

Understanding the command syntax		
Command syntax quick reference Syntax example		
Chapter 3. Using the XCLI	• •	9
Using identification parameters		9
User and password parameters		
Defining XCLI configurations.		
Display options		
Using display options		11
Table display options . . .		
Running commands in batch mode		
Displaying XCLI help and version		. 14
NI		4 -
Notices		. 15
Trademarks		. 17
Glossary	•	. 19
Index		21
	•	. 21

Figures

- 1.

About this guide

This document describes how to use the IBM[®] XIV[®] Storage System command-line interface (XCLI) to invoke XCLI utility and system commands.

Who should use this guide

This publication is for personnel that are responsible for administering IBM XIV Storage Systems.

Conventions used in this guide

These notices are used to highlight key information.

Note: These notices provide important tips, guidance, or advice.

Important: These notices provide information or advice that might help you avoid inconvenient or difficult situations.

Attention: These notices indicate possible damage to programs, devices, or data. An attention notice appears before the instruction or situation in which damage can occur.

CAUTION:

These notices indicate a situation that is potentially hazardous to people because of some existing condition or where a potentially dangerous situation might develop because of some unsafe practice.

DANGER

These notices indicate a situation that is potentially lethal or extremely hazardous to people. For example, after a computer side panel is removed, exposed high-voltage wires might be lethal.

Publications and related information

Product manuals, other IBM publications, and websites contain information that relates to the IBM XIV Storage System.

To view a PDF file, you need Adobe Acrobat Reader, which can be downloaded for free from the Adobe website (www.adobe.com/products/acrobat/readstep.html) website.

Information centers

From the IBM XIV Storage System Information Center website (publib.boulder.ibm.com/infocenter/ibmxiv/r2/index.jsp), you can browse all product documentation.

Publications

Information that is available in the information center is also available in a set of publications, in PDF format.

IBM XIV Storage System

• IBM XIV Storage System Product Overview (publib.boulder.ibm.com/ infocenter/ibmxiv/r2/topic/com.ibm.help.xiv.doc/docs/GA32-0791-02.pdf)

This document contains an overview of the IBM XIV Storage System hardware and software.

• IBM XIV Storage System Planning Guide (publib.boulder.ibm.com/ infocenter/ibmxiv/r2/topic/com.ibm.help.xiv.doc/docs/GA32-0770-05.pdf)

This document defines installation requirements for IBM XIV Storage System. It is important to ensure that you meet all requirements to guarantee a fast and reliable installation.

• IBM XIV Storage System Host Attachment Guides

These documents provide information about attaching host systems to the IBM XIV Storage System:

- Host System Attachment Guide for AIX (publib.boulder.ibm.com/ infocenter/ibmxiv/r2/topic/com.ibm.help.xiv.doc/docs/hag_1_5_x/ GA32-0643-06.pdf)
- Host System Attachment Guide for HP-UX (publib.boulder.ibm.com/infocenter/ibmxiv/r2/topic/ com.ibm.help.xiv.doc/docs/hag_1_5_x/GA32-0645-02.pdf)
- Host System Attachment Guide for Linux (publib.boulder.ibm.com/ infocenter/ibmxiv/r2/topic/com.ibm.help.xiv.doc/docs/hag_1_5_x/ GA32-0647-02.pdf)
- Host System Attachment Guide for Solaris (publib.boulder.ibm.com/infocenter/ibmxiv/r2/topic/ com.ibm.help.xiv.doc/docs/hag_1_5_x/GA32-0649-02.pdf)
- Host System Attachment Guide for Windows (publib.boulder.ibm.com/infocenter/ibmxiv/r2/topic/ com.ibm.help.xiv.doc/docs/hag_1_5_x/GA32-0652-03.pdf)
- Host System Attachment Guide for VMware (publib.boulder.ibm.com/infocenter/ibmxiv/r2/topic/ com.ibm.help.xiv.doc/docs/ Host_System_Attachment_Guide_for_VMWare2.pdf)
- IBM XIV Storage System XCLI Reference Guide
 (publib.boulder.ibm.com/infocenter/ibmxiv/r2/topic/ com.ibm.help.xiv.doc/docs/GC27-2213-10.pdf), GC27-2213

This document describes the IBM XIV command-line interface (XCLI) system and utility commands used to manage and maintain the XIV system, including the command syntax, parameter descriptions, output descriptions, and examples.

• IBM XIV Storage System XCLI User Manual (publib.boulder.ibm.com/infocenter/ibmxiv/r2/topic/ com.ibm.help.xiv.doc/docs/GA32-0638-03.pdf), GA32-0638 This document describes how to use the IBM XIV command-line interface (XCLI) to run XIV system and utility commands.

VSS Provider - Xprov

 IBM XIV Storage System VSS Provider - Xprov Release Notes (publib.boulder.ibm.com/infocenter/ibmxiv/r2/topic/ com.ibm.help.xiv.doc/docs/xProv_2_2_4.pdf)

This document describes the supported environment, new features, known issues, and installation information.

Remote Mirroring for VCS Cluster

- IBM XIV Storage System Remote Mirroring for VCS Installation Guide (publib.boulder.ibm.com/infocenter/ibmxiv/r2/topic/ com.ibm.help.xiv.doc/docs/ IBM_XIV_Remote_Mirroring_Agent_for_VCS_2.1.0_Installation_Guide.pdf) This guide describes how to install and configure the VERITAS Cluster Server (VCS) enterprise agent for IBM XIV Remote Mirroring.
- IBM XIV Storage System Remote Mirroring for VCS Release Notes for Windows (publib.boulder.ibm.com/infocenter/ibmxiv/r2/topic/com.ibm.help.xiv.doc/docs/

IBM_XIV_Remote_Mirroring_Agent_for_VCS_2.1.0_Release_Notes_for_Windows.pdf)

This document describes the supported environment, new features, fixes, and known issues.

• IBM XIV Storage System Remote Mirroring for VCS Release Notes for Solaris (publib.boulder.ibm.com/infocenter/ibmxiv/r2/topic/com.ibm.help.xiv.doc/docs/

IBM_XIV_Remote_Mirroring_Agent_for_VCS_2.1.0_Release_Notes_for_Solaris.pdf) This document describes the supported environment, new features, fixes, and known issues.

MPIO Management Console

• IBM XIV Storage System MPIO Management Console User's Guide (publib.boulder.ibm.com/infocenter/ibmxiv/r2/topic/ com.ibm.help.xiv.doc/docs/GA32-0795.pdf), GA32-0746

This guide discusses the IBM XIV MPIO Management Console application, which provides monitoring and management capabilities to the multipath subsystems of the IBM XIV Storage System.

Remote Support Proxy

• IBM XIV Storage System Remote Support Proxy Installation and User's Guide (publib.boulder.ibm.com/infocenter/ibmxiv/r2/topic/com.ibm.help.xiv.doc/docs/GA32-0795.pdf), GA32-0795

This guide describes how to install, configure, and use the IBM XIV Storage System Remote Support Proxy to connect an XIV system to the XIV Remote Support Center.

Management Console for VMware vCenter

 IBM XIV Storage System Management Console for VMware vCenter User's Guide (publib.boulder.ibm.com/infocenter/ibmxiv/r2/topic/ com.ibm.help.xiv.doc/docs/ IBM_XIV_MNG_Console_2.0.0_for_VMware_vCenter_User_Guide.pdf), GA32-0820

This guide provides installation, configuration, and usage instructions for the IBM XIV Management Console for VMware vCenter.

IBM Redbooks publications and technical papers

Various IBM Redbooks[®] publications, Redpapers, and white papers are available for the IBM XIV Storage System. For additional papers, see the IBM XIV Storage System (www.ibm.com/systems/storage/disk/xiv/) website.

 IBM XIV Storage System: Architecture, Implementation, and Usage (www.redbooks.ibm.com/abstracts/sg247659.html?Open&cm_sp=MTE10970)

This Redbooks publication describes the concepts, architecture, and implementation of the XIV system, which is designed to be a scalable enterprise storage system based upon a grid array of hardware components.

 IBM XIV Storage System with the Virtual I/O Server and IBM i (www.redbooks.ibm.com/abstracts/redp4598.html?Open&cm_sp=MTE11087)

This Redbooks publication discusses and explains how you can connect the XIV system to the IBM i operating system through the Virtual I/O Server (VIOS). A connection through the VIOS is especially useful for IT centers that have many small IBM i partitions. When using the VIOS, the fibre-channel host adapters can be installed in the VIOS and shared by many IBM i clients using virtual connectivity to the VIOS.

 XIV Storage System: Host Attachment and Interoperability (www.redbooks.ibm.com/redpieces/abstracts/sg247904.html?Open)

This Redbooks publication describes how to attach an XIV system to various hosting operating system platforms in combination with databases and other storage-oriented application software. It also provides solutions for combining the IBM XIV Storage System with other storage platforms, host servers, or gateways.

 IBM XIV Storage System: Copy Services and Migration (www.redbooks.ibm.com/abstracts/sg247759.html?Open)

This Redbooks publication describes IBM XIV Storage System copy and migration functions for various data protection scenarios, to enhance your business continuance, data migration, and online-backup solutions. These include point-in-time copies (also known as snapshots and full volume copies) and remote-copy capabilities in synchronous or asynchronous mode. This book also discusses how to integrate the snapshot function with the IBM Tivoli FlashCopy Manager, built-in migration capability, and migration alternatives based on the IBM SAN Volume Controller (SVC).

Related websites

View these websites to get more information about the XIV system.

 IBM XIV Storage System website (www.ibm.com/systems/storage/disk/ xiv/) Use this website to learn about the XIV system, including features and hardware summary. This website also has links to white papers, Redbooks publications, and product documentation.

• **W** IBM Support Portal (www.ibm.com/storage/support)

Use this website to obtain downloadable files, links to submit and track problems, and support phone numbers and contacts.

• IBM Systems Storage forum website (www.ibm.com/developerworks/ forums/forum.jspa?forumID=846)

Use this forum to share ideas with knowledgeable experts and discover how the latest IBM storage solutions can address your business challenges. Forum topics include storage management, storage virtualization, business continuity, infrastructure simplification, disk storage systems, and storage software products and solutions.

Getting information, help, and service

If you need help, service, technical assistance, or just want more information about IBM products, you can find a variety of sources to assist you. You can view the following websites to get information about IBM products and services and to find the latest technical information and support.

- IBM website (ibm.com[®])
- IBM Support Portal (www.ibm.com/storage/support)
- IBM Directory of Worldwide Contacts website (www.ibm.com/planetwide)

Ordering publications

The IBM Publications Center is a worldwide central repository for IBM product publications and marketing material.

The IBM Publications Center website (www.ibm.com/shop/publications/order/) offers customized search functions to help you find the publications that you need. Some publications are available for you to view or download at no charge. You can also order publications. The publications center displays prices in your local currency.

Sending your comments

Your feedback is important in helping to provide the most accurate and highest quality information.

Procedure

To submit any comments about this book or any other IBM XIV Storage System documentation:

- Go to the feedback form (publib.boulder.ibm.com/infocenter/ibmxiv/r2/topic/ com.ibm.xiv.doc/icfeedback.htm) in the IBM XIV Storage System information center. You can use this form to enter and submit comments.
- Send your comments by email to starpubs@us.ibm.com. Be sure to include the following information:
 - Exact publication title and version
 - Publication form number (for example, GA32-0770-00)
 - Page, table, or illustration numbers that you are commenting on

- A detailed description of any information that should be changed

Chapter 1. Overview of the IBM XIV Storage System command-line interface

The IBM XIV Storage System command-line interface (XCLI) provides a mechanism for issuing commands to manage and maintain the XIV systems. XCLI commands are entered on an XCLI client system (or *XCLI client*) supplied by the customer.

Some XCLI commands run directly on the XCLI client. But usually, XCLI commands are sent by the XCLI client to the XIV system for processing.




Figure 1. XCLI commands running on the IBM XIV Storage System

The XCLI relies on code running in two places: the XCLI client system and the XIV system. A single XCLI client system usually supports multiple XIV systems, and these XIV systems can be running different microcode versions. The XCLI client code version is independent of the version of microcode firmware that is running on the XIV system. When you receive a new version of IBM XIV microcode that supports additional XCLI system commands, you do not need to update the XCLI code running on the XCLI client system to use the new commands.

Communication between the XCLI client and the XIV system

The XCLI client and the XIV system communicate using Secure Sockets Layer (SSL) over TCP/IP. Each XIV system has three Ethernet ports used as management interfaces, and each XIV system can be assigned up to three IP addresses – one per management interface. Having three management interfaces provides redundancy so that management interface communication can continue on a different port and IP address if one of the ports or the customer Ethernet network fails. When running a command, the XCLI client receives these three IP addresses and tries each of them until communication with one of the IP addresses is successful.

Interactive and basic modes

You can use the IBM XIV Storage System command-line interface (XCLI) in two modes: interactive and basic.

The differences between these two modes are as follows:

- Basic mode requires you to log in to an XIV system each time that you issue a command, but the interactive mode requires you to log in only once.
- In basic mode, you must enter the entire XCLI command syntax. In interactive mode, you can enter a shorter syntax.
- Interactive mode offers several command and argument completion features.

The following example shows the command syntax for each of these modes:

```
Basic xcli -u user -p password -m 127.0.0.1 vol_list
```

Interactive

vol_list

Note: Each of the batch-mode parameters in these examples is explained later in this manual.

Chapter 2. Getting started with XCLI

This information gets you started with the IBM XIV Storage System command-line interface (XCLI), including how to install and start the XCLI. It also provides information about interactive and basic modes for running commands in the XCLI and an overview of the XCLI command structure and parameters.

Installing the XCLI

This information describes how to download and install the IBM XIV Storage System command-line interface (XCLI) on the XCLI client system. The XCLI is available on Microsoft Windows, Linux and other operating systems.

About this task

Note: For the installation requirements and a list of available packages, see the *XCLI Release Notes* on the IBM Support Portal (www.ibm.com/storage/support) website.

Procedure

Perform these steps to download and install the XCLI:

- 1. Download the IBM XIV Management Tools installation package and *Release Notes* from the IBM Support Portal (www.ibm.com/storage/support) website.
- 2. Perform one of the following procedures for your operating system.
 - **Windows:** Double-click the installation file, and follow the instructions on the screen.

On the Select Components page in the installation wizard, you can choose which XIV management tools to install:

Full installation

Installs the IBM XIV Storage Management GUI, IBM XIV online monitoring tool (XIVTop) and IBM XIV command-line interface (XCLI).

CLI installation

Installs only the XCLI.

• Linux: Extract the installation file to a designated folder on your system, using the following command:

tar -xzf file_name.tar

• AIX[®], HP-UX, Solaris: Extract the installation file using the following command:

gunzip file_name.tar.gz

Then, extract the file to a designated folder on your system, using the following command:

tar -xvf file_name.tar

Tip: You can download the GNU Unzip utility (**gunzip**) from the GZIP home page Web site at www.gzip.org/.

- 3. Optional: Add the installation directory to your PATH environment variable.
- 4. Start the XCLI.

Starting the XCLI

You start the XCLI in different ways depending on the hosting operating system and operational mode. This information describes how to start the XCLI on Windows and Linux hosts in both interactive and basic modes.

Starting the XCLI on a Windows system

You can start the XCLI on a Windows system in either interactive or basic mode.

Interactive mode About this task

To run commands in interactive mode, perform the following steps:

Procedure

- 1. Click Start > Programs > XIV > XCLI to open an XCLI session window.
- 2. Follow the instructions on the screen and type the following information:
 - a. User name
 - b. Password
 - c. XIV system IP address or DNS

You are now connected to the specified XIV system. The XCLI prompt appears in the session window. The window title includes the name of XIV system to which the XCLI is connected.



Figure 2. XCLI prompt on Windows

3. Run any XCLI command from this prompt (for example, you can run the **vol_list** command to list volumes).

Basic mode About this task

To run commands in basic mode, perform the following steps:

Procedure

- 1. Open a Windows command session.
- 2. Type c:\program files\xiv.

3. Run any XCLI command, including the XCLI identification parameters, for example:

```
xcli -u user -p ******* -m 127.0.0.1 vol_list
```

Starting the XCLI on a Linux system

You can start the XCLI on a Linux system in either interactive or basic mode.

Interactive mode About this task

To run commands in interactive mode, perform the following steps:

Procedure

- 1. Type xcli -w to open a new session.
- 2. Follow the instructions on the screen and type the following information:
 - a. User name
 - b. Password
 - c. XIV system IP address or DNS
- **3.** You are now connected to the specified XIV system. The XCLI prompt appears in the session window. You can run any XCLI command from this prompt (for example, you can run the **vol_list** command to list volumes).

Basic mode About this task

To run commands in basic mode, enter the command including the XCLI identification parameters, for example:

xcli -u user -p ******* -m 127.0.0.1 vol_list

Exiting an interactive XCLI session

When running the IBM XIV Storage System command-line interface (XCLI) in interactive mode, you can exit the interactive session by either closing the session window or running the **exit** command.

Interactive mode features

Running XCLI commands in interactive mode provides command and argument completion, along with possible values to these arguments.

Interactive mode

To run a command in interactive mode, type the command. For example, the following command lists storage pools.

pool_list

Command-name completion

The XCLI can list commands that start with one or more characters. To list commands, type one or more characters and press Tab.

• This example lists all commands that start with the letter v:

>> v			
version_get	vol_by_id	vol_copy	vol_create
vol_delete	vol_format	vol_list	vol_lock
vol_mapping_list	vol_move	vol_rename	vol_resize
vol_unlock	<pre>vpd_config_get</pre>	<pre>vpd_config_set</pre>	

• This example lists all commands that start with the letters cg_:

>> cg_			
cg_add_vol	cg_create	cg_delete	cg_list
cg_move	cg_remove_vol	cg_rename	cg_snapshots_create

Command-argument completion

The XCLI can provide list arguments and argument values to help you complete a command. To list arguments for a specific command, type the command name and press Tab. To list values for a specific argument, type the command name and argument, optionally specify one or more characters for the value, and then press Tab.

Listing arguments for a command

This example lists arguments for the **vol_create** command:

>> vol_create
vol= size= size block= pool=

Listing values for a specific argument

This example lists valid values for the **pool** argument that is required for the **pool_create** command:

>> pool_create pool=
8058 2nd Pool 8059 pool1

• Listing a subet of values for a specific argument

This example lists valid values that start with v for the **vol** argument that is required for the **vol_list** command:

>> vol_list vol=v
vol1 vol2

Understanding the command syntax

This information describes the general syntax for the XCLI command.

```
The XCLI uses the following general syntax:

xcli < <[ --file=FILE ] -c CONFIG|-m IP1 [-m IP2 [-m IP3]] >

-L|-a <config> -m IP1 [-m IP2 [ -m IP3]]|-d IP1 [-m IP2 [ -m IP3]] >|

[ -r ]

[ <-1 | --list> | <-s | --csv> | <-x | --xml> ]

[ <-u | --user> user ]

[ <-p | --password> password ]

[-t [--fields=field1,field2,...]]

[command]
```

The parameters and options are described later in this document.

Command syntax quick reference

This information describes the command parameters and options that are available in the XCLI.

Use the following table as a quick reference to the various parameters and options.

Options	Values
-f	Specifies the name of a configuration file that lists the XIV system
-c	Specifies the XIV system on which the command is to be run
-m	Specifies the IP address of the XIV system on which the command runs
-L	Lists the XIV systems, as read from the configuration file
-a	Specifies the name of the XIV system to add to the configuration file
-d	Removes an XIV system from the configuration file
-r	Specifies the name of a batch file that runs XCLI commands
-1	Displays the command output in user-readable format
-s	Displays the command output in CSV format
-x	Displays the command output in XML format
-u	Specifies the user
-р	Specifies the password
-t	Manages the fields of the command output
-h	Displays command help
-у	Suppresses the Are you sure? prompt
-v	Displays the version of the XCLI on the screen
command	Runs the specified command

Syntax example

The XCLI command syntax specifies the command to be run, along with its applicable parameters and their values.

In the following example, the parameters to the left of the **vol_list** command specify the IBM XIV Storage System to which the command is being directed, and also specify the required user and password for this XIV system:

xcli -u admin -p ******** -m 127.0.0.1 vol_list

Identification parameters

- -u Specifies the user ID.
- -p Specifies the password.

XIV system

The XIV system is specified by either its IP address or name of the XIV system as listed in the configuration file. See "Configuration parameters" on page 10 for more information.

- -m Specifies the IP address of the XIV system to which this command is directed.
- -c Specifies the name of the XIV system to which this command is directed, as it is defined in the configuration file (for example, my_system).

Command

vol_list

Specifies the command to be run. For more information about running commands, see "Interactive mode features" on page 5.

Chapter 3. Using the XCLI

This information describes each XCLI command parameter.

Using identification parameters

This information describes parameters used to set the user, password, and XIV system.

User and password parameters

The XCLI and the IBM XIV Storage System provide a password-controlled user ID as a security mechanism for controlling XCLI operations.

When running in basic mode, specify the user name and password as follows: xcli -u admin -p ********* -c my system vol list

In this command:

Identification parameters

- -u Specifies the user ID.
- -p Specifies the password.

XIV system

-c Specifies the name of the XIV system to which this command is directed, as it is defined in the configuration file (for example, my_system).

Command

vol_list

Specifies the command to be run. For more information about running commands, see "Interactive mode features" on page 5.

The password handling mechanism performs as follows:

- 1. Checking the user:
 - The **-u** or **--user** parameter on the command line is checked first and its value is used as the user name.
 - If the **-u** or **--user** parameter is not specified, the XIV_XCLIUSER environment variable is used as a user name.
- 2. Checking the password:
 - The **-p** or **--password** parameter on the command line is checked first and its value is used as the password.
 - If the **-p** or **--password** parameter is not specified, the XIV_XCLIPASSWORD environment variable is used as the password.

Note: If you do not specify both the user ID and the password, the command fails.

Defining XCLI configurations

This information describes the parameters used to identify the XIV system on which a command is to run and how to create a configuration file to manage the XIV systems that you can use.

Configuration parameters

Most XCLI commands are directed to a specific XIV system using the IP address. You must provide at least one address and up to three addresses per XIV system.

To provide the XIV system IP address, log in to an interactive session or specify the configuration file that stores the XIV system IP address or addresses.

Specifying an XIV system using its IP address

In the following example, the command is directed to an XIV system with an IP address of 127.0.0.1:

xcli -u admin -p ******* -m 127.0.0.1 vol list

In this command:

Identification parameters

- -u Specifies the user ID.
- -p Specifies the password.

XIV system

The XIV system is specified by its IP address.

-m Specifies the IP address of the XIV system to which this command is directed.

Command

vol_list

Specifies the command to be run. For more information about running commands, see "Interactive mode features" on page 5.

Specifying an XIV system by using a configuration file

In the following example, the command is directed to an XIV system that is listed on the my system configuration file:

xcli -u admin -p ******** -c my_system vol_list

In this command:

Identification parameters

- -u Specifies the user ID.
- -p Specifies the password.

XIV system

The XIV system is specified by its name on the configuration file.

-c Specifies the name of the XIV system to which this command is directed, as it is defined in the configuration file (for example, my_system).

Command

vol_list

Specifies the command to be run. For more information about running commands, see "Interactive mode features" on page 5.

Creating a configuration file

You can use the configuration file to manage a list of the XIV systems that you are working with.

Use the following options to add and subtract XIV systems from this file and to list them.

Listing the available XIV systems

In the following example, the configuration information is read from a default file location or from the file that is specified with [-f *file*]. xcli [-f *file*] -L

Adding a new XIV system to the configuration file

In the following example, IP1...IP3 are added to the configuration file at the default file location. If applicable, the addresses are added to the file that is specified in [-f *file*]. The *<config>* variable represents the configuration name of the XIV system that you are adding to the list.

xcli [-f file] -a <config> -m IP1 [-m IP2 [-m IP3]]

Removing an XIV system from the configuration file

In the following example, IP1...IP3 are removed from the configuration file. If applicable, the addresses are removed from the file that is specified with [-f *file*].

xcli [-f *file*] -d IP1 [-m IP2 [-m IP3]]

Location of the configuration file

The configuration file is located in the following directory, depending on the operating system. You do not specify the location of the configuration file when you add or remove XIV systems from the configuration.

Windows

\Application Data\XIV\GUI10\properties

UNIX In the home folder under .xiv

Display options

This information describes the formats that you can choose to display the command output.

Using display options

Output from an XCLI command can be displayed in a list, comma-separated value (CSV) and XML formats. You can specify only one format. If you do not specify the format, the output defaults to a list. The display options are:

- -1 Displays command output in a list (also known as user-readable format).
- -s Displays command output in CSV format.
- -x Displays command output in XML format.

Use the display options as follows:

```
Interactive mode
    vol_list -s
Basic mode
    xcli -u user -p ********* -m 127.0.0.1 -s vol_list
```

In this command:

Identification parameters

- -u Specifies the user ID.
- -p Specifies the password.

XIV system

The XIV system is specified by either its IP address or name of the XIV system as listed in the configuration file. See "Configuration parameters" on page 10 for more information.

- -m Specifies the IP address of the XIV system to which this command is directed.
- -c Specifies the name of the XIV system to which this command is directed, as it is defined in the configuration file (for example, my_system).

Display option

-s Displays command output in CSV format.

Command

vol_list

Specifies the command to be run. For more information about running commands, see"Interactive mode features" on page 5.

Table display options

The list option displays the command output in a user-readable format. When running a command with a list option, you can specify which table columns are displayed on the screen.

Determine the way that the table is displayed as follows:

Interactive mode

vol_list -t "size"

Single-command mode

```
xcli -u admin -p ******** -m 127.0.0.1 vol list -t "size"
```

In this command:

Identification parameters

- -u Specifies the user ID.
- -p Specifies the password.

XIV system

The XIV system is specified by either its IP address or name of the XIV system as listed in the configuration file. See "Configuration parameters" on page 10 for more information.

- -m Specifies the IP address of the XIV system to which this command is directed.
- -c Specifies the name of the XIV system to which this command is directed, as it is defined in the configuration file (for example, my_system).

Table display option

-t "size"

Specifies the one or more columns that are to be displayed. In this example, only the Size column is displayed. You can list any combination of the table columns.

Command

vol_list

Specifies the command to be run. For more information about running commands, see "Interactive mode features" on page 5.

Viewing the available columns

You can view all of the available table's columns by running: help command=<command_name> format=full.

The result provides information about the command, including a list of all of its fields. For example, the available fields for the **vol_list** command are: name, size, master_name, cg_name, pool_name, creator, used_capacity, used_capacity_MiB, snapshot_time_on_master, serial, wwn, capacity, mirrored, sg_name, snapshot_time, sg_snapshot_of, locked_by_pool, size_MiB, locked, snapshot_of, modified, delete_priority.

Running commands in batch mode

XCLI commands can be grouped together and run in a batch. For example, you can use batch mode to run an identical set of commands on multiple IBM XIV Storage Systems.

Creating a batch file for the commands

Create a text file and write the commands without the **xcli** prefix or XCLI parameters. For example:

```
pool_create pool=pool_00001 hard_size=171 soft_size=171 snapshot_size=65
vol_create vol=vol_00010 size=17 pool=pool_00001
vol list vol=vol 00010
```

This example contains the following commands:

- The **pool_create** command, along with its arguments. This command creates a storage pool, which is a prerequisite for creating a volume.
- The **vol_create** command, along with its arguments. This command creates a volume in the pool that has just been created.
- The vol_list command displays the details of the newly created volume.

Name the script file and save it.

Running a batch file

To run the batch file, you must specify the XCLI parameters:

```
xcli -u admin -p ********* -m 127.0.0.1 -r
"C:\Documents and Settings\avia\xcli\xcli script.txt"
```

In this command:

Identification parameters

- -u Specifies the user ID.
- -p Specifies the password.

XIV system

The XIV system is specified by either its IP address or name of XIV system as listed in the configuration file. See "Configuration parameters" on page 10 for more information.

- -m Specifies the IP address of the XIV system to which this command is directed.
- -c Specifies the name of the XIV system to which this command is directed, as it is defined in the configuration file (for example, my_system).

The batch parameter

-r Specifies the name of the batch file to run on the XIV system.

Viewing the output

The three commands in the previous example create a pool, then create a volume, then display the volume details. The following output is returned from running these three commands in batch mode:

- Confirmation that a pool was created
- · Confirmation that a volume was created
- Table with the details of the newly created volume

Failure of batch mode

When one of the commands that run in batch mode fails, the following actions occur:

- 1. The script exits immediately.
- 2. No commands after the failing command are run.
- 3. An error message is displayed identifying the XCLI command that failed.

Displaying XCLI help and version

This information describes how to display help for the XCLI command and the version of the XCLI code that is running on the XCLI client.

About this task

The following command prints the help text for the XCLI in batch mode: xcli <-h | --help>

The following command prints the XCLI version: xcli <-v | --version>

Notices

This information was developed for products and services offered in the U.S.A.

IBM may not offer the products, services, or features discussed in this document in other countries. Consult your local IBM representative for information on the products and services currently available in your area. Any reference to an IBM product, program, or service is not intended to state or imply that only that IBM product, program, or service may be used. Any functionally equivalent product, program, or service that does not infringe any IBM intellectual property right may be used instead. However, it is the user's responsibility to evaluate and verify the operation of any non-IBM product, program, or service.

IBM may have patents or pending patent applications covering subject matter described in this document. The furnishing of this document does not grant you any license to these patents. You can send license inquiries, in writing, to:

IBM Director of Licensing IBM Corporation North Castle Drive Armonk, NY 10504-1785 U.S.A.

For license inquiries regarding double-byte character set (DBCS) information, contact the IBM Intellectual Property Department in your country or send inquiries, in writing, to:

Intellectual Property Licensing Legal and Intellectual Property Law IBM Japan Ltd. 1623-14, Shimotsuruma, Yamato-shi Kanagawa 242-8502 Japan

The following paragraph does not apply to the United Kingdom or any other country where such provisions are inconsistent with local law: INTERNATIONAL BUSINESS MACHINES CORPORATION PROVIDES THIS PUBLICATION "AS IS" WITHOUT WARRANTY OF ANY KIND, EITHER EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF NON-INFRINGEMENT, MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. Some states do not allow disclaimer of express or implied warranties in certain transactions, therefore, this statement may not apply to you.

This information could include technical inaccuracies or typographical errors. Changes are periodically made to the information herein; these changes will be incorporated in new editions of the publication. IBM may make improvements and/or changes in the product(s) and/or the program(s) described in this publication at any time without notice.

Any references in this information to non-IBM Web sites are provided for convenience only and do not in any manner serve as an endorsement of those Web sites. The materials at those Web sites are not part of the materials for this IBM product and use of those Web sites is at your own risk. IBM may use or distribute any of the information you supply in any way it believes appropriate without incurring any obligation to you.

Licensees of this program who wish to have information about it for the purpose of enabling: (i) the exchange of information between independently created programs and other programs (including this one) and (ii) the mutual use of the information which has been exchanged, should contact:

IBM Corporation Almaden Research 650 Harry Road Bldg 80, D3-304, Department 277 San Jose, CA 95120-6099 U.S.A.

Such information may be available, subject to appropriate terms and conditions, including in some cases, payment of a fee.

The licensed program described in this document and all licensed material available for it are provided by IBM under terms of the IBM Customer Agreement, IBM International Program License Agreement or any equivalent agreement between us.

Any performance data contained herein was determined in a controlled environment. Therefore, the results obtained in other operating environments may vary significantly. Some measurements may have been made on development-level systems and there is no guarantee that these measurements will be the same on generally available systems. Furthermore, some measurements may have been estimated through extrapolation. Actual results may vary. Users of this document should verify the applicable data for their specific environment.

Information concerning non-IBM products was obtained from the suppliers of those products, their published announcements or other publicly available sources. IBM has not tested those products and cannot confirm the accuracy of performance, compatibility or any other claims related to non-IBM products. Questions on the capabilities of non-IBM products should be addressed to the suppliers of those products.

All statements regarding IBM's future direction or intent are subject to change or withdrawal without notice, and represent goals and objectives only.

This information is for planning purposes only. The information herein is subject to change before the products described become available.

This information contains examples of data and reports used in daily business operations. To illustrate them as completely as possible, the examples include the names of individuals, companies, brands, and products. All of these names are fictitious and any similarity to the names and addresses used by an actual business enterprise is entirely coincidental.

If you are viewing this information softcopy, the photographs and color illustrations may not appear.

Trademarks

IBM, the IBM logo, and ibm.com are trademarks or registered trademarks of International Business Machines Corp., registered in many jurisdictions worldwide. Other product and service names might be trademarks of IBM or other companies. A current list of IBM trademarks is available on the Web at Copyright and trademark information website (www.ibm.com/legal/copytrade.shtml).

Adobe, the Adobe logo, PostScript, and the PostScript logo are either registered trademarks or trademarks of Adobe Systems Incorporated in the United States, and/or other countries.

IT Infrastructure Library is a registered trademark of the Central Computer and Telecommunications Agency which is now part of the Office of Government Commerce.

Intel, Intel logo, Intel Inside, Intel Inside logo, Intel Centrino, Intel Centrino logo, Celeron, Intel Xeon, Intel SpeedStep, Itanium, and Pentium are trademarks or registered trademarks of Intel Corporation or its subsidiaries in the United States and other countries.

Linux is a registered trademark of Linus Torvalds in the United States, other countries, or both.

Microsoft, Windows, Windows NT, and the Windows logo are trademarks of Microsoft Corporation in the United States, other countries, or both.

ITIL is a registered trademark, and a registered community trademark of the Office of Government Commerce, and is registered in the U.S. Patent and Trademark Office.

UNIX is a registered trademark of The Open Group in the United States and other countries.

Java and all Java-based trademarks and logos are trademarks or registered trademarks of Oracle and/or its affiliates.

Cell Broadband Engine is a trademark of Sony Computer Entertainment, Inc. in the United States, other countries, or both and is used under license therefrom.

Linear Tape-Open, LTO, the LTO Logo, Ultrium, and the Ultrium logo are trademarks of HP, IBM Corp. and Quantum in the U.S. and other countries.

Other product and service names might be trademarks of IBM or other companies.

Glossary

This glossary includes terms and definitions for IBM XIV Storage System.

This glossary includes selected terms and definitions from:

- The American National Standard Dictionary for Information Systems, ANSI X3.172–1990, copyright 1990 by the American National Standards Institute (ANSI), 11 West 42nd Street, New York, New York 10036. Definitions derived from this book have the symbol (A) after the definition.
- IBM Terminology, which is available online at the following Web site: http://www-01.ibm.com/software/globalization/ terminology/index.jsp. Definitions derived from this source have the symbol (GC) after the definition.
- The *Information Technology Vocabulary* developed by Subcommittee 1, Joint Technical Committee 1, of the International Organization for Standardization and the International Electrotechnical Commission (ISO/IEC JTC1/SC1). Definitions derived from this book have the symbol (I) after the definition. Definitions taken from draft international standards, committee drafts, and working papers that the ISO/IEC JTC1/SC1 is developing have the symbol (T) after the definition, indicating that final agreement has not been reached among the participating National Bodies of SC1.

This glossary uses the following cross-reference forms:

- **See** Refers the reader to one of two kinds of related information:
 - A term that is the expanded form of an abbreviation or acronym. This expanded form of the term contains the full definition.
 - A synonym or more preferred term

See also

Refers the reader to one or more related terms.

Contrast with

Refers the reader to a term that has an opposite or substantively different meaning.

В

basic mode

A means of entering XCLI commands on the XCLI client that requires specifying IP address and login information for each command. Additional output formatting options are available in basic mode.

I

interactive mode

A means of entering XCLI commands on the XCLI client in which the IP address, user, and password information does not need to be specified for each command.

Х

XCLI client

The system on which the XCLI command is entered.

XCLI identification parameters

Parameters that identify the user issuing the command and the XIV system (if any) on which the command is to run. XCLI identification parameters can be specified:

- By entering them at the beginning of an interactive mode session
- In a configuration file
- When running a command in basic mode
- When running a list of commands as a batch

XCLI system command

An XCLI command that is sent to the XIV system for processing.

XCLI utility command

An XCLI command that is issued on the XCLI client. An XCLI utility command is not sent to an XIV system for processing. XCLI utility commands are used for setting up configurations on the XCLI client and for queries (for example, of software version) that can be processed on the client.

Index

Α

about this document sending comments xi

В

basic mode 2 batch mode 13

С

command modes 2 commands argument completion 5 commands name completion 5 commands, running 1 comments, sending xi configuration parameters 10 configuration definition 1 configuration files 10 configuration parameters 10 CSV display option 11

D

display options 11 displaying XCLI help 14 XCLI version 14 documentation improvement xi

E

exiting an XCLI session 5

F

forums vii

Η

help, displaying 14

installing XCLI AIX 3 HP-UX 3 Linux 3 Windows 3 interactive mode 1, 2

L

legal notices 17

© Copyright IBM Corp. 2009, 2010

list display option 11

Ν

notices legal 15

0

options display 11

Ρ

password parameter 9, 12 PDFs vii publications vii

R

reader feedback, sending xi related information vii running commands from a script file 13

S

scripts, running commands in 13 sending comments xi single-command mode 1 starting the XCLI on Linux 5 on Windows 4 syntax examples 7 syntax of XCLI commands 6

Т

trademarks 17

U

user parameter 9, 12

V

version, displaying 14

Х

XCLI command syntax 6 configuration file 10 configuration parameters 10 install 3 XCLI (continued)

overview 1
user and password parameters 9, 12

XCLI options

display 11

XCLI parameters

configuration 10
script 13

XCLI session

exiting 5
features 5

XCLI version 14
XML

display option 11

21

Printed in USA

GA32-0638-03

