



# JVC



## AUDIO/VIDEO CONTROL RECEIVER

# RX-5022RSL



**COMPU LINK**  
/// Remote ///

DIGITAL  
**dtS**  
SURROUND

**DOLBY**  
DIGITAL  
PRO LOGIC II

**R-D-S**

## INSTRUCTIONS

### For Customer Use:


Enter below the Model No. and Serial No. which are located either on the rear, bottom or side of the cabinet. Retain this information for future reference.

Model No. \_\_\_\_\_

Serial No. \_\_\_\_\_

LVT0850-008A

[B]



# Warnings, Cautions and Others

---

**IMPORTANT** for the U.K.

**DO NOT** cut off the mains plug from this equipment. If the plug fitted is not suitable for the power points in your home or the cable is too short to reach a power point, then obtain an appropriate safety approved extension lead or consult your dealer.

**BE SURE** to replace the fuse only with an identical approved type, as originally fitted.

If nonetheless the mains plug is cut off ensure to remove the fuse and dispose of the plug immediately, to avoid a possible shock hazard by inadvertent connection to the mains supply.

If this product is not supplied fitted with a mains plug then follow the instructions given below:

**IMPORTANT.**

**DO NOT** make any connection to the terminal which is marked with the letter E or by the safety earth symbol or coloured green or green-and-yellow.

The wires in the mains lead on this product are coloured in accordance with the following code:

Blue : Neutral  
Brown : Live

As these colours may not correspond with the coloured markings identifying the terminals in your plug proceed as follows:

The wire which is coloured blue must be connected to the terminal which is marked with the letter N or coloured black.

The wire which is coloured brown must be connected to the terminal which is marked with the letter L or coloured red.


**IF IN DOUBT - CONSULT A COMPETENT ELECTRICIAN.**

## CAUTION

To reduce the risk of electrical shocks, fire, etc.:

1. Do not remove screws, covers or cabinet.
2. Do not expose this appliance to rain or moisture.

## Caution — switch!

Disconnect the mains plug to shut the power off completely. The  switch in any position does not disconnect the mains line. The power can be remote controlled.

## CAUTION

- Do not block the ventilation openings or holes.  
(If the ventilation openings or holes are blocked by a newspaper or cloth, etc., the heat may not be able to get out.)
- Do not place any naked flame sources, such as lighted candles, on the apparatus.
- When discarding batteries, environmental problems must be considered and local rules or laws governing the disposal of these batteries must be followed strictly.
- Do not expose this apparatus to rain, moisture, dripping or splashing and that no objects filled with liquids such as vases, shall be placed on the apparatus.

## SAFETY INSTRUCTIONS

### “SOME DOS AND DON'TS ON THE SAFE USE OF EQUIPMENT”

This equipment has been designed and manufactured to meet international safety standards but, like any electrical equipment, care must be taken if you are to obtain the best results and safety is to be assured.

\*\*\*\*\*

Do read the operating instructions before you attempt to use the equipment.

Do ensure that all electrical connections (including the mains plug, extension leads and interconnections between pieces of equipment) are properly made and in accordance with the manufacturer's instructions. Switch off and withdraw the mains plug when making or changing connections.

Do consult your dealer if you are ever in doubt about the installation, operation or safety of your equipment.

Do be careful with glass panels or doors on equipment.

\*\*\*\*\*

DON'T continue to operate the equipment if you are in any doubt about it working normally, or if it is damaged in any way—switch off, withdraw the mains plug and consult your dealer.

DON'T remove any fixed cover as this may expose dangerous voltages.

DON'T leave equipment switched on when it is unattended unless it is specifically stated that it is designed for unattended operation or has a standby mode.

Switch off using the switch on the equipment and make sure that your family know how to do this.

Special arrangements may need to be made for infirm or handicapped people.

DON'T use equipment such as personal stereos or radios so that you are distracted from the requirements of traffic safety. It is illegal to watch television whilst driving.

DON'T listen to headphones at high volume as such use can permanently damage your hearing.

DON'T obstruct the ventilation of the equipment, for example with curtains or soft furnishings.

Overheating will cause damage and shorten the life of the equipment.

DON'T use makeshift stands and NEVER fix legs with wood screws — to ensure complete safety always fit the manufacturer's approved stand or legs with the fixings provided according to the instructions.

DON'T allow electrical equipment to be exposed to rain or moisture.

ABOVE ALL

- NEVER let anyone, especially children, push anything into holes, slots or any other opening in the case -this could result in a fatal electrical shock.;
- NEVER guess or take chances with electrical equipment of any kind — it is better to be safe than sorry!


#### Caution: Proper Ventilation

To avoid risk of electric shock and fire and to protect from damage.

Locate the apparatus as follows:

- Front: No obstructions open spacing.
- Sides: No obstructions in 10 cm from the sides.
- Top: No obstructions in 10 cm from the top.
- Back: No obstructions in 15 cm from the back
- Bottom: No obstructions, place on the level surface.

In addition, maintain the best possible air circulation as illustrated.



# Table of Contents

<b>Parts Identification .....</b>	<b>2</b>
<b>Getting Started .....</b>	<b>3</b>
Before Installation .....	3
Checking the Supplied Accessories .....	3
Putting Batteries in the Remote Control .....	3
Connecting the FM and AM (MW/LW) Antennas .....	4
Connecting the Speakers .....	5
Connecting Audio/Video Components .....	6
Connecting the Power Cord .....	7
<b>Basic Operations .....</b>	<b>8</b>
Turning On the Power .....	8
Selecting the Source to Play .....	8
Adjusting the Volume .....	9
Listening Only with Headphones .....	9
Turning Off the Sounds Temporarily—Muting .....	10
Turning Off the Power with the Sleep Timer .....	10
Changing the Display Brightness .....	10
<b>Basic Settings .....</b>	<b>11</b>
Setting the Digital Input (DIGITAL IN) Terminals .....	11
Selecting the Analog or Digital Input Mode .....	11
Setting the Speaker Information .....	12
<b>Sound Adjustments .....</b>	<b>15</b>
Attenuating the Input Signal .....	15
Adjusting the Front Speakers Output Balance .....	15
Adjusting the Tone .....	15
Adjusting the Subwoofer Output Level .....	15
<b>Tuner Operations .....</b>	<b>16</b>
Tuning in Stations Manually .....	16
Using Preset Tuning .....	16
Selecting the FM Reception Mode .....	17
Using the RDS (Radio Data System) to Receive FM Stations ...	18
Searching for a Program by PTY Codes .....	18
Switching to a Broadcast Program of Your Choice Temporarily .....	20
<b>Creating Realistic Sound Fields .....</b>	<b>21</b>
About Relations between Speaker Layout and Surround Modes .....	23
Using Dolby Pro Logic II, Dolby Digital and DTS Digital Surround .....	24
Using DAP Modes and All Channel Stereo .....	26
<b>COMPU LINK Remote Control System .....</b>	<b>27</b>
<b>Operating JVC's Audio/Video     Components .....</b>	<b>28</b>
Operating Audio Components .....	28
Operating Video Components .....	30
<b>Troubleshooting .....</b>	<b>31</b>
<b>Specifications .....</b>	<b>32</b>




This mark indicates that the remote control CAN ONLY be used for the operation explained.




This mark indicates that the remote control CANNOT be used for the operation explained. Use buttons on the front panel.

## Front Panel



## Remote Control



See pages in the parentheses for details.

### Front Panel

- 1 STANDBY/ON button and STANDBY lamp (8)
- 2 FM/AM TUNING UP/ DOWN buttons (16)
- 3 FM/AM PRESET UP/ DOWN buttons (16, 17)
- 4 FM MODE button (17)
- 5 MEMORY button (16, 17)
- 6 Display (8)
- 7 ADJUST button (15, 25, 26)
- 8 Remote sensor (3)
- 9 SETTING button (11 – 14)
- 10 DIMMER button (10)
- 11 RDS operating buttons (18 – 20)  
PTY SEARCH, TA/NEWS/INFO, DISPLAY MODE
- 12 MASTER VOLUME control (9)
- 13 PHONES jack (9)
- 14 SURROUND ON/OFF button (23, 25, 26)
- 15 SURROUND MODE button (23, 25, 26)
- 16 SPEAKERS ON/OFF button (9)
- 17 • INPUT ANALOG button (11)  
• INPUT ATT button (15)
- 18 INPUT DIGITAL button (11, 12)
- 19 Source selecting buttons (8, 9, 11, 16, 17)  
DVD, VCR, TV SOUND, CD, TAPE/CDR, FM/AM
- 20 SOURCE NAME button (8)
- 21 CONTROL UP /DOWN buttons

### Remote Control

- 1 • 10 keys for selecting preset channels (17)  
• 10 keys for adjusting sound (15, 25, 26)  
• 10 keys for operating audio/video components (28 – 30)
- 2 SOUND button (15, 25, 26)
- 3 • Operating buttons for audio/video components (29, 30)  
• RDS operating buttons (18 – 20)  
PTY SEARCH, TA/NEWS/INFO, DISPLAY MODE
- 4 REC PAUSE button (29, 30)
- 5 Source selecting buttons (8, 9, 11, 17, 29, 30)  
TAPE/CDR, CD, DVD, FM/AM, TV SOUND, VCR
- 6 FM MODE button (17)
- 7 DIMMER button (10)
- 8 TV/VIDEO button (30)
- 9 TV CH (channel) +/- buttons (30)
- 10 VCR CH (channel) +/- buttons (30)
- 11 STANDBY/ON buttons (8, 30)  
AUDIO, TV, VCR, DVD
- 12 SLEEP button (10)
- 13 CD-DISC button (29)
- 14 ANALOG/DIGITAL button (11, 12)
- 15 SURROUND ON/OFF and SURROUND MODE buttons (23, 24, 26, 28)
- 16 MUTING button (10)
- 17 TV VOLUME +/- buttons (30)
- 18 VOLUME +/- button (9)

# Getting Started

## Before Installation

### General Precautions

- DO NOT insert any metal object into the unit.
- DO NOT disassemble the unit or remove screws, covers, or cabinet.
- DO NOT expose the unit to rain or moisture.

### Locations

- Install the unit in a location that is level and protected from moisture.
- The temperature around the unit must be between  $-5^{\circ}\text{C}$  and  $35^{\circ}\text{C}$  ( $23^{\circ}\text{F}$  and  $95^{\circ}\text{F}$ ).
- Make sure there is good ventilation around the unit. Poor ventilation could cause overheating and damage the unit.

### Handling the unit

- DO NOT touch the power cord with wet hands.
- DO NOT pull on the power cord to unplug the cord. When unplugging the cord, always grasp the plug so as not to damage the cord.
- Keep the power cord away from the connecting cords and the antenna. The power cord may cause noise or screen interference. It is recommended to use a coaxial cable for antenna connection, since it is well-shielded against interference.
- When a power failure occurs, or when you unplug the power cord, the preset settings such as preset FM or AM (MW/LW) channels and sound adjustments may be erased in a few days.

## Checking the Supplied Accessories

Check to be sure you have all of the following supplied accessories. The number in the parentheses indicates the quantity of the pieces supplied.

- Remote Control (1)
- Batteries (2)
- AM (MW/LW) Loop Antenna (1)
- FM Antenna (1)


If anything is missing, contact your dealer immediately.

## Putting Batteries in the Remote Control

Before using the remote control, put two supplied batteries first.


- When using the remote control, aim the remote control directly at the remote sensor on the unit.

### 1 On the back of the remote control, remove the battery cover.




### 2 Insert batteries.

- Make sure to match the polarity: (+) to (+) and (–) to (–).



### 3 Replace the cover.




If the range or effectiveness of the remote control decreases, replace the batteries. Use two R6P(SUM-3)/AA(15F) type dry-cell batteries.

### CAUTION:

Follow these precautions to avoid leaking or cracking cells:

- Place batteries in the remote control so they match the polarity: (+) to (+) and (–) to (–).
- Use the correct type of batteries. Batteries that look similar may differ in voltage.
- Always replace both batteries at the same time.
- Do not expose batteries to heat or flame.

## Connecting the FM and AM (MW/LW) Antennas



### AM (MW/LW) antenna connection

Connect the AM (MW/LW) loop antenna supplied to the AM LOOP terminals.

Turn the loop until you have the best reception.

- If the reception is poor, connect an outdoor single vinyl-covered wire (not supplied) to the AM EXT terminal. (Keep the AM (MW/LW) loop antenna connected.)

### FM antenna connection


Connect the supplied FM antenna to the FM 75  $\Omega$  COAXIAL terminal as temporary measure.

Extend the supplied FM antenna horizontally.

- If the reception is poor, connect an outdoor FM antenna (IEC or DIN45325) (not supplied). Before attaching a 75  $\Omega$  coaxial cable (with a standard type connector), disconnect the supplied FM antenna.

### Notes:

- If the AM (MW/LW) loop antenna wire is covered with vinyl, remove the vinyl while twisting it as shown to the right.
- Make sure the antenna conductors do not touch any other terminals, connecting cords and power cord. This could cause poor reception.





# Getting Started


## Connecting the Speakers

After connecting the front, center, rear speakers and/or a subwoofer, set the speaker setting information properly to obtain the best possible Surround effect. For details, see pages 12 to 14.

### CAUTION:

Use speakers with the SPEAKER IMPEDANCE indicated by the speaker terminals.

## Connecting the front, center and rear speakers




For each speaker, connect the (+) and (–) terminals on the rear panel to the (+) and (–) terminals marked on the speakers.

- 1 Cut, twist and remove the insulation at the end of each speaker cord.
- 2 Open the terminal (①), then insert the speaker cord (②).
- 3 Close the terminal.

## Connecting the subwoofer speaker

By connecting a subwoofer, you can enhance the bass or reproduce the original LFE signals recorded in the digital software.






Connect the input jack of a powered subwoofer to the SUBWOOFER OUT jack on the rear panel, using a cable with RCA pin plugs (not supplied).

- Refer also to the manual supplied with your subwoofer.

Since bass sound is non-directional, you can place a subwoofer wherever you like. Normally place it in front of you.

## Speaker layout diagram

“NO” for the subwoofer, “LARGE” for the front speakers, and “SMALL” for the center and rear speakers are initial settings. To get best possible sound, change the subwoofer and speaker settings to fit your listening conditions. (See pages 12 and 13).





## Connecting Audio/Video Components

**Turn off all components before connections.**

You can connect the following audio/video components to this receiver. Refer also to the manuals supplied with your components.

Audio Components	Video Components
• CD player*	• TV*
• Cassette deck or CD recorder*	• VCR
	• DVD player*

\* You can connect these components using the methods described in "Analog connections" (below) or in "Digital connections" (see page 7).

## Analog connections



## Audio component connections

Use the cables with RCA pin plugs (not supplied).

Connect the white plug to the audio left jack, and the red plug to the audio right jack.

**CAUTION:**

If you connect a sound-enhancing device such as a graphic equalizer between the source components and this receiver, the sound output through this receiver may be distorted.



**Note:**

*You can connect either a cassette deck or a CD recorder to the TAPE/CDR jacks. When connecting a CD recorder to the TAPE/CDR jacks, change the source name to "CDR," which will be shown on the display when selected as the source. See page 8 for details.*


### If your audio components have a COMPU LINK jack

See also page 27 for detailed information about the connection and the COMPU LINK remote control system.

## **Video component connections**


Use the cables with RCA pin plugs (not supplied).

Connect the white plug to the audio left jack, the red plug to the audio right jack, and the yellow plug to the video jack.




Connect the TV to the MONITOR OUT jack to view the playback picture from the other connected video components.

# Getting Started



- A To left/right channel audio output
- B To left/right channel audio input
- C To video output
- D To video input



- A To front left/right channel audio output (or to audio mixed output)
- B To video output

## Note:


To enjoy the software encoded with Dolby Digital or DTS Digital Surround, you must connect the DVD player using the digital terminal on the rear of this receiver. (See "Digital connections" below.)

## Digital connections

This receiver is equipped with two DIGITAL IN terminals—one digital coaxial terminal and one digital optical terminal. You can connect any component to one of the digital terminals using a digital coaxial cable (not supplied) or digital optical cable (not supplied).

## IMPORTANT:



- When connecting the DVD player or digital TV using the digital terminal, you also need to connect it to the video jack on the rear. Without connecting it to the video jack, you can view no playback picture.
- After connecting the components using the DIGITAL IN terminals, set the followings correctly if necessary:
  - Set the digital input (DIGITAL IN) terminal setting correctly. For details, see "Setting the Digital Input (DIGITAL IN) Terminals" on page 11.
  - Select the digital input mode correctly. For details, see "Selecting the Analog or Digital Input Mode" on page 11.



When the component has a digital coaxial output terminal, connect it to the DIGITAL 1 (DVD) terminal, using the digital coaxial cable (not supplied).

When the component has a digital optical output terminal, connect it to the DIGITAL 2 (CD) terminal, using the digital optical cable (not supplied).

Before connecting a digital optical cable, unplug the protective plug.



## Notes:

- When shipped from the factory, the DIGITAL IN terminals have been set for use with the following components.
  - DIGITAL 1 (coaxial): For DVD player
  - DIGITAL 2 (optical): For CD player
- When you want to operate the CD player or CD recorder using the COMPU LINK remote control system, connect the target component also as described in "Analog connections" (see page 6).

## Connecting the Power Cord


Before plugging the power cord into an AC outlet, make sure that all connections have been made.

**Plug the power cord into an AC outlet.**

## CAUTIONS:


- Do not touch the power cord with wet hands.
- Do not pull on the power cord to unplug the cord. When unplugging the cord, always grasp the plug so as not to damage the cord.

# Basic Operations



## Turning On the Power

Press STANDBY/ON  $\odot$ /I (or STANDBY/ON  $\odot$ /I AUDIO on the remote control).




On the front panel



From the remote control

The STANDBY lamp goes off. The name of the current source (or station frequency) appears on the display.




Current volume level is shown here

### To turn off the power (into standby mode)

Press STANDBY/ON  $\odot$ /I (or STANDBY/ON  $\odot$ /I AUDIO on the remote control) again.

The STANDBY lamp on the front panel lights up.




### Note:


A small amount of power is consumed in standby mode. To turn the power off completely, unplug the AC power cord.

## Selecting the Source to Play

Press one of the source selecting buttons. The selected source name appears on the display.



On the front panel



From the remote control

- DVD : Select the DVD player.
- VCR : Select the VCR.
- TV SOUND : Select the TV sound.
- CD \* : Select the CD player.
- TAPE/CDR \* : Select the cassette deck (or the CD recorder).
- FM/AM \* : Select an FM or AM (MW/LW) broadcast.
- Each time you press the button, the band alternates between FM and AM (MW/LW).

### Notes:


- When connecting a CD recorder (to the TAPE/CDR jacks), change the source name that appears on the display. See below for details.
- When you have connected some digital source components using the digital terminals (see page 7), you need to select the digital input mode (see page 11).
- When you press one of the source selecting buttons on the remote control marked above with an asterisk (\*), the receiver automatically turns on.

## Changing the source name

When you connect the CD recorder to the TAPE/CDR jacks on the rear panel and select the CD recorder as the source, change the source name shown on the display.



- 1 Press TAPE/CDR (SOURCE NAME).
  - Make sure "TAPE" appears on the display.
- 2 Press and hold SOURCE NAME (TAPE/CDR) until "ASSIGN CDR" appears on the display.



To change the source name from "CDR" to "TAPE," repeat the same procedure above (in step 1, make sure "CDR" appears on the display).

### Note:

Without changing the source name, you can still use the connected component. However, there may be some inconvenience.


- "TAPE" will appear on the display when you select the CD recorder.
- You cannot use the digital input (see page 11) for the CD recorder.
- You cannot use the COMPU LINK remote control system (see page 27) to operate the CD recorder.

# Basic Operations


## Selecting different sources for picture and sound

You can watch picture from a video component while listening to sound from another component.

Press one of the audio source selecting buttons (CD, TAPE/CDR, FM/AM), while viewing the picture from a video component such as the VCR or DVD player, etc.



On the front panel



From the remote control

### Note:


Once you have selected a video source, pictures of the selected source are sent to the TV until you select another video source.

## Adjusting the Volume

### On the front panel:

To increase the volume, turn MASTER VOLUME clockwise.

To decrease the volume, turn it counterclockwise.



### From the remote control:

To increase the volume, press VOLUME +.

To decrease the volume, press VOLUME -.

### CAUTION:

Always set the volume to the minimum before starting any source. If the volume is set at its high level, the sudden blast of sound energy can permanently damage your hearing and/or ruin your speakers.

### Note:

The volume level can be adjusted within the range of "0" (minimum) to "50" (maximum).

## Listening Only with Headphones

You must turn off the speakers when you listen with headphones.

- 1 Connect a pair of headphones to the PHONES jack on the front panel.
- 2 Press SPEAKERS ON/OFF.
  - "HEADPHONE" appears for a while and the H. PHONE indicator lights up on the display.

The H. PHONE indicator lights up.



This cancels the Surround mode currently selected, and activates the HEADPHONE mode.

### HEADPHONE mode

When using the headphones, following signals are output regardless of your speaker setting:

- For 2 channel sources, the front left and right channel signals are output directly from the headphones.
  - For multichannel sources, the front left and right, center, and rear channel signals are down-mixed and then output from the headphones.
- You can enjoy multichannel sound sources using the headphones.

### CAUTION:

Be sure to turn down the volume:


- Before connecting or putting on headphones, as high volume can damage both the headphones and your hearing.
- Before turning on speakers again, as high volume may output from the speakers.

## Turning Off the Sounds Temporarily—Muting



Press **MUTING** **on the remote control** to mute the sound through all speakers and headphones connected.

- “MUTING” appears on the display and the volume turns off (the volume level indicator goes off).



To restore the sound, press **MUTING** again.

- Turning **MASTER VOLUME** on the front panel or pressing **VOLUME +/-** on the remote control also restores the sound.





## Turning Off the Power with the Sleep Timer



You can fall asleep while listening to music—Sleep Timer.

Press **SLEEP** **on the remote control** repeatedly.

- The **SLEEP** indicator lights up on the display, and the shut-off time changes in 10 minutes intervals.



### When the shut-off time comes

The receiver turns off automatically.

To check or change the time remaining until the shut-off time Press **SLEEP** once.

The remaining time (in minutes) until the shut-off time appears.

- To change the shut-off time, press **SLEEP** repeatedly.

### To cancel the Sleep Timer

Press **SLEEP** repeatedly until “**SLEEP 0 MIN**” appears on the display. (The **SLEEP** indicator goes off.)

- Turning off the power also cancels the Sleep Timer.

## Changing the Display Brightness

You can dim the display.

Press **DIMMER**.

- Each time you press the button, the display dims and brightens alternately.



On the front panel



From the remote control

### Note:

Even though you have made the display dimmer, it brightens for a while when you operate the receiver.

## Basic adjustment auto memory

This receiver memorizes sound settings for each source when:

- you turn off the power,
- you change the source, and
- you assign the source name.

When you change the source, the memorized settings for the newly selected source are automatically recalled.

The following can be stored for each source:

- Input attenuator mode (see page 15)
- Balance (see page 15)
- Tone adjustment (see page 15)
- Subwoofer output level (see page 15)
- Surround mode selection (see pages 24 – 26 )

### Notes:

- You cannot assign and store different settings for digital input mode and analog input mode.
- If the source is FM or AM, you can assign a different setting for each band.

## For recording

You can record any sources playing through the receiver to a cassette deck (or a CD recorder) connected to the **TAPE/CDR** jacks and the **VCR** connected to the **VCR** jacks at the same time.


While recording, you can listen to the selected sound source at whatever sound level you like without affecting the sound levels of the recording.

### Note:

The output volume level, tone adjustment (see page 15), and Surround modes (see page 21) cannot affect the recording.

## Signal and speaker indicators on the display

### Signal indicators



### Speaker indicators



The following signal indicators light up—:

- L** : •When **digital input** is selected: Lights up when the left channel signal comes in.  
•When **analog input** is selected: Always lights up.
- R** : •When **digital input** is selected: Lights up when the right channel signal comes in.  
•When **analog input** is selected: Always lights up.
- C** : When the center channel signal comes in.
- LS** : When the left rear channel signal comes in.
- RS** : When the right rear channel signal comes in.
- S** : When the monaural rear channel signal or 2 channel Dolby Surround encoded signal comes in.
- LFE**: When the LFE channel signal comes in.


The speaker indicators light up when both of the following conditions satisfied:

- The corresponding speaker is activated, and
- The corresponding speaker is required for the current playback.

### Note:

When “**SUBWOOFER**” is set to “**YES**” (see page 12), **S.WFR** lights up.

# Basic Settings



## Setting the Digital Input [DIGITAL IN] Terminals




When you use the digital input terminals, register what components are connected to which terminals (DIGITAL 1/2) so that the correct source name will appear when you select the digital source.

**Before you start, remember...**

There is a time limit in doing the following steps. If the setting is canceled before you finish, start from step 1 again.

### 1 Press SETTING repeatedly until "DIGITAL IN" appears on the display.

The display changes to show the current setting.




\* "1DVD 2CD" is the initial setting. If you have already changed the setting, another combination will be shown.

### 2 Press CONTROL UP ▲/DOWN ▼ to select the appropriate digital terminal setting.

- Each time you press the button, the display changes to show the following:

1 DVD 2 CD ↔ 1 DVD 2 TV ↔ 1 DVD 2 CDR ↔  
 1 CD 2 DVD ↔ 1 CD 2 TV ↔ 1 CD 2 CDR ↔  
 1 TV 2 DVD ↔ 1 TV 2 CD ↔ 1 TV 2 CDR ↔  
 1 CDR 2 DVD ↔ 1 CDR 2 CD ↔ 1 CDR 2 TV ↔  
 (back to the beginning)



#### Note:


When shipped from the factory, the DIGITAL IN terminals can be used as the digital input for the following components.

- DIGITAL 1 (coaxial): For DVD player
- DIGITAL 2 (optical): For CD player


## Selecting the Analog or Digital Input Mode

When you have connected digital source components using both the analog connection (see page 6) and the digital connection (see page 7) methods, you need to select the input mode correctly.

### 1 Press one of the source selecting buttons—DVD, TV SOUND, CD, or TAPE/CDR\*—for which you want to change the input mode.



On the front panel



From the remote control

#### Note:


\* Among the sources listed above, you can select the digital input only for the sources which you have selected the digital input terminals for. (See "Setting the Digital Input (DIGITAL IN) Terminals.")

### 2 Select digital input mode.

#### On the front panel:


Press INPUT DIGITAL.

"DIGITAL AUTO" appears on the display and the indicator for the detected signals also lights up.



To change the input mode back to analog input, press INPUT ANALOG.

"ANALOG" appears on the display for a while.



#### From the remote control:

Press ANALOG/DIGITAL.

- Each time you press the button, the input mode alternates between the analog input ("ANALOG") and the digital input ("DIGITAL AUTO").



TO BE CONTINUED TO THE NEXT PAGE



**DIGITAL AUTO** : Select this for the digital input mode. The receiver automatically detects the incoming signal format. (The DIGITAL AUTO indicator lights up on the display, then the digital signal indicator for the detected signals lights up.)

**ANALOG** : Select this for the analog input mode. (Initial setting when shipped from the factory.)

**If the following symptoms occur while playing Dolby Digital or DTS Digital Surround software with “DIGITAL AUTO” selected, follow the procedure below.**

- Sound does not come out at the beginning of playback.
- Noise comes out while searching or skipping chapters or tracks.


**1** Press INPUT DIGITAL (or ANALOG/DIGITAL on the remote control).

- “DIGITAL AUTO” appears on the display.

**2** Press CONTROL UP ▲/DOWN ▼ to select “DOLBY DIGITAL” or “DTS SURROUND” while “DIGITAL AUTO” still remains on the display.

- Each time you press the button, the digital input mode changes as follows:

When “DOLBY DIGITAL” or “DTS SURROUND” is selected, “DIGITAL AUTO” goes off.





- To play back software encoded with Dolby Digital, select “DOLBY DIGITAL.”
- To play back software encoded with DTS Digital Surround, select “DTS SURROUND.”

#### Note:

When you turn off the power or select another source, “DOLBY DIGITAL” and “DTS SURROUND” are canceled and the digital input mode is automatically reset to “DIGITAL AUTO.”

The followings are the analog/digital signal indicators on the display to indicate what type of the signal comes into the receiver.

**ANALOG** : Lights when the analog input is selected.  
**LINEAR PCM** : Lights when Linear PCM signals come in.  
 **DIGITAL** : Lights when Dolby Digital signals come in.  
 • Flashes when “DOLBY DIGITAL” is selected for software not encoded with Dolby Digital signals.  
 : Lights when DTS signals come in.  
 • Flashes when “DTS SURROUND” is selected for software not encoded with DTS signals.

#### Note:

When “DIGITAL AUTO” cannot recognize the incoming signals, no digital signal indicators light up on the display.

## Setting the Speaker Information



To obtain the best possible sound or effect from the Surround modes (see page 18), register the following speakers and subwoofer information after all connections are completed.

The followings are items you can set:

- Subwoofer information—SUBWOOFER
- Speaker size—FRNT SP, CNTR SP, REAR SP
- Speaker distance—UNIT, FRNT DIS, CNTR DIS, REAR DIS
- Crossover frequency—CROSS
- Low frequency effect attenuator—LFE ATT
- Dynamic range compression—D. COMP

#### Before you start, remember...

There is a time limit in doing the following steps. If the setting is canceled before you finish, start from step **1** again.

“NO” for the subwoofer, “LARGE” for the front speakers, and “SMALL” for the center and rear speakers are initial settings. To get best possible sound, change the subwoofer and speaker settings to fit your listening conditions.


### Subwoofer information

Register whether you have connected a subwoofer or not.

**1** Press SETTING repeatedly until “SUBWOOFER” (with the current setting) appears on the display.



**2** Press CONTROL UP ▲/DOWN ▼ to register whether you have connected a subwoofer or not.



- Each time you press the button, the subwoofer setting alternates between “YES” and “NO.”

**YES** : Select this when you have connected a subwoofer. You can adjust the subwoofer output level (see page 15).

**NO** : Select this when you have not connected or have disconnected a subwoofer.



# Basic Settings

## Speaker size

Register the sizes of all the connected speakers.



- When you change your speakers, register the information about the speakers again.

**1** Press **SETTING** repeatedly until “FRNT SP (Front speaker),” “CNTR SP (Center speaker)” or “REAR SP (Rear speaker)” (with the current setting) appears on the display.



**2** Press **CONTROL UP ▲/DOWN ▼** to select the appropriate item about the speaker selected in the above step.

- Each time you press the button, the display changes as follows:



**LARGE** : Select this when the speaker size is relatively large. (See “Notes” below.)

**SMALL** : Select this when the speaker size is relatively small. (See “Notes” below.)

**NONE** : Select this when you have not connected a speaker. (Not selectable for the front speakers)

**3** Repeat steps **1** and **2** to select the appropriate items for other speakers.

### Notes:

- Keep the following comment in mind as reference when adjusting.
  - If the size of the cone speaker unit built in your speaker is greater than 12 cm (4 3/4 inches), select “LARGE,” and if it is smaller than 12 cm (4 3/4 inches), select “SMALL.”
- If you have selected “NO” for the subwoofer setting, you can only select “LARGE” for the front speaker setting.
- If you have selected “SMALL” for the front speaker setting, you cannot select “LARGE” for the center and rear speaker settings.

## Speaker distance

Register the unit you use, then the speaker distance from your listening point.

- If you have set the unit before, start from step **3**.


**1** Press **SETTING** repeatedly until “UNIT” (with the current setting)\* appears on the display.



\* “METER” is the initial setting. If you have already changed the setting, “FEET” will be shown.

**2** Press **CONTROL UP ▲/DOWN ▼** to select the unit.

- Each time you press the button, the setting alternates between “METER” and “FEET.”



**METER** : Speaker distance is shown in meter.

**FEET** : Speaker distance is shown in feet.


**3** Press **SETTING** repeatedly until “FRNT DIS (Front distance),” “CNTR DIS (Center distance)” or “REAR DIS (Rear distance)” (with the current setting)\* appears on the display.




The display shows the current setting in the unit selected in step **2**.

\* “3.0m” is the initial setting for meter and “10FT” is for feet. If you have already changed the setting, another value will be shown.

**4** Press **CONTROL UP ▲/DOWN ▼** to select the appropriate speaker distance.



- If you have selected “METER” in step **2**, the value is changed from “0.3m” to “9.0m” by 0.3 m step.
- If you have selected “FEET” in step **2**, the value is changed from “1FT” to “30FT” by 1 foot step.



Example: In this case,  
set “FRNT DIS” to “3.0m” or “10FT,”  
set “CNTR DIS” to “2.7m” or “9FT” and,  
set “REAR DIS” to “2.4m” or “8FT.”

### Note:

If you have selected “NONE” for the center and rear speakers setting, you cannot set the speaker distance for the center and rear speakers.

## Crossover frequency

Small speakers cannot reproduce the bass sounds efficiently. If you use a small speaker in any position, this receiver automatically reallocates the bass sound elements assigned to the small speaker to the large speakers.

To use this function properly, set this crossover frequency level according to the size of the small speaker connected.


- If you have selected “LARGE” for all speakers, this function will not take effect (“CROSS OFF” appears).

### 1 Press SETTING repeatedly until “CROSS (Crossover)” (with the current setting)\* appears on the display.




\* “100HZ” is the initial setting. If you have already changed the setting, another frequency will be shown.

### 2 Press CONTROL UP ▲/DOWN ▼ to select the crossover frequency level you like to use.



- Each time you press the button, the crossover frequency level changes as follows:



#### Note:

Crossover frequency is not valid for the HEADPHONE mode.

## Low frequency effect attenuator

If the bass sound is distorted while playing back software using **Dolby Digital** or **DTS Digital Surround**, follow the procedure below:


- This function takes effect only when the subwoofer (LFE) signals come in, (with “SUBWOOFER” set to “YES”).

### 1 Press SETTING repeatedly until “LFE ATT (Low Frequency Effect Attenuator)” (with the current setting)\* appears on the display.



\* “0dB” is the initial setting. If you have already changed the setting, “-10dB” will be shown.

### 2 Press CONTROL UP ▲/DOWN ▼ to select the low frequency effect attenuator level.



- Each time you press the button, the setting alternates between “0dB” and “-10dB.”

**0dB** : Normally select this.

**-10dB** : Select this when the bass sound is distorted.

## Dynamic range compression

You can compress the dynamic range (difference between maximum sound and minimum sound) of the reproduced sound. This is useful when enjoying surround sound at night.


- This function takes effect only when playing back a source using **Dolby Digital**.

### 1 Press SETTING repeatedly until “D. COMP (Dynamic range compression)” (with the current setting)\* appears on the display.




\* “MID” is the initial setting. If you have already changed the setting, another setting will be shown.

### 2 Press CONTROL UP ▲/DOWN ▼ to select the appropriate compression level.



- Each time you press the button, the display changes as follows:




**OFF** : Select this when you want to enjoy surround with its full dynamic range. (No effect applied.)

**MID** : Select this when you want to reduce the dynamic range a little.

**MAX** : Select this when you want to apply the compression effect fully. (Useful at night.)

# Sound Adjustments




Once each of following settings has been adjusted, this receiver memorizes the adjustment for each source.

## Attenuating the Input Signal



When the input level of the **analog source** is too high, the sounds will be distorted. If this happens, you need to attenuate the input signal level to prevent the sound distortion.

- 1 Press and hold **INPUT ATT (INPUT ANALOG)** so that the **INPUT ATT** indicator lights up on the display.



- Each time you press and hold the button, the Input Attenuator mode turns on ("INPUT ATT ON") or off ("INPUT NORMAL").

## Adjusting the Front Speakers Output Balance



If the sounds you hear from the front right and left speakers are unequal, you can adjust the speakers output balance.

**Before you start, remember...**


There is a time limit in doing the following steps. If the setting is canceled before you finish, start from step 1 again.

- 1 Press **ADJUST** repeatedly until "**BALANCE**" (with the current setting)\* appears on the display.



- \* "CNTR" (Center) is the initial setting. If you have already changed the setting, another setting will be shown.

- 2 Press **CONTROL UP ▲/DOWN ▼** to adjust the balance.



- Pressing **CONTROL UP ▲** decreases the left channel output from "CNTR" (Center) to "L-21."
- Pressing **CONTROL DOWN ▼** decreases the right channel output from "CNTR" (Center) to "R-21."

## Adjusting the Tone




You can adjust the bass and treble sounds as you like.

**Before you start, remember...**

There is a time limit in doing the following steps. If the setting is canceled before you finish, start from step 1 again.

- 1 Press **ADJUST** repeatedly until "**BASS**" or "**TREBLE**" (with the current setting)\* appears on the display.




- \* "0" is the initial setting. If you have already changed the setting, another number (level) will be shown.

**BASS** : To adjust the bass (-10 to +10).

**TREBLE** : To adjust the treble (-10 to +10).

- 2 Press **CONTROL UP ▲/DOWN ▼** to adjust the bass or treble sounds level.



- Each time you press the button, the sound level changes by  $\pm 2$  steps.

## Adjusting the Subwoofer Output Level


You can adjust the subwoofer output level if you have connected a subwoofer and set the subwoofer information correctly—"YES."

**On the front panel:**

**Before you start, remember...**


There is a time limit in doing the following steps. If the setting is canceled before you finish, start from step 1 again.

- 1 Press **ADJUST** repeatedly until "**SUBWFR (Subwoofer)**" (with the current setting)\* appears on the display.



- \* "0" is the initial setting. If you have already changed the setting, another number (level) will be shown.

- 2 Press **CONTROL UP ▲/DOWN ▼** to adjust the subwoofer output level (-10 to +10).



**From the remote control:**

- 1 Press **SOUND**.

The 10 keys are activated for sound adjustments.



- 2 Press **SUBWOOFER +/-** to adjust the subwoofer output level (-10 to +10).




**Note:**


Subwoofer output level cannot be adjusted when using headphones.

# Tuner Operations

## Front Panel




## Remote Control



## Tuning in Stations Manually

### 1 Press FM/AM to select the band (FM or AM—MW/LW).

The last received station of the selected band is tuned in.




On the front panel



From the remote control


- Each time you press the button, the band alternates between FM and AM (MW/LW).



Ex.: When the FM band is selected.

### 2 Press FM/AM TUNING UP/ DOWN until you find the frequency you want.

- Pressing FM/AM TUNING UP increases the frequency.
- Pressing FM/AM TUNING DOWN decreases the frequency.



#### Notes:

- When you press and hold FM/AM TUNING UP/DOWN for a few seconds in step 2, the frequency keeps changing until a station is tuned in.
- When a station of sufficient signal strength is tuned in, the TUNED indicator lights up on the display.
- When an FM stereo program is received, the STEREO indicator also lights up.

## Using Preset Tuning

Once a station is assigned to a channel number, the station can be quickly tuned. You can preset up to 30 FM and 15 AM (MW/LW) stations.

### To store the preset stations


Before you start, remember...

There is a time limit in doing the following steps. If the setting is canceled before you finish, start from step 2 again.




### 1 Tune in the station you want to preset (see "Tuning in Stations Manually").

- If you want to store the FM reception mode for this station, select the FM reception mode you want. See "Selecting the FM Reception Mode" on page 17.




### 2 Press MEMORY.

"CH-" appears and the channel number position starts flashing on the display for about 5 seconds.




### 3 Press FM/AM PRESET UP/ DOWN to select a channel number while the channel number position is flashing.



# Tuner Operations

## 4 Press MEMORY again while the selected channel number is flashing on the display.

The selected channel number stops flashing.  
The station is assigned to the selected channel number.



## 5 Repeat steps 1 to 4 until you store all the stations you want.

### To erase a stored preset station

Storing a new station on a used number erases the previously stored one.



### To tune in a preset station

#### On the front panel:

## 1 Press FM/AM to select the band (FM or AM—MW/LW).


The last received station of the selected band is tuned in.

- Each time you press the button, the band alternates between FM and AM (MW/LW).



## 2 Press FM/AM PRESET UP/ DOWN until you find the channel you want.

- Pressing FM/AM PRESET UP increases the channel numbers.
- Pressing FM/AM PRESET DOWN decreases the channel numbers.



#### From the remote control:

## 1 Press FM/AM to select the band (FM or AM—MW/LW).

The last received station of the selected band is tuned in and the 10 keys now work for tuner operation.

- Each time you press the button, the band alternates between FM and AM (MW/LW).



## 2 Press 10 keys to select a preset channel number.

- For channel number 5, press 5.
- For channel number 15, press +10 then 5.
- For channel number 20, press +10 then 10.
- For channel number 30, press +10, +10, then 10.



## Selecting the FM Reception Mode

When an FM stereo broadcast is hard to receive or noisy, you can change the FM reception mode while receiving an FM broadcast.

- You can store the FM reception mode for each preset station (see page 16).

## 1 While listening to an FM station, press FM MODE.


- Each time you press the button, the FM reception mode alternates between “AUTO” and “MONO.”



On the front panel



From the remote control



### AUTO

: Normally select this.

When a program is broadcasted in stereo, you will hear stereo sound; when in monaural, you will hear monaural sounds. This mode is also useful to suppress static noise between stations. The AUTO MUTING indicator lights up on the display. (Initial setting)

### MONO

: Select this to improve the reception (but stereo effect will be lost).

In this mode, you will hear noise while tuning into the stations. The AUTO MUTING indicator goes off from the display. (The STEREO indicator also goes off.)

### To restore the stereo effect

Select “AUTO” in step 1.

## Using the RDS (Radio Data System) to Receive FM Stations

RDS allows FM stations to send an additional signal along with their regular program signals. For example, the stations send their station names, as well as information about what type of program they broadcast, such as sports or music, etc.

When tuned to an FM station which provides the RDS service, the RDS indicator lights up on the display.

With the receiver, you can receive the following types of RDS signals.

<b>PS (Program Service):</b>	Shows commonly known station names
<b>PTY (Program Type):</b>	Shows types of broadcast programs
<b>RT (Radio Text):</b>	Shows text messages the station sends
<b>Enhanced Other Network:</b>	See page 20.

### Notes:


- RDS is not available for AM (MW/LW) broadcasts.
- RDS may not operate correctly if the station tuned is not transmitting RDS signal properly or if the signal strength is weak.

## What information can RDS signals provide?

You can see the RDS signals the station sends on the display.

### To show the RDS signals


Press **DISPLAY MODE** while listening to an FM station.



On the front panel

From the remote control

- Each time you press the button, the display changes to show you the following information:



### PS (Program Service):

While searching, "PS" appears and then the station names will be displayed. "NO PS" appears if no signal is sent.

### PTY (Program Type):

While searching, "PTY" appears and then the type of the broadcast program will be displayed. "NO PTY" appears if no signal is sent.

### RT (Radio Text):

While searching, "RT" appears and then text messages the station sends will be displayed. "NO RT" appears if no signal is sent.

### Frequency:

Station frequency (non-RDS service).


## About characters shown on the display

When the display shows PS, PTY, or RT signals, the following characters are used.

- The display cannot show accented letters, "A," for instance, may stand for accented "A's" like "Å, Ä, Æ, Á, À, and Â."

### Notes:

- When pressing **DISPLAY MODE** on the remote control, make sure that you have selected FM station using the remote control. If not, the **DISPLAY MODE** button does not work for tuner operation. (Pressing **FM/AM** activates the remote control for tuner operation.)



- If searching finishes at once, "PS," "PTY," and "RT" will not appear on the display.


## Searching for a Program by PTY Codes

One of the advantages of the RDS service is that you can locate a particular kind of program from the preset channels (see page 16) by specifying the PTY codes.

## To search for a program using the PTY codes

### Before you start, remember...

- The PTY Search is only applicable to preset stations.
- To stop searching any time during the process, press **PTY SEARCH** while searching.
- There is a time limit in doing the following steps. If the setting is canceled before you finish, start from step 1 again on the next page.
- When pressing the buttons on the remote control, make sure that you have selected the FM station using the remote control. If not, the RDS operation buttons do not work for RDS operation. (Pressing **FM/AM** activates the remote control for RDS operation.)





# Tuner Operations

## On the front panel:


- 1 Press **PTY SEARCH** while listening to an FM station.

“PTY SELECT” flashes on the display.



- 2 Press **CONTROL UP ▲/DOWN ▼** until the PTY code you want appears on the display, while “PTY SELECT” is flashing.

The display gives you the PTY codes described to the right.



- 3 Press **PTY SEARCH** again, while the PTY code selected in the previous step is still on the display.

While searching, “SEARCH” and the selected PTY code alternate on the display.

The receiver searches 30 preset FM stations, stops when it finds the one you have selected, and tunes in that station.



### To continue searching after the first stop


Press **PTY SEARCH** again while the indications on the display are flashing.

If no program is found, “NOT FOUND” appears on the display.

## From the remote control:

- 1 Press **PTY SEARCH** while listening to an FM station.

“PTY SELECT” flashes on the display.



- 2 Press **PTY +** or **PTY -** until the PTY code you want appears on the display, while “PTY SELECT” is flashing.

The display gives you the PTY codes described to the right.

- 3 Press **PTY SEARCH** again, while the PTY code selected in the previous step is still on the display.

While searching, “SEARCH” and the selected PTY code alternate on the display.

The receiver searches 30 preset FM stations, stops when it finds the one you have selected, and tunes in that station.

### To continue searching after the first stop

Press **PTY SEARCH** again while the indications on the display are flashing.

If no program is found, “NOT FOUND” appears on the display.

## PTY codes



### When an emergency broadcast (ALARM signal) is sent from an FM station

The receiver automatically tunes in the station except in the following cases:

- When you are listening to non-RDS stations (all AM—MW/LW, some FM stations and other sources).
- When the receiver is in standby mode.

While receiving an emergency broadcast, “ALARM” appears on the display.

### The TEST signal is used for equipment test—whether it can receive the ALARM signal correctly.

The TEST signal makes the receiver work in the same way as the ALARM signal does. If the TEST signal is received, the receiver automatically switches to the station broadcasting the TEST signal. While receiving the test signal, “TEST” appears on the display.



## Switching to a Broadcast Program of Your Choice Temporarily

Another convenient RDS service is called “Enhanced Other Network.”


This allows the receiver to switch temporarily to a broadcast program of your choice (TA, NEWS, and/or INFO) from a different source except in the following cases:

- When you are listening to non-RDS stations (all AM—MW/LW, some FM stations and other sources).
- When the last received FM station is a non-RDS station.
- When the receiver is in standby mode.


### Before you start, remember...

- The Enhanced Other Network function is only applicable to preset stations.

### 1 Press TA/NEWS/INFO repeatedly until the program type you want appears on the display.



- Each time you press the button, the display changes to show the following:



**TA:** Traffic Announcement in your area.

**NEWS:** News.

**INFO:** Program the purpose of which is to impart advice in the widest sense.

### Note:

You can use TA/NEWS/INFO on the remote control after pressing FM/AM.

### CASE 2 If the FM station you are listening to is broadcasting the program you have selected

The receiver continues to receive the station, but the indicator of received PTY code starts flashing.



When the program is over, the indicator of received PTY code stops flashing and remains lit, but the receiver remains in Enhanced Other Network standby mode.

### To stop listening to the program selected by Enhanced Other Network

Press TA/NEWS/INFO again so that the program type (TA/NEWS/INFO) indicator goes off from the display. The receiver exits from Enhanced Other Network and goes back to the previously selected station.

### Notes:

- Enhanced Other Network data sent from some stations may not be compatible with this receiver.
- Enhanced Other Network does not function for some FM stations with RDS service.
- In Enhanced Other Network standby mode, if you carry out synchronized recording (see page 27), Enhanced Other Network standby mode is canceled temporarily. The receiver goes back to Enhanced Other Network standby mode again when you have finished that operation.
- The Enhanced Other Network mode only works when receiving an FM station with the Enhanced Other Network code. (The TA/NEWS/INFO indicator lights up while receiving an AM (MW/LW) station but the Enhanced Other Network function will not work.)
- While listening to a program tuned in by the Enhanced Other Network function, you cannot use source selecting buttons and PTY SEARCH button.

### CAUTION:

When the source alternates intermittently between the station tuned in by the Enhanced Other Network function and the currently selected source, press TA/NEWS/INFO repeatedly to cancel the Enhanced Other Network function. If you do not press the button, the currently tuned station is received finally, and the indication of the Enhanced Other Network program type flashing on the display disappears.

### CASE 1 If there is no station broadcasting the program you have selected

The receiver continues playing the current source (all sources except AM—MW/LW).



When a station starts broadcasting the program you have selected, the receiver automatically switches to the station. The indicator of received PTY code starts flashing.



When the program is over, the receiver goes back to the previously selected source, but still remains in Enhanced Other Network standby mode. The indicator of received PTY code stops flashing and remains lit.

# Creating Realistic Sound Fields

You can use the following Surround modes to reproduce a realistic sound field:

- Dolby Surround
  - Dolby Pro Logic II
  - Dolby Digital
- DTS Digital Surround
- DAP (Digital Acoustic Processor) modes
- All Channel Stereo


## ■ Dolby Surround

### Dolby Pro Logic II\*


**Dolby Pro Logic II** has a newly developed multichannel playback format to decode all 2 channel sources—regular stereo source and Dolby Surround encoded source—into 5.1 channel.

Matrix-based encoding/decoding method for Dolby Pro Logic II makes no limitation for the cutoff frequency of the rear treble and enables stereo rear sound compared to conventional Dolby Pro Logic.


Dolby Pro Logic II enables to reproduce spacious sound from original sound without adding any new sounds and tonal colorations. Dolby Pro Logic II has two modes—**Movie mode** and **Music mode**:

**Pro Logic II Movie (PL II MOVIE)**—suitable for reproduction of Dolby Surround encoded sources bearing the mark . You can enjoy soundfield very close to the one created with discrete 5.1 channel sounds.

**Pro Logic II Music (PL II MUSIC)**—suitable for reproduction of any 2 channel stereo music sources. You can enjoy wide and deep sound by using this mode. For this mode, Panorama control can be selected, which gives “wraparound” sound effect with side-wall image.

- When Dolby Pro Logic II is activated,  PRO LOGIC II indicator lights up on the display.

### Dolby Digital\*

Used to reproduce multichannel sound tracks of the software encoded with Dolby Digital (  ).

- To enjoy the software encoded with Dolby Digital, connect the source component using the digital terminal on the rear of this receiver. (See page 7.)


**Dolby Digital 5.1 ch** encoding method (so-called discrete multichannel digital audio format) records and digitally compresses the left front channel, right front channel, center channel, left rear channel, right rear channel, and LFE channel signals.

Since each channel is completely independent from the other channel signals to avoid interference, you can obtain much better sound quality with much stereo and surround effects.

### Note:

*Dolby Digital software can be roughly grouped into two categories—multichannel (up to “5.1” channel) and 2 channel software. To enjoy surround sounds while playing Dolby Digital 2 ch software, you can use Dolby Pro Logic II.*


## ■ DTS Digital Surround\*\*

Used to reproduce multichannel sound tracks of the software encoded with DTS Digital Surround (  ).

- To enjoy the software encoded with DTS Digital Surround, connect the source component using the digital terminal on the rear of this receiver. (See page 7.)

**DTS Digital Surround** is another discrete multichannel digital audio format available on CD, LD, and DVD software. Compared to Dolby Digital, audio compression ratio is relatively low. This fact allows DTS Digital Surround format to add breadth and depth to the reproduced sounds. As a result, DTS Digital Surround features natural, solid and clear sound.

## Typical Multichannel (5.1 ch) reproduction



\* Manufactured under license from Dolby Laboratories. “Dolby,” “Pro Logic,” and the double-D symbol are trademarks of Dolby Laboratories. Confidential unpublished works. ©1992–1997 Dolby Laboratories, Inc. All rights reserved.

\*\* Manufactured under license from Digital Theater Systems, Inc. US PAT. No. 5,451,942 and other world-wide patents issued and pending. “DTS” and “DTS Digital Surround” are trademarks of Digital Theater Systems, Inc. Copyright 1996 Digital Theater Systems, Inc. All rights reserved.

## ■ DAP (Digital Acoustic Processor) modes

DAP modes have been designed to create important acoustic surround elements.

The sound heard in a live club, dance club, hall or pavilion consists of direct sound and indirect sound—early reflections and reflections from behind. Direct sounds reach the listener directly without any reflection. On the other hand, indirect sounds are delayed by the distances of the ceiling and walls (see the diagram below). These indirect sounds are important elements of the acoustic surround effects. The DAP mode can reproduce a realistic sound field by adding these indirect sounds.

**DAP modes can be used when the front and rear speakers are connected to this receiver (without respect to the center speaker connection: no sound comes out of the center speaker even if it is connected).**


The following DAP modes are provided with this receiver:

<b>LIVE CLUB</b>	: Gives the feeling of a live music club with a low ceiling.
<b>DANCE CLUB</b>	: Gives a throbbing bass beat.
<b>HALL</b>	: Gives clear vocal and the feeling of a concert hall.
<b>PAVILION</b>	: Gives the spacious feeling of a pavilion with a high ceiling.

These DAP modes can be used to add the acoustic surround effects while reproducing 2 channel stereo software—either analog or digital except Dolby Digital and DTS Digital Surround—and can give you a real “being there” feeling.

- When one of the DAP modes is selected, the DSP indicator lights up on the display.

### Creating sound field



## ■ All Channel Stereo

This mode can reproduce a larger stereo sound field using all the connected (and activated) speakers.


**All Channel Stereo can be used when the front and rear speakers are connected to this receiver without respect to the center speaker connection.**

If the center speaker is connected and activated, the same phase of the front left and right signals are output through the center speaker.


All Channel Stereo can be used while reproducing 2 channel stereo software, either analog or digital except Dolby Digital and DTS Digital Surround.

- When All Channel Stereo is selected, the DSP indicator lights up on the display.

### All Channel Stereo reproduction



Sound reproduced from normal stereo



Sound reproduced from All Channel Stereo

Available Surround modes for each input signal

○: Possible / ×: Impossible

Mode Signals	SURROUND OFF (stereo)	DOLBY DIGITAL	DTS SURROUND	PLII MOVIE	PLII MUSIC	LIVE CLUB	DANCE CLUB	HALL	PAVILION	ALL CH STEREO
Dolby Digital (Multichannel)	○	○	×	×	×	×	×	×	×	×
Dolby Digital (2 channel)	○	×	×	○	○	×	×	×	×	×
DTS Digital Surround (Multichannel)	○	×	○	×	×	×	×	×	×	×
DTS Digital Surround (2 channel)	○	×	×	○	○	×	×	×	×	×
Linear PCM	○	×	×	○	○	○	○	○	○	○
Analog	○	×	×	○	○	○	○	○	○	○






















# Creating Realistic Sound Fields

## About Relations between Speaker Layout and Surround Modes

Available Surround modes will vary depending on how many speakers are used with this receiver.

Make sure that you have set the speaker information correctly (see pages 12 to 14).


- If only front speakers are connected, you cannot use Surround modes.
- If rear speakers are not connected, you cannot use DAP modes and All Channel Stereo.

Speaker Layout	Available Surround modes																
<p>When the center and rear speakers are connected (5 channels):</p> 	<p><b>Turning on or off the Surround modes</b></p> <p>Each time you press SURROUND ON/OFF, Surround modes turn on or off.</p> <div> (Remote) </div> <div></div> <p>Last selected Surround mode → SURROUND OFF</p> <p>Ex.: "PL II MUSIC" has been selected.</p> <p><b>Selecting the Surround modes</b></p> <p>Each time you press SURROUND MODE, Surround modes change as follows:</p> <div> (Remote) </div> <div></div> <table><tr><td>PL II MOVIE</td><td>→</td><td>PL II MUSIC</td><td>→</td></tr><tr><td>LIVE CLUB</td><td>→</td><td>DANCE CLUB</td><td>→</td></tr><tr><td>HALL</td><td>→</td><td>PAVILION</td><td>→</td></tr><tr><td>ALL CH STEREO</td><td>→</td><td>(Back to the beginning)</td><td>→</td></tr></table> <p><b>Note:</b></p> <p>When the digital multichannel software such as Dolby Digital or DTS Digital Surround is played back, the appropriate multichannel Surround mode is automatically activated ("DOLBY DIGITAL" or "DTS SURROUND") by pressing SURROUND ON/OFF (with the digital input mode selected).</p> <ul style="list-style-type: none"><li>• For Dolby Digital 2 channel software, you need to select "PLII MUSIC" or "PLII MOVIE" by pressing SURROUND MODE.</li><li>• For more details, see the table on page 22.</li></ul>	PL II MOVIE	→	PL II MUSIC	→	LIVE CLUB	→	DANCE CLUB	→	HALL	→	PAVILION	→	ALL CH STEREO	→	(Back to the beginning)	→
PL II MOVIE	→	PL II MUSIC	→														
LIVE CLUB	→	DANCE CLUB	→														
HALL	→	PAVILION	→														
ALL CH STEREO	→	(Back to the beginning)	→														
<p>When the rear speakers are connected (4 channels):</p> 	<p><b>Turning on or off the Surround modes</b></p> <p>Each time you press SURROUND ON/OFF, Surround modes turn on or off.</p> <div> (Remote) </div> <div></div> <p>PL II MOVIE or PL II MUSIC → SURROUND OFF</p> <p>Ex.: "PL II MUSIC" has been selected.</p> <p><b>Selecting the Surround modes</b></p> <p>Each time you press SURROUND MODE, Surround modes change as follows:</p> <div> (Remote) </div> <div></div> <table><tr><td>PL II MOVIE</td><td>↔</td><td>PL II MUSIC</td></tr></table> <p><b>Note:</b></p> <p>When the digital multichannel software such as Dolby Digital or DTS Digital Surround is played back, the appropriate multichannel Surround mode is automatically activated ("DOLBY DIGITAL" or "DTS SURROUND") by pressing SURROUND ON/OFF (with the digital input mode selected).</p> <ul style="list-style-type: none"><li>• For Dolby Digital 2 channel software, you need to select "PLII MUSIC" or "PLII MOVIE" by pressing SURROUND MODE.</li><li>• For more details, see the table on page 22.</li></ul>	PL II MOVIE	↔	PL II MUSIC													
PL II MOVIE	↔	PL II MUSIC															
<p>When the center speaker is connected (3 channels):</p> 	<p><b>Turning on or off the Surround modes</b></p> <p>Each time you press SURROUND ON/OFF, Surround modes turn on or off.</p> <div> (Remote) </div> <div></div> <p>PL II MOVIE or PL II MUSIC → SURROUND OFF</p> <p>Ex.: "PL II MUSIC" has been selected.</p> <p><b>Selecting the Surround modes</b></p> <p>Each time you press SURROUND MODE, Surround modes change as follows:</p> <div> (Remote) </div> <div></div> <table><tr><td>PL II MOVIE</td><td>↔</td><td>PL II MUSIC</td></tr></table> <p><b>Note:</b></p> <p>When the digital multichannel software such as Dolby Digital or DTS Digital Surround is played back, the appropriate multichannel Surround mode is automatically activated ("DOLBY DIGITAL" or "DTS SURROUND") by pressing SURROUND ON/OFF (with the digital input mode selected).</p> <ul style="list-style-type: none"><li>• For Dolby Digital 2 channel software, you need to select "PLII MUSIC" or "PLII MOVIE" by pressing SURROUND MODE.</li><li>• For more details, see the table on page 22.</li></ul>	PL II MOVIE	↔	PL II MUSIC													
PL II MOVIE	↔	PL II MUSIC															


Before you start, remember...

- Make sure that you have set the speaker information correctly (see pages 12 to 14).
- You cannot adjust the center speaker output level when you have set "CNTR SP" to "NONE."
- You cannot adjust the rear speaker output levels when you have set "REAR SP" to "NONE."
- Remember not to change the speaker setting while using any Surround modes; otherwise, it may be canceled when you deactivate the speakers required for the Surround mode.

## Front Panel



## Remote Control



## Using Dolby Pro Logic II, Dolby Digital and DTS Digital Surround

Once you have adjusted the sound, the adjustment is memorized for each source.

- When playing back digital multichannel software (Dolby Digital 5.1 ch or DTS Digital Surround), the SURROUND MODE button does not work.

### From the remote control:

It will be convenient for you to use the remote control for adjustments, since you can make adjustments from your listening point by using the test signal.

- For selecting Panorama control for Pro Logic II Music, use the buttons on the front panel.

### 1 Setting the analog or digital input mode for the source you like to listen and start playing.

When playing back software encoded with Dolby Digital and DTS Digital Surround, select the digital input mode (see page 11).

### 2 Press SURROUND ON/OFF to activate Surround mode.



Each time you press the button, Surround mode turns on and off alternately.

- If you are playing back software encoded with Dolby Digital multichannel, "DOLBY DIGITAL" is selected.
- If you are playing back software encoded with DTS Digital Surround, "DTS SURROUND" is selected.
- If you are playing back any software other than above, you can select "PL II MUSIC" or "PL II MOVIE" according to the source by pressing SURROUND MODE. (PRO LOGIC II indicator lights up on the display.)



If you like to adjust sound, go to step 3.

TO BE CONTINUED TO THE NEXT PAGE



# Creating Realistic Sound Fields


## 3 Press SOUND.

The 10 keys are activated for sound adjustments.



## 4 Press TEST to check if you can hear the sounds through all the speakers at the equal level.

“TEST TONE L” starts flashing on the display, and a test tone comes out of the speakers in the following order:




### Notes:

- You can adjust the speaker output levels without outputting the test tone.
- No test tone comes out of the center speaker when “CNTR SP” is set to “NONE.”
- No test tone comes out of the rear speakers when “REAR SP” is set to “NONE.”

## 5 Adjust the speaker output levels (–10 to +10).

Adjust the center speaker and rear speakers levels comparing to the sound from the front speakers.

- To adjust the center speaker level, press CENTER +/-.
- To adjust the left rear speaker level, press REAR•L +/-.
- To adjust the right rear speaker level, press REAR•R +/-.



## 6 Press TEST again to stop the test tone.



### On the front panel:

You can also use the buttons on the front panel to adjust the Surround modes. However, no test tone is available when using the buttons on the front panel. So make adjustments while listening to the sound of the source played back.



## 1 Setting the analog or digital input mode for the source you like to listen and start playing.

When playing back software encoded with Dolby Digital and DTS Digital Surround, select the digital input mode (see page 11).

## 2 Press SURROUND ON/OFF to activate Surround mode.

Each time you press the button, Surround mode turns on and off alternately.

- If you are playing back software encoded with Dolby Digital multichannel, “DOLBY DIGITAL” is selected.
- If you are playing back software encoded with DTS Digital Surround, “DTS SURROUND” is selected.
- If you are playing back any software other than above, you can select “PL II MUSIC” or “PL II MOVIE” according to the source by pressing SURROUND MODE. (PRO LOGIC II indicator lights up on the display.)



## 3 Adjust the speaker output levels.

- Press ADJUST repeatedly until one of the following indications (with the current setting)\* appears on the display.




**CENTER** : To adjust the center speaker output level (–10 to +10).

**REAR L** : To adjust the left rear speaker output level (–10 to +10).

**REAR R** : To adjust the right rear speaker output level (–10 to +10).

\* “0” is the initial setting. If you have already changed the setting, another number (level) will be shown.

- Press CONTROL UP ▲/DOWN ▼ to adjust the selected speaker output level.



- Repeat steps 1) and 2) to adjust the other speaker levels.

When you select “PL II MUSIC,” you can go to the following adjustment.

## 4 Turn on Panorama control or off.


- Press ADJUST repeatedly until “PANORAMA” (with the current setting)\* appears on the display.

\*“OFF” is the initial setting. If you have already changed the setting, “ON” will be shown.



- Press CONTROL UP ▲/DOWN ▼ to select if you turn on or off Panorama control.

- Each time you press the button, “ON” and “OFF” change alternately.



<b>ON</b>	: Select this when you like to enjoy “wraparound” sound effect with side-wall image.
<b>OFF</b>	: Select this when you like to enjoy originally recorded sounds.

### To cancel Surround mode

Press SURROUND ON/OFF again so that “SURROUND OFF” appears on the display.

- If Surround mode is canceled while playing back multichannel digital software, all channel signals are mixed and output through the front speakers (and subwoofer, if you have connected a subwoofer and set the subwoofer setting correctly—“YES”).

If you like to adjust sound, go to step 3.

## Using DAP Modes and All Channel Stereo

Once you have adjusted the DAP modes and All Channel Stereo, the adjustment is memorized for each source.

- You cannot use the DAP modes and All Channel Stereo if the rear speakers are not connected or deactivated.
- You cannot adjust the effect level for “ALL CH STEREO.”

### From the remote control:

It will be convenient for you to use the remote control for adjustments, since you can make adjustments from your listening point.

### 1 Start playing 2 channel software—either analog or Linear PCM—and select the source.

### 2 Press SURROUND ON/OFF to activate Surround mode.

When Surround mode turns on, the last selected Surround mode will be activated.

- Each time you press the button, Surround mode turns on and off alternately.



### 3 Press SURROUND MODE repeatedly until one of the DAP modes—“LIVE CLUB,” “DANCE CLUB,” “HALL,” “PAVILION”—or “ALL CH STEREO” appears on the display.

The DSP indicator also lights up on the display.



If you like to adjust sound, go to step 4.

### 4 Press SOUND.

The 10 keys are activated for sound adjustments.




### 5 Adjust the speakers output levels (–10 to +10).

- To adjust the left rear speaker level, press REAR•L +/-.
- To adjust the right rear speaker level, press REAR•R +/-.


For “ALL CH STEREO” only:

- To adjust the center speaker level, press CENTER +/-.



### 6 For DAP modes only: Press EFFECT to select the effect level (1 to 5) you want.

- Each time you press the button, the effect level changes as follows:




As the number increases, selected mode becomes stronger (normally set it to “EFFECT 3”).




### 2 Press SURROUND ON/OFF to activate Surround mode.

When the Surround mode turns on, the last selected Surround mode will be activated.

- Each time you press the button, Surround mode turns on and off alternately.



### 3 Press SURROUND MODE repeatedly until one of the DAP modes—“LIVE CLUB,” “DANCE CLUB,” “HALL,” “PAVILION”—or “ALL CH STEREO” appears on the display. The DSP indicator also lights up on the display.



If you like to adjust sound, go to step 4.

### 4 Adjust the speaker output levels.

#### 1) Press ADJUST repeatedly until one of the following indications (with the current setting)\* appears on the display.




**REAR L** : To adjust the left rear speaker output level (–10 to +10).

**REAR R** : To adjust the right rear speaker output level (–10 to +10).

**CENTER** : For “ALL CH STEREO” only—to adjust the center speaker output level (–10 to +10).

\* “0” is the initial setting. If you have already changed the setting, another number (level) will be shown.

#### 2) Press CONTROL UP ▲/DOWN ▼ to adjust the selected speaker output level.



#### 3) Repeat steps 1) and 2) to adjust the other speaker level.


### 5 For DAP modes only: Adjust the effect level.

#### 1) Press ADJUST repeatedly until “EFFECT” (with the current setting)\* appears on the display.




\* “EFFECT 3” is the initial setting. If you have already changed the setting, another setting will be shown.

#### 2) Press CONTROL UP ▲/DOWN ▼ to select the effect level (1 to 5) you want.



- Each time you press the button, the effect level changes as follows:



As the number increases, selected mode becomes stronger (normally set it to “EFFECT 3”).

#### Note:

You cannot select any DAP mode and All Channel Stereo when software encoded with Dolby Digital or DTS Digital Surround is played back.

### To cancel DAP modes and All Channel Stereo

Press SURROUND ON/OFF so that “SURROUND OFF” appears on the display. The DSP indicator goes off.

### On the front panel:


### 1 Start playing 2 channel software—either analog or Linear PCM—and select the source.



# COMPU LINK Remote Control System

The COMPU LINK remote control system allows you to operate JVC's audio components through the remote sensor on the receiver. To use this remote control system, you need to connect JVC's audio components through the COMPU LINK-4 (SYNCHRO) jacks (see below) in addition to the connections using cables with RCA pin plugs (see page 6).

- Make sure that the AC power cords of these components are unplugged before connection. Plug the AC power cords only after all connections are completed.



## Notes:

- There are four versions of COMPU LINK remote control system. This receiver is equipped with the fourth version—COMPU LINK-4. This version is added systematic operations with the CD recorder to the previous version—COMPU LINK-3.
- If your audio component has two COMPU LINK jacks, you can use either one. If it has only one COMPU LINK jack, connect it so that it is the last item in the series of components.
- To operate the cassette deck or CD recorder using the COMPU LINK remote control system, set the source name correctly. (See page 8.)
- Refer also to the manuals supplied with your audio components.

This remote control system allows you to use four functions listed below.

## Remote Control through the Remote Sensor on the Receiver

You can control the connected audio components through the remote sensor on the receiver using this remote control. Aim the remote control directly at the remote sensor on the receiver. For details, see pages 28 to 30.

## Automatic Source Selection

When you press the play (▶) button on a connected component or on its own remote control, the receiver automatically turns on and changes the source to the component. On the other hand, if you select a new source on the receiver or on the remote control, the selected component begins playing immediately.

In both cases, the previously selected source continues playing without sound for a few seconds.

## Automatic Power On/Off (Standby): only possible with the COMPU LINK-3 and COMPU LINK-4

Both the CD player and cassette deck (or CD recorder) turn on and off (standby) along with the receiver.

When you turn on the receiver, the CD player or cassette deck (or CD recorder) will turn on automatically, depending on which component has been previously selected.

When you turn off the receiver, both the CD player and cassette deck (or CD recorder) will turn off (standby).

## Synchronized Recording

Synchronized recording means the cassette deck starts recording as soon as a CD begins playing.

To use synchronized recording, follow these steps:

**1 Put a tape in the cassette deck and a disc in the CD player.**

**2 Press the record (●) button and the pause (II) button on the cassette deck at the same time.**

This puts the cassette deck into recording pause.

If you do not press the record (●) button and pause (II) button at the same time, the synchronized recording feature will not operate.

**3 Press the play (▶) button on the CD player.**

The source changes on the receiver, and as soon as play starts, the cassette deck starts recording. When the play ends, the cassette deck enters recording pause, and stops about 4 seconds later.

## Notes:

- During synchronized recording, the selected source cannot be changed.
- If the power of any component is shut off during synchronized recording, the COMPU LINK remote control system may not operate properly. In this case, you must start again from the beginning.

# Operating JVC's Audio/Video Components


You can use the remote control to operate other JVC's components.

## Operating Audio Components

### IMPORTANT:

To operate JVC's audio components using this remote control:

- You need to connect JVC's audio components through the COMPU LINK (SYNCHRO) jacks (see page 27) in addition to the connections using cables with RCA pin plugs (see page 6).
- Aim the remote control directly at the remote sensor on the receiver.
- If you use the buttons on the front panel, the remote control will not operate that source. To operate a source with the remote control, the source must be selected using source selecting buttons on the remote control.
- To operate the cassette deck or CD recorder using the COMPU LINK remote control system, set the source name correctly. (See page 8.)
- Refer also to the manuals supplied with your audio components.



### Sound Adjustment

You can always perform the following operations:

**SURROUND ON/OFF** : Turn on or off the Surround modes.

**SURROUND MODE** : Select the Surround modes.

After pressing SOUND, you can use the following buttons for sound adjustment:

**SUBWOOFER +/-** : Adjust the subwoofer output level.

**CENTER +/-** : Adjust the center speaker output level.

**REAR•L +/-** : Adjust the left rear speaker output level.

**REAR•R +/-** : Adjust the right rear speaker output level.

**EFFECT** : Select the DAP effect level.

**TEST** : Turn on or off the test tone output.

### Note:

After adjusting sounds, press the corresponding source selecting button or CD-DISC to operate your target source by using the 10 keys; otherwise, the 10 keys cannot be used for operating your target source.

### Tuner

You can always perform the following operations:

**FM/AM** : Alternate between FM and AM (MW/LW).

**FM MODE** : Change the FM reception mode.

After pressing FM/AM, you can use the following buttons for tuner operations:

**1 – 10, +10** : Select a preset channel number directly.

- For channel number 5, press 5.
- For channel number 15, press +10, then 5.
- For channel number 20, press +10, then 10.

**DISPLAY MODE** : Shows the RDS signals.

**PTY SEARCH** : Searches for a program by PTY codes.







**PTY +/-** : Selects the PTY codes.

**TA/NEWS/INFO** : Selects a broadcast program type.

# Operating JVC's Audio/Video Components







## CD player

After pressing CD, you can use the following buttons for CD operations:

	: Start playback.
	: Return to the beginning of the current (or previous) track.
	: Skip to the beginning of the next track.
	: Stop playback.
	: Pause playback. To release it, press  .
<b>1 – 10, +10</b>	: Select a track number directly. <ul style="list-style-type: none"><li>• For track number 5, press 5.</li><li>• For track number 15, press +10, then 5.</li><li>• For track number 20, press +10, then 10.</li></ul>






## CD changer

After pressing CD-DISC, you can use the following buttons for CD changer operations:

	: Start playback.
	: Return to the beginning of the current (or previous) track.
	: Skip to the beginning of the next track.
	: Stop playback.
	: Pause playback. To release it, press  .
<b>1 – 6, 7/P</b>	: Select the number of a disc installed in a CD changer.

## Cassette deck

After pressing TAPE/CDR, you can use the following buttons for cassette deck operations:








	: Start playback.
<b>FF</b>	: Fast wind the tape from left to right.
<b>REW</b>	: Fast wind the tape from right to left.
	: Stop playback or recording.
	: Pause playback. To release it, press  .
<b>REC PAUSE</b>	: Press this button to enter recording pause. Press this button then  to start recording.

### Note:

Before starting the above operations, make sure that you have changed the source name correctly. See page 8.

## CD recorder

After pressing TAPE/CDR, you can use the following buttons for CD recorder operations:

	: Start playback.
	: Return to the beginning of the current (or previous) track.
	: Skip to the beginning of the next track.
	: Stop playback or recording.
	: Pause playback. To release it, press  .
<b>REC PAUSE</b>	: Press this button to enter recording pause. Press this button then  to start recording.

### Note:

Before starting the above operations, make sure that you have changed the source name correctly. See page 8.

## Operating Video Components

### IMPORTANT:

To operate JVC's video components using this remote control:

- Some JVC's VCRs can accept two types of the control signals—remote code "A" and "B." Before using this remote control, make sure that the remote control code of the VCR connected to the VCR jacks is set to code "A."
- Aim the remote control directly at the remote sensor on each component, not on the receiver.

### VCR

You can always perform the following operations:





#### STANDBY/ON VCR

: Turn on or off a VCR.

#### VCR CH +/-

: Change the TV channels on the VCR.

After pressing VCR (source selecting button), you can use the following buttons for VCR operations:

	: Start playback.
<b>FF</b>	: Fast wind a tape.
<b>REW</b>	: Rewind a tape.
	: Stop playback or recording.
<b>II</b>	: Pause playback. To release it, press  .
<b>REC PAUSE</b>	: Press this button to enter recording pause. Press this button then  to start recording.






### DVD player

You can always perform the following operations:

#### STANDBY/ON DVD


: Turn on or off a DVD player.

After pressing DVD (source selecting button), you can use the following buttons for DVD operations:

	: Start playback.
	: Return to the beginning of the current (or previous) chapter.
	: Skip to the beginning of the next chapter.
	: Stop playback.
<b>II</b>	: Pause playback. To release it, press  .

### DVD menu operations

After pressing DVD (source selecting button), you can use the following buttons for DVD menu operations:



**MENU** : Display or erase the menu screen.

 : Select an item on the menu screen.

**ENTER** : Enter a selected item.

### TV

You can always perform the following operations:

#### STANDBY/ON TV

: Turn on or off a TV.

**TV/VIDEO** : Change the input mode (TV tuner and video input).

**TV VOLUME +/-** : Adjust the volume.

**TV CH +/-** : Change the channels.





After pressing TV SOUND (source selecting button), you can use the following buttons for TV operations:

**1 - 9, 0, 100+ (+10)** : Select a channel.

**RETURN (10)** : Function as the RETURN button.

# Troubleshooting

Use this chart to help you solve daily operational problems. If there is any problems you cannot solve, contact your JVC's service center.

PROBLEM	POSSIBLE CAUSE	SOLUTION
The power does not come on.	The power cord is not plugged in.	Plug the power cord into an AC outlet.
No sound from speakers.	Speaker signal cables are not connected.	Check speaker wiring and reconnect if necessary.
	The SPEAKERS ON/OFF button is not set correctly.	Press SPEAKERS ON/OFF button correctly.
	An incorrect source is selected.	Select the correct source.
	Muting is activated.	Press MUTING to cancel the mute.
	An incorrect input mode (analog or digital) is selected.	Select the correct input mode (analog or digital).
Sound from one speaker only.	Connections are incorrect.	Check connections. For analog connections, see page 6. For digital connections, see page 7.
	Speaker signal cables are not connected properly.	Check speaker wiring and reconnect if necessary.
	The balance is set to one extreme.	Adjust the balance properly (see page 15).
Continuous hiss or buzzing during FM reception.	Incoming signal is too weak.	Connect an outdoor FM antenna or contact your dealer.
	The station is too far away.	Select a new station.
	An incorrect antenna is used.	Check with your dealer to be sure you have the correct antenna.
	Antennas are not connected properly.	Check connections.
Occasional cracking noise during FM reception.	Ignition noise from automobiles.	Move the antenna farther from automobile traffic.
“OVERLOAD” starts flashing on the display.	Speakers are overloaded because of high volume.	1. Press STANDBY/ON  on the front panel to turn off the receiver. 2. Stop the playback source. 3. Turn on the receiver again, and adjust the volume.
	Speakers are overloaded because of short circuit of speaker terminals.	Press STANDBY/ON  on the front panel, then check the speaker wiring. If “OVERLOAD” does not disappear, unplug the AC power cord, then plug it back again. If speaker wiring is not short-circuited, contact your dealer.
“DSP MICOM NG” starts flashing on the display.	The built-in microcomputer is not functioning correctly.	Press STANDBY/ON  on the front panel to turn off the receiver. After unplugging the power cord, consult your dealer.
The STANDBY lamp lights up after turning on the power, but soon the receiver turns off (into standby mode).	The receiver is overloaded because of a high voltage.	Press STANDBY/ON  on the front panel to turn off the receiver. After unplugging the power cord, consult your dealer.
Remote control does not work.	There is an obstruction in front of the remote sensor on the receiver.	Remove the obstruction.
	Batteries are weak.	Replace batteries.
Remote control does not work as you intend.	The remote control is not ready for your intended operation.	Press SOUND or a source selecting button first, then press the buttons you want to use. (See pages 28 to 30).

## Amplifier

### Output Power

At Stereo operation:		
Front channels:	100 W per channel, min. RMS, both channels driven into 8 $\Omega$ at 1 kHz with no more than 0.9% total harmonic distortion. (IEC268-3/DIN)	
At Surround operation:		
Front channels:	100 W per channel, min. RMS, driven into 8 $\Omega$ at 1 kHz with no more than 0.8% total harmonic distortion.	
Center channel:	100 W, min. RMS, driven into 8 $\Omega$ at 1 kHz, with no more than 0.8% total harmonic distortion.	
Rear channels:	100 W per channel, min. RMS, driven into 8 $\Omega$ at 1 kHz, with no more than 0.8% total harmonic distortion.	

## Audio

Audio Input Sensitivity/Impedance (1 kHz):	CD, TAPE/CDR, TV SOUND, VCR, DVD:	220 mV/47 k $\Omega$
Audio Input (DIGITAL IN)* :	Coaxial: DIGITAL 1 (DVD):	0.5 V (p-p)/75 $\Omega$
	Optical: DIGITAL 2 (CD):	-21 dBm to -15 dBm (660 nm $\pm$ 30 nm)
	* Corresponding to Linear PCM, Dolby Digital, and DTS Digital Surround (with sampling frequency — 32 kHz, 44.1 kHz, 48 kHz).	
Audio Output Level:	TAPE/CDR, VCR:	220 mV
Signal-to-Noise Ratio ('66 IHF/DIN):	CD, TAPE/CDR, TV SOUND, VCR, DVD:	87 dB/67 dB
Frequency Response (8 $\Omega$ ):	CD, TAPE/CDR, TV SOUND, VCR, DVD:	20 Hz to 20 kHz ( $\pm$ 1 dB)
Tone Control:	Bass (100 Hz):	$\pm$ 10 dB
	Treble (10 kHz):	$\pm$ 10 dB

## Video

Video Input Sensitivity/Impedance:		
Composite video:	VCR, DVD:	1 V (p-p)/75 $\Omega$
Video Output Level/Impedance:		
Composite video:	VCR, MONITOR OUT:	1 V (p-p)/75 $\Omega$
Synchronization:	Negative	
Signal-to-Noise Ratio:	45 dB	

## FM tuner (IHF)

Tuning Range:	87.50 MHz to 108.00 MHz
Usable Sensitivity:	Monoaural: 17.0 dBf (1.95 $\mu$ V/75 $\Omega$ )
50 dB Quieting Sensitivity:	Monoaural: 21.3 dBf (3.2 $\mu$ V/75 $\Omega$ )
	Stereo: 41.3 dBf (31.5 $\mu$ V/75 $\Omega$ )
Signal-to-Noise Ratio (IHF-A weighted):	Monoaural: 78 dB at 85 dBf
	Stereo: 73 dB at 85 dBf
Total Harmonic Distortion:	Monoaural: 0.4% at 1 kHz
	Stereo: 0.6% at 1 kHz
Stereo Separation at REC OUT:	35 dB at 1 kHz
Alternate Channel Selectivity:	45 dB: ( $\pm$ 400 kHz)
Frequency Response:	30 Hz to 15 kHz: (+0.5 dB, -3 dB)

## AM tuner

Tuning Range:	MW:	522 kHz to 1 629 kHz
	LW:	144 kHz to 288 kHz
Usable Sensitivity:	Loop antenna:	400 $\mu$ V/m
Signal-to-Noise Ratio:	50 dB (100 mV/m)	

## General

Power Requirements:	AC 230V $\sim$ , 50 Hz
Power Consumption:	200 W (at operation)
	2 W (in standby mode)
Dimensions (W x H x D):	435 mm x 146.5 mm x 416 mm (17 <sup>3</sup> / <sub>16</sub> in. x 5 <sup>13</sup> / <sub>16</sub> in. x 16 <sup>7</sup> / <sub>16</sub> in.)
Mass:	8.8 kg (19.5 lbs)

