

SUPERIOR FLEXIBILITY AND USABILITY.











Ethernet





Automatic

2-Sided





Second Tray



50-Page Auto Document Feeder

Overview:

Time-Saving Shortcuts

Enhance efficiency and productivity with time-saving shortcuts, including Scan to Network, Scan to Email and Scan to PDF.

Print from Anywhere

Provides the flexibility of networking via Ethernet or wireless-N.1

Affordable Printing

Save on what you print most with high-yield supplies that deliver three times the number of pages as standard yield cartridges.²

Rapid Scanning

Quickly scan documents using the 50-sheet automatic document feeder.

Eco-Friendly Printing

Reduce paper consumption by up to 50% with automatic two-sided printing.

Multiple Media Support

Easily load different types of paper with the optional 550-sheet tray that boosts plain paper input capacity to 700 sheets.



Lexmark 1-Touch Shortcuts

Simplify everyday tasks with Lexmark productivity 1-touch shortcuts. Eliminate unnecessary steps and save time by customizing shortcuts to run commonly performed workflows.

Scan to Email

Scan to Network

Customizable Copy

Sometimes faxing isn't convenient or send it directly to an email account.

Reduce clutter and easily share documents: Save time and make custom available. Easily scan a document and scan a document and send the image to a personal or shared network folder.

copies more easily by automating commonly selected copy settings.

	Сору	
	Scan	
	Photo	-
System ready.		

Product specifications	Lexmark Pro715	
Function	Color Copying, Color Faxing, Color Printing, Color Scanning	
Printing		
Print Technology	Thermal Inkjet	
Color Technology	4 Color Inkjet - Cyan, Magenta, Yellow, Black	
Laser Quality Print Speed: Up to	Black: 10 ppm in accordance with ISO/IEC 24734 / OMY: 6 ppm in accordance with ISO/IEC 24734	
Maximum Print Speed: Up to	Black, Draft: 35 ppm / Color, Draft: 30 ppm	
Paper Input Capacity: Up to	Standard: 150 pages 20 lb or 75 gsm bond / Maximum: 700 pages 20 lb or 75 gsm bond	
Paper Output Capacity, Standard: Up to	50 pages 20 lb or 75 gsm bond	
Memory, Standard	256 MB	
Print Resolution, Color	Up to 4800 x 1200 dpi	
Duplex (2-sided) Printing	Integrated Duplex	
Printer Languages (Standard)	PCL 5c Emulation, PCL 6 Emulation, PostScript 3 Emulation, PDF 1.6, Direct Image	
Recommended Monthly Page Volume ³	200 - 930 pages	
Scanning		
Scan Technology	CIS with 48 bit depth	
Scanner Type	Flatbed scanner with ADF	
ADF Paper Input Capacity: Up to	50 pages 20 lb or 75 gsm bond	
Optical Scan Resolution	1200 x 1200 dpi	
Scan Area, Maximum	8.5 x 14 inches	
Copying		
Reduce / Enlarge Range	25 - 400%	
Maximum Copy Speed: Up to	Black, Draft: 25 cpm / Color, Draft: 21 cpm	
Faxing		
Modem Speed	33.6 Kbps	
Compatibility		
Media Sizes Supported	10 Envelope, 7 3/4 Envelope, 9 Envelope, A4, A5, B5 Envelope, C5 Envelope, DL Envelope, B5, Custom, Hagaki Card, Index Card, Executive,	
· · · · · · · · · · · · · · · · · · ·	Folio, Legal, Letter, 4 x 6 in., Statement, L, 2L, 5 x 7 in., 13 x 18 cm, 10 x 15 cm, 10 x 20 cm, 4 x 8 in., Oficio, A6	
Media Types Supported	Card Stock, Envelopes, Labels, Plain Paper, Transparencies, Banner (A4 or Letter), Hagaki Card, Iron-On Transfers, Photo Paper, Heavy Weight	
21	Matte Paper	
Apple Macintosh Operating Systems Supported	Mac OS X (10.4, 10.5, 10.6)	
Microsoft Windows Operating Systems Supported	XP, Server 2003, XP x64, Server 2003 x64, Vista, Vista x64, Server 2008, Server 2008 x64, Windows 7, Windows 7, Server 2008 R2	
Ink Cartridge Compatibility	150 - Riack Oven Magente Vellow	
	150 Black, Cyan, Magenta, Yellow High Yield 150XLA - Black, Cyan, Magenta, Yellow High Yield	
	150XLA - Black, Cyan, Magenta, Yellow High Yield	
	155XL - Black High Yield	
Standard Ports	Ethernet 10/100BaseTX (RJ-45), USB 2.0 Specification Hi-Speed Certified (Type B), 802.11b/a/n Wireless, Front USB 2.0 Specification Hi-Speed	
	Certified Port (Type A)	
General	Contrade - On (1)porty	
Size (in H x W x D)	9.88 x 18.31 x 15.87 in.	
Packaged Size (in H x W x D)	19.17 x 22.01 x 12.83 in.	
Weight (lb.)	20.0 lb.	
Packaged Weight (lb.)	26.05 lb.	
Product Warranty	1-Year Exchange, Next Business Day	
Display	2.4 inch (60 mm) Color LCD display	
Standard box contents	Lexmark Pro715 All-In-One printer, Printhead, One each: black, cyan, magenta and yellow cartridges*, Quick setup sheet, Quick Reference Guid	
	/ User's Guide on CD-ROM, Installation software on CD-ROM, Power supply and cord, Wireless setup cable for USB connection, RJ-11 Phone	
	cable or adapter, Fax Guide, Service information and statement of limited warranty	
	*Licensed Return Program Cartridges	
	Eloniou notari i rogram Oditnugoo	



¹ When used with a wireless-N enabled router. Also subject to the range of the router. Compatible with Wi-Fi CERTIFIED IEEE 802.11 b/g/n routers.
² XL cartridges not included. Available for aftermarket purchase.
³ "Recommended Monthly Page Volume" is a range of pages that helps customers evaluate Lexmark's product offerings based on the average number of pages customers plan to print on the device each month. Lexmark recommends that the number of pages per month be within the stated range for optimum device performance, based on factors including: supplies replacement intervals, paper loading intervals, speed, and typical customer usage.

Lexmark and Lexmark with the diamond design are trademarks of Lexmark International, Inc., registered in the United States and/or other countries. All other trademarks are the property of their respective owners. The USB-IF logos are trademarks of Universal Serial Bus Implementers Forum, Inc. Mac and Macintosh are trademarks of Apple Computer, Inc., registered in the United States and other countries. ENERGY STAR® is a U.S. registered mark. Microsoft, Windows, the Windows Vista, and the Windows Vista and the Windows Vista and other countries. ENERGY STAR® is a U.S. registered mark. Microsoft, Windows, the Windows Vista, and the Windows Vista and the areademarks or registered trademarks of Microsoft Corporation in the United States and other countries. Enformation in this document is subject to change without notice.

