

## X1180

## Easy All-In-One



# Personal productivity starts here. The Lexmark X1180



All-In-One is ideal for your personal printing, scanning and copying needs.

## **USES**

- Printing letters, web pages and homework
- Scanning documents and photos
- Black and white or colour copies

## **KEY FEATURES**

- Flatbed copier perfect for documents, photos and more
- Up to 4800 x 1200 dpi for great print quality
- 48 bit and 600 x 1200 dpi scanner for sharp results
- **■** PC connected colour copy



## **Print**

#### ■ Resolution:

Mode (dpi)	Glossy paper	Other media
Best	4800 x 1200	2400 x 1200
Better	2400 x 1200	1200 x 1200
Normal	1200 x 1200	600 x 600
Quick	600 x 600	300 x 600

- Ink drop size:24 pL black drop size7 pL colour drop size
- Acoustics: 44 dBA or less (600 dpi in Normal Quality)
- Duty cycle: 2 000/month
- Print Technology: Thermal Inkjet 4 Colour – Cyan, Magenta, Yellow, Black
- Speed:

Mode	Quick (ppm)	Normal (ppm)
Black	Up to 14	up to 10
Colour	Up to 8	up to 3

## Scan

- Resolution:600 x 1200 dpi (optical)9 600 x 9 600 dpi (enhanced)
- Colour depth:
  48 bits internal True Colour
  24 bits external True Colour
  16 bits internal Grey Mode
  8 bits external Grey Mode
  1 bit Per Pixel Text/Line Art
- Scan area: 216 x 297 mm
- Removable cover
- Twain driver includes preview and online options for resolution, scan mode, crop etc.
- No warm up time
- Acoustics: 38 dBA or less (300 dpi)
- Scan Technology: Flatbed CIS scanner

## Copy

- Copy via Host computer
- Up to 99 copies at one time (selectable via computer)
- Reduce/Enlarge: 25% to 400% selectable via computer
- Acoustics: 44 dBA or less (300 dpi scan, 600 dpi print quality)
- Speed:

Mode	Quick (ppm)
Black	Up to 13
Colour	Up to 5

#### **TECHNOLOGY**



## Supplies

#### BLACK CARTRIDGE COLOUR CARTRIDGE

■ No. 17: up to 205 pages\* at 5% coverage

■ No. 27: up to 140 pages\* at 15% coverage

## Miscellaneous

■ Max. paper weight:

■ Input/Output tray:

■ Paper Handling Technology:

■ Memory:

■ Interface:

■ Lexmark guarantee:

Power requirements:

■ Windows 98, ME, 2000, XP

■ Mac OS 9, OS X

■ Minimum system requirements:

Operating system	Processor Speed (Mhz)	RAM (MB)	Hard disc space (MB)	Virtual Memory (MB)
Windows 98	Pentium II 233	64	286	N/A
Windows ME	Pentium II 233	128	286	N/A
Windows 2000	Pentium II 233	128	286	286
Windows XP	Pentium II 300	128	500	286
Mac OS 9.2.2	G3 300	128	250	129
Mac OS X	G3 300	128	250	N/A

500 gsm

1 year

Accu-Feed™

**RAM 256 KB** 

up to 100 sheets/25 sheets

220v - 240v input voltage

USB (USB 2.0 full speed compatible)

## LOGISTICAL INFORMATION

#### *In the box*

- Lexmark X1180 All-In-One
- Power supply and line cord
- High-Resolution Black Cartridge No. 17
- High-Resolution Colour Cartridge No. 27
- Set-up Sheet and User's Guide
- Installation CD including Printer Drivers: Twain Driver, Lexmark Photo Editor, OCR software, Fax software, User's Guide

### Weight and dimensions

■ Machine retracted: 445 mm (W) x 308 mm (D) x 163 mm (H)
■ Machine extended: 445 mm (W) x 488 mm (D) x 276 mm (H)

■ Machine weight: 4.1 kg■ Packaged weight: 4.9 kg

■ Packaging dimension: 56 cm (W) x 24 cm (D) x 41 cm (H)



<sup>\*</sup> Approximate number of pages printable per cartridge in normal mode (600 x 600 dpi). Yield may vary based on factors such as machine model, media, print mode, print file type and print application.