

$V_{DSM}$	$=$	<b>2800 V</b>	<h1 style="margin: 0;">Phase Control Thyristor</h1> <h1 style="margin: 0;">5STP 33L2800</h1>
$I_{TAVM}$	$=$	<b>3740 A</b>	
$I_{TRMS}$	$=$	<b>5880 A</b>	
$I_{TSM}$	$=$	<b>60000 A</b>	
$V_{T0}$	$=$	<b>0.95 V</b>	
$r_T$	$=$	<b>0.100 mΩ</b>	


- Patented free-floating silicon technology
- Low on-state and switching losses
- Designed for traction, energy and industrial applications
- Optimum power handling capability
- Interdigitated amplifying gate

### Blocking

Part Number	5STP 33L2800	5STP 33L2600	5STP 33L2200	Conditions
$V_{DRM}$ $V_{RRM}$	2800 V	2600 V	2200 V	$f = 50 \text{ Hz}$ , $t_p = 10\text{ms}$
$V_{RSM1}$	3000 V	2800 V	2400 V	$t_p = 5\text{ms}$ , single pulse
$I_{DRM}$	$\leq 400 \text{ mA}$			$T_j = 125^\circ\text{C}$
$I_{RRM}$	$\leq 400 \text{ mA}$			
$dV/dt_{crit}$	$1000 \text{ V}/\mu\text{s}$			Exp. to $0.67 \times V_{DRM}$ , $T_j = 125^\circ\text{C}$

### Mechanical data

$F_M$	Mounting force	nom.	70 kN
		min.	63 kN
		max.	84 kN
$a$	Acceleration		
	Device unclamped		$50 \text{ m/s}^2$
	Device clamped		$100 \text{ m/s}^2$
$m$	Weight		1.45 kg
$D_S$	Surface creepage distance		36 mm
$D_a$	Air strike distance		15 mm



## On-state

$I_{TAVM}$	Max. average on-state current	3740 A	Half sine wave, $T_C = 70^\circ\text{C}$	
$I_{TRMS}$	Max. RMS on-state current	5880 A		
$I_{TSM}$	Max. peak non-repetitive	60000 A	$t_p = 10\text{ ms}$	$T_j = 125^\circ\text{C}$
	surge current	65000 A	$t_p = 8.3\text{ ms}$	After surge:
$I^2t$	Limiting load integral	18000 $\text{kA}^2\text{s}$	$t_p = 10\text{ ms}$	$V_D = V_R = 0\text{V}$
		17500 $\text{kA}^2\text{s}$	$t_p = 8.3\text{ ms}$	
$V_T$	On-state voltage	1.23 V	$I_T = 3000\text{ A}$	$T_j = 125^\circ\text{C}$
$V_{T0}$	Threshold voltage	0.95 V	$I_T = 2000 - 6000\text{ A}$	
$r_T$	Slope resistance	0.100 $\text{m}\Omega$		
$I_H$	Holding current	30-100 mA	$T_j = 25^\circ\text{C}$	
		15-60 mA	$T_j = 125^\circ\text{C}$	
$I_L$	Latching current	100- mA	$T_j = 25^\circ\text{C}$	
		100- mA	$T_j = 125^\circ\text{C}$	

## Switching

$di/dt_{crit}$	Critical rate of rise of on-state current	250 A/ $\mu\text{s}$	Cont. $f = 50\text{ Hz}$	$V_D \leq 0.67 \cdot V_{DRM}$ , $T_j = 125^\circ\text{C}$ $I_{TRM} = 4500\text{ A}$ $I_{FG} = 2\text{ A}$ , $t_r = 0.5\text{ }\mu\text{s}$
		500 A/ $\mu\text{s}$	60 sec. $f = 50\text{ Hz}$	
$t_d$	Delay time	$\leq 3.0\text{ }\mu\text{s}$	$V_D = 0.4 \cdot V_{DRM}$	$I_{FG} = 2\text{ A}$ , $t_r = 0.5\text{ }\mu\text{s}$
$t_q$	Turn-off time	$\leq 400\text{ }\mu\text{s}$	$V_D \leq 0.67 \cdot V_{DRM}$ $dv_D/dt = 20\text{ V}/\mu\text{s}$	$I_{TRM} = 4500\text{ A}$ , $T_j = 125^\circ\text{C}$ $V_R > 200\text{ V}$ , $di_T/dt = -5\text{ A}/\mu\text{s}$
$Q_{rr}$	Recovery charge	min	2000 $\mu\text{As}$	
		max	4000 $\mu\text{As}$	

## Triggering

$V_{GT}$	Gate trigger voltage	2.6 V	$T_j = 25^\circ$
$I_{GT}$	Gate trigger current	400 mA	$T_j = 25^\circ$
$V_{GD}$	Gate non-trigger voltage	0.3 V	$V_D = 0.4 \times V_{DRM}$
$I_{GD}$	Gate non-trigger current	10 mA	$V_D = 0.4 \times V_{DRM}$
$V_{FGM}$	Peak forward gate voltage	12 V	
$I_{FGM}$	Peak forward gate current	10 A	
$V_{RGM}$	Peak reverse gate voltage	10 V	
$P_G$	Gate power loss	3 W	

### Thermal

$T_{jmax}$	Max. operating junction temperature range	125 °C	
$T_{stg}$	Storage temperature range	-40...140 °C	
$R_{thJC}$	Thermal resistance junction to case	14 K/kW	Anode side cooled
		14 K/kW	Cathode side cooled
		7 K/kW	Double side cooled
$R_{thCH}$	Thermal resistance case to heat sink	3 K/kW	Single side cooled
		1.5 K/kW	Double side cooled

Analytical function for transient thermal impedance:

$$Z_{thJC}(t) = \sum_{i=1}^n R_i(1 - e^{-t/\tau_i})$$

i	1	2	3	4
$R_i(K/kW)$	4.7	0.853	1.07	0.49
$\tau_i(s)$	0.4787	0.0824	0.0104	0.0041




Fig. 1 Transient thermal impedance junction to case.

On-state characteristic model:

$$VT = A + B \cdot iT + C \cdot \ln(iT + 1) + D \cdot \sqrt{IT}$$

Valid for  $i_T = 400 - 11000$  A

A	B	C	D
0.731174	0.000079	0.017903	0.002314




Fig. 2 On-state characteristics.  $T_j=125^\circ\text{C}$ , 10ms half sine




Fig. 3 On-state characteristics.




Fig. 4 On-state power dissipation vs. mean on-state current. Turn - on losses excluded.




Fig. 5 Max. permissible case temperature vs. mean on-state current.




Fig. 6 Surge on-state current vs. pulse length. Half-sine wave.




Fig. 7 Surge on-state current vs. number of pulses. Half-sine wave, 10 ms, 50Hz.




Fig. 8 Gate trigger characteristics.




Fig. 9 Max. peak gate power loss.




Fig. 10 Recovery charge vs. decay rate of on-state current.




Fig. 11 Peak reverse recovery current vs. decay rate of on-state current.

Turn - off time, typical parameter relationship.




Fig. 12  $t_q/t_{q1} = f_1(T_j)$




Fig. 13  $t_q/t_{q1} = f_2(-di_T/dt)$




Fig. 14  $t_q/t_{q1} = f_3(dv/dt)$

$$t_q = t_{q1} \cdot f_1(T_j) \cdot f_2(-di_T/dt) \cdot f_3(dv/dt)$$

$t_{q1}$  : at normalized values (see page 2)  
 $t_q$  : at varying conditions

# Turn-on and Turn-off losses




Fig. 15  $W_{on} = f(I_T, t_p)$ ,  $T_j = 125^\circ\text{C}$ .  
Half sinusoidal waves.




Fig. 16  $W_{on} = f(I_T, di/dt)$ ,  $T_j = 125^\circ\text{C}$ .  
Rectangular waves.




Fig. 17  $W_{off} = f(V_0, I_T)$ ,  $T_j = 125^\circ\text{C}$ .  
Half sinusoidal waves.  $t_p = 10 \text{ ms}$ .




Fig. 18  $W_{off} = f(V_0, di/dt)$ ,  $T_j = 125^\circ\text{C}$ .  
Rectangular waves.

$P_{TOT} = P_T + W_{on} \cdot f + W_{off} \cdot f$   
 $W_{off} \text{ at } V_{RRM}/V_c = 1.3-1.5$   
 $P_T = \frac{1}{T} \int_0^T i_T \cdot v \cdot dt$

ABB Semiconductors AG reserves the right to change specifications without notice.



**ABB Semiconductors AG**  
 Fabrikstrasse 3  
 CH-5600 Lenzburg, Switzerland

Doc. No. 5SYA1011-03 Sep. 01

Telephone +41 (0)62 888 6419  
 Fax +41 (0)62 888 6306  
 Email [abbsem@ch.abb.com](mailto:abbsem@ch.abb.com)  
 Internet [www.abbsem.com](http://www.abbsem.com)