

#### MATERIAL SAFETY DATA SHEET

#### Section 1 - Product and Company Identification

 

 Product Name:
 Cyano (CN) Bulk SPE Sorbent

 Agilent Part Number:
 189-0602

 Date Prepared:
 09/11/01
 Number of Pages: 3

 Distributed By:
 Agilent Technologies, Inc. Chemical Analysis Logistics Center of America 300 Century Blvd
 Number of Pages: 3

 U.S.A. Information/Emergency Telephone No: 1-302-633-8899 or 1-877-424-4536
 Vilanda

U.S.A. Information/Emergency Telephone No: 1-302-633-8899 or 1-877-424-4536 European Information Telephone No.: (7243) 602-0 European Emergency Telephone Number: 0049 (0)6151/722440 When Calling From Outside the USA, Dial Your International Access Code for the USA, then 1, then 302-633-8000

## Section 2 - Composition/Information on Ingredients

A 25 gm bottle of chromatography packing material - a reaction product of amorphous silica with a nitrile functional group.

Chemical Families: Surface modified amorphous silica Chemical Synonyms: SPE is also known as solid phase extraction. Silica is also known as amphorous silica.

#### Section 3 - Hazards Identification

May cause eye irritation. Do not breathe dust.

### Section 4 - First-Aid Measures

Inhalation: Symptoms of overexposure may include cough and discomfort. If large amounts are inhaled, move affected person to fresh air. If breathing is difficult give oxygen. If breathing has stopped begin resuscitation measures. Contact physician. Skin Contact: Wash with soap and water. Eye Contact: May be a mild eye irritant. Contamination of the eyes should be treated by immediate and prolonged irrigation with copious amounts of water by separating the eyelids with fingers. If redness or discomfort persist, contact a physician. Ingestion: This compound is not likely to be hazardous by ingestion. However, if swallowed, wash out mouth with water provided affected person is conscious. Consult a physician.

# Section 5 - Fire-Fighting Measures

**Extinguishing Media:** Appropriate to surroundings. **Special Fire Fighting Procedures:** Wear full protective clothing and self contained positive pressure breathing apparatus certified by NIOSH when fighting chemically related fires. **Unusual Fire and Explosion Hazards:** Small amounts of flammable vapor may be produced if heated to approximately 500°F.

#### Section 6 - Accidental Release Measures

Wearing appropriate personal protective equipment, shovel or sweep up using a dust suppresser. Vacuum the remainder of the smaller quantities using a HEPA-type vacuum. Avoid inhaling dust. Place waste in a plastic bag or other suitable container and dispose of as residual waste. Unused material is not defined as hazardous waste by RCRA (40 CFR Part 261) and may be landfilled according to federal, state and local regulations.

#### Section 7 - Handling and Storage

Do not breathe dust and avoid contact with skin and eyes. Wash thoroughly after handling. Maintain good housekeeping practices. Avoid creating dust. Keep containers closed. Do not store with incompatible materials. Store in a cool, dry place.

#### Section 8 - Exposure Controls/Personal Protection

**Ventilation**: Adequate ventilation is required to protect personnel from exposure to chemical vapors or dusts exceeding PEL and to minimize fire hazards. See Section 15 for regulatory standards of exposure. **Respiratory**: Use NIOSH approved respirator equipment. See Section 15.

**Eyes**: Safety glasses are considered minimum protection. Chemical safety goggles or face shield may be necessary depending on quantity of material and conditions of use. Emergency eye wash fountains should be

<u>DISCLAIMER</u>: This Safety Data Sheet is offered without charge to the clients of Agilent Technologies. Data is the most current available to Agilent Technologies at the time of preparation and is issued as a matter of information only, no warranty as to its accuracy or completeness is expressed or implied.



Agilent Part Number: 189-0602

available in the vicinity of any possible exposure.

**Skin**: Chemical-resistant protective gloves and clothing are recommended. The choice of protective gloves or clothing must be based on chemical resistance and other user requirements. Generally BUNA-N offers acceptable chemical resistance. Individuals who are acutely and specifically sensitive to this chemical may require additional protective clothing.

### Section 9 - Physical and Chemical Properties

 Flash Point (Method Used):
 NA
 Explosion Potential: LEL ( NA )/UEL ( NA )

 Specific Gravity (H20 = 1):
 ND

 Melting Point (Degree C):
 Decomposes above approximately 250°C (500°F)

 Evaporation Rate (n-butyl acetate =1 )
 NA

 Vapor Pressure (mm Hg at 25°C):
 ND

 Odor Threshold:
 ND

 Solubility in Water:
 Insoluble (X) /Soluble ( )

 Appearance and Odor:
 White/off-white powder, faint odor

### Section 10 - Stability and Reactivity

Stability: Stable ( x ) / Unstable ( )
Conditions to Avoid: NA
Incompatibility (Materials to Avoid): Reacts with hydrofluoric acid (HF)
Hazardous Decomposition or Byproducts: NA
Hazardous Polymerization: May Occur ( ) / Will Not Occur ( x)

### Section 11 - Toxicological Information

Route(s) of Entry: Inhalation? Yes Skin? No Ingestion? Yes May be harmful if inhaled or swallowed. Health Hazard Acute/Chronic: This product does not contain crystalline silica (CA) which is considered hazardous by inhalation.

Carcinogenicity: NTP? No IARC Monographs? No OSHA Regulated? No OTHER? No Medical Conditions Generally Aggravated by Exposure: Preclude from exposure to dust those persons with preexisting upper respiratory and lung disease such as, but not limited to, bronchitis, emphysema and asthma.

#### Section 12 - Ecological Information

Persistence/Degradability: Based on chemical experience, will degrade over very long periods of time. Biodegradability: Will not biodegrade Bioaccumulation: NA

#### Section 13 - Disposal Considerations

Unused product is not hazardous as defined by RCRA (40 CFR Part 261). Unused material may be landfilled as a residual waste according to federal, state and local regulations.

Section 14 - Transport Information

DOT Regulations:		IATA-DGR Regulations:	
Shipping Name:	Non-regulated Material	Shipping Name:	Non-regulated Material
RID/ADR: NA	ADNR: NA		

#### Section 15 - Regulatory Information

Exposure Limits: There are no established exposure limits for this product-however if dust is generated by<br/>grinding or other means the following standard would apply:Particulate Matter Not Otherwise Classified:<br/>15 mg/m3 (Total dust)(PNOC)OSHA PEL:5 mg/m3 (Respirable fraction)15 mg/m3 (Total dust)

ACGIH TWA: 3 mg/m3 (Respirable particulate) 10 mg/m3 (Inhalable particulate)

SARA Reporting: Section 302: None Section 304: None Section 313: None OSHA Labeling Requirements: None TSCA Inventory List: Reaction product not on list

# Section 16 - Other Information

Unless otherwise noted, the above information pertains only for the base material and similar types of components in the sample. When no toxicity data is provided, it is prudent to handle this chemical as hazardous. Furthermore, since individual chemical hypersensitivity cannot be predicted, every chemical should be handled with due respect.



### EUROPEAN INFORMATION (Silica)

CAUTION: SUBSTANCE NOT YET FULLY TESTED. HARMFUL R 20: Harmful by inhalation. R 36/37: Irritating to eyes and repiratory system. S 26: In case of contact with eyes, rinse immediately with plenty of water and seek medical advice. S 36: Wear suitable protective clothing.

S 22: Do not breathe dust.

#### KEY TO ABBREVIATIONS

ACGIH - American Conference of Governmental Industrial Hygienists` ADNR - Regulations concerning the carriage of dangerous goods on the Rhine CAS - Chemical Abstract Service DOT - US. Department of Transportation 49 Code of Federal Regulations IARC - International Agency for Research on Cancer IATA-DGR - International Air Transport Association- Dangerous Goods Regulation LEL - Lower Explosion Limit NA - Not Applicable ND - No Data NIOSH - National Institute for Occupational Safety and Health NTP - National Toxicology Program OSHA - Occupational Safety and Health Administration PEL - Permissible Exposure Limit RID/ADR - Regulations Concerning the International Carriage of Dangerous Goods by Rail/European Agreement Concerning the International Carriage of Dangerous Goods by Road TLV - Threshold Limit Value TWA - Time Weighted Average UEL - Upper Explosion Limit [ ] - Indicates CAS Number