

Varian Standard Disintegration Apparatus



The Varian Standard Disintegration Apparatus provides versatility and reliability for disintegration testing of dosage formulations.

Variable	Specification
Condition	Operating but not necessarily meeting performance specifications
Altitude	0 – 2000 m (0 – 6562 ft.)
Temperature	5 to 40 °C
Humidity (non-condensing)	Not more than 80% RH
Voltage requirements	115 V / 60 Hz
	230 V / 50 Hz
Current requirements	115 V–0.75 Amp
	230 V–0.50 Amp
Fuse requirements	115 V–0.75 Amp, 5 mm x 20 mm FAST
	230 V–0.50 Amp, 5 mm x 20 mm FAST
Dip speed	30 ± 1 DPM
Stroke length	5.5 ± 0.1 cm
Beaker volume	1000 mL
Dimensions	Width: 17.78 cm (7 in.)
	Depth: 21.92 cm (8.63 in.)
	Height (when dipping): 60.96 cm (24 in.)
Machine weight	8.6 kg (19 lb)

NOTICE: Varian, Inc. was acquired by Agilent Technologies in May 2010. This document is provided as a courtesy but is no longer kept current and thus will contain historical references to Varian. For more information, go to www.agilent.com/chem.



Agilent Technologies

Varian, Inc.

www.varianinc.com

North America: 800.926.3000, 925.939.2400

Europe The Netherlands: 31.118.67.1000

Asia Pacific Australia: 613.9560.7133

Latin America Brazil: 55.11.3238.0400

Other sales offices and dealers throughout the world—
check our Web site.