



## MAT'L:

1. CABLE: #28 25C+1+AL/MY (BEIGE PVC JACKET) O.D: 7.5MM
2. BOTH CONNECTORS WITH NORMAL TYPE
3. THUMBSCREW: #4-40UNC TYPE
4. OUTER MOLDED WITH BEIGE PVC

## NOTE:

1. TOTAL LENGTH: 3M ± 5CM
2. COLOR: BEIGE
3. MOLDED TYPE

CONFIGURATION:  
DB25F

## DB25F

|        |        |
|--------|--------|
| 1      | 1      |
| 2      | 2      |
| 3      | 3      |
| 4      | 4      |
| 5      | 5      |
| 6      | 6      |
| 7      | 7      |
| 8      | 8      |
| 9      | 9      |
| 10     | 10     |
| 11     | 11     |
| 12     | 12     |
| 13     | 13     |
| 14     | 14     |
| 15     | 15     |
| 16     | 16     |
| 17     | 17     |
| 18     | 18     |
| 19     | 19     |
| 20     | 20     |
| 21     | 21     |
| 22     | 22     |
| 23     | 23     |
| 24     | 24     |
| 25     | 25     |
| SHIELD | SHIELD |

PN# AK170-3

|       |       |       |       |              |           |                                               |           |                         |  |                     |
|-------|-------|-------|-------|--------------|-----------|-----------------------------------------------|-----------|-------------------------|--|---------------------|
| DRAWN | CHECK | APPRO | DATE  | 23 OCT. 1995 | PART NO   | AK170-3                                       | TITLE     | DB25 FEMALE-DB25 FEMALE |  |                     |
| S.M.  |       |       | UNIT  |              | DRAWN NO  | 205M2-02                                      | (MD TYPE) |                         |  |                     |
| 10/23 |       |       | MAT'L |              | TOLERANCE | UNLESS OTHERWISE ALL TOLERANCES ERROR ARE 10% | REMARK    |                         |  | ASSMANN ELECTRONICS |
|       |       |       | SCALE |              |           |                                               |           |                         |  |                     |