



Industrial Interface IC Solutions

RS-485 PROFIBUS, CAN, Ethernet

Overview:

Texas Instruments provides Interface IC solutions ranging from CAN, LVDS, RS-485, RS-232 industry standards to 1394 (Firewire), USB, PCI Cardbus and more. Our Interface Selection Tool is available to help you understand what Interface IC best suits your connectivity needs.

For more information including selection guides, datasheets application notes and samples visit:

www.ti.com/interface

RS-485 solutions

SN65HVD178x – $\pm 70V$ fault protected RS485, 5V, half & full duplex transceiver

Features	Benefits
<ul style="list-style-type: none">• $\pm 70V$ fault protection• Wide common mode -20V to +25V	<ul style="list-style-type: none">• Equipment is protected if it shorts to power rails• Allows operation over wide differences in GND

SN65HVD30-35 – 3.3-V RS-485 single full-duplex transceiver

Features	Benefits
<ul style="list-style-type: none">• 1/8 unit-load option available• Low-current standby mode < 1 μA	<ul style="list-style-type: none">• Allows up to 256 nodes• Low power consumption

ISO1176 – 4kV Isolated – PROFIBUS RS485 transceiver

Features	Benefits
<ul style="list-style-type: none">• Meets-EN-50170 (Profibus), RS-422, RS-485• Failsafe receiver for bus open, short, idle• 4KV max isolation, 560V working	<ul style="list-style-type: none">• Fully compliant to Profibus and RS-485• High reliability in harsh environments• Life span > 25 years @ 125°C

ISO1177 – Isolated RS-485 transceiver with transformer driver – preview

Features	Benefits
<ul style="list-style-type: none">• Meets or exceeds TIA/EIA RS-485• 1Mbps / 20Mbps / 40Mbps• Silicon integrated SiO₂ insulation - 4kVmax / 2.5kVrms isolation	<ul style="list-style-type: none">• Fully compliant to RS-485 standard• Optimized for long cables or high speed• Life span > 25 years @ 125°C

CAN solutions

ISO1050 – 4kV isolated – 5V CAN transceiver

Features	Benefits
<ul style="list-style-type: none">• Industry's first isolated CAN transceiver• Isolated CAN with ultra low loop time• Silicon integrated SiO₂ insulation - 4kVmax / 2.5kVrms isolation	<ul style="list-style-type: none">• Reduce components and board space - 30%• High speed isolation allows longer buses – 34%• Life span > 25 years @ 105°C

SN65HVD23x – 3.3-V CAN transceiver

Features	Benefits
<ul style="list-style-type: none">• Operates with a 3.3V supply• High input impedance allows for 120 nodes on a bus	<ul style="list-style-type: none">• Eliminates 5V supply requirement• Supports large industrial networks

Ethernet solutions

TLK100 – Industrial Ethernet 10/100 PHY

Features	Benefits
<ul style="list-style-type: none">• Predictable and precise for time-critical apps• Flexible supply options: 3.3V or 3.3V & 1.8V & 1.1V• Cable diagnostics (breaks/damage/length)	<ul style="list-style-type: none">• Supports time stamping/slotting protocols• 3.3V only for simple power solution or separate power for low power consumption• Finds cable faults / length within $\pm 1m$• Operates offline or with live traffic

Voltage to current converter solutions

XTR111 – Precision voltage-to-current converter/transmitter

Features	Benefits
<ul style="list-style-type: none">• Input/Output: 0mA-20mA, 4mA-20mA, 5mA-25mA	<ul style="list-style-type: none">• Highly flexible and easy to design with

Important Notice: The products and services of Texas Instruments Incorporated and its subsidiaries described herein are sold subject to TI's standard terms and conditions of sale. Customers are advised to obtain the most current and complete information about TI products and services before placing orders. TI assumes no liability for applications assistance, customer's applications or product designs, software performance, or infringement of patents. The publication of information regarding any other company's products or services does not constitute TI's approval, warranty or endorsement thereof.

The platform bar is a trademark of Texas Instruments. All other trademarks are the property of their respective owners