

AN3355 Application note

Designing an application board compatible with either standard M24LRxx-R or energy-harvesting M24LRxxE-R devices

Introduction

The goal of this application note is to describe how to design application boards accepting either standard M24LRxx-R or energy-harvesting M24LRxxE-R devices.

Contents

1	M24LRxx-R and M24LRxxE-R pin-out comparison
2	Designing a board compatible with both devices
3	Summary9
4	Revision history



List of tables

Table 1.	Compatibility overview (Pin1)	7
Table 2.	Compatibility overview (Pin7)	8
Table 3.	M24LRxx-R Device Select byte	9
Table 4.	M24LRxxE-R Device Select byte	9
Table 5.	Document revision history	0



List of figures

Figure 1.	Two families, two pin-outs	5
Figure 2.	Typical schematic of an application powered from M24LRxxE-R	6



AN3355

1 M24LRxx-R and M24LRxxE-R pin-out comparison

The standard dual-interface M24LRxx-R and the energy-harvesting M24LRxxE-R devices have small differences in pin-out, which apply to only two pins:

- M24LRxx-R
 - Pin1: E0 input (used to define the hardware address of the I²C-bus slave)
 - Pin7: E1 input (used to define the hardware address of the I²C-bus slave)
- M24LRxxE-R
 - Pin1: Vout (output used to deliver supply voltage to the application)
 - Pin7: WIP/Busy output signal (during a Write cycle)





When designing a new application, it can be useful to design an application board which can embed either the standard M24LRxx-R or the energy-harvesting M24LRxxE-R devices.



2 Designing a board compatible with both devices

The purpose of this application note is to design an application board that accepts either the standard M24LRxx-R (dual-interface) or the M24LRxxE-R (energy-harvesting) devices.

Let's see how pin1 and pin7 are used in a typical application based on M24LRxxE-R.

- Pin1: M24LRxxE-R Vout pin, providing a power supply to the application.
 This pin is actually connected to the input of the application power supply management block.
- Pin7: M24LRxxE-R WIP/Busy output.
 This pin is connected to one input of the application controller.





If we substitute the M24LRxxE-R (offering the Energy harvesting function) with an M24LRxx-R (without energy-harvesting output), we have to check that the two pins 1 and 7 do not induce malfunction or stress in the application.

Conditions applying to pin1:

The M24LRxx-R pin1 is the E0 input. Its logical value is internally read as:

- either E0=1 when directly connected to V_{cc},
- or E0=0 when directly connected to V_{ss},
- or E0=0 when left unconnected (HiZ).



Comparing this with the M24LRxxE-R requirements, we can see that:

- If pin1 is directly connected to V_{cc}:
 - OK for the M24LRxx-R,
 - not compatible with the M24LRxxE-R: this would short-circuit Vout to V_{cc}.
 - If pin1 is directly connected to V_{ss}:
 - OK for the M24LRxx-R,
 - not compatible with the M24LRxxE-R: this would short-circuit Vout to V_{ss}.
- If pin1 is left unconnected (HiZ):
 - OK for the M24LRxx-R.
 - OK for the M24LRxxE-R.

Table 1.Compatibility overview (Pin1)

Pin1	M24LRxxx-R	M24LRxxE-R	Result		
Connected to V _{cc}	E0=1	Conflict on Vout	Not possible		
Connected to V _{ss}	E0=0	Conflict on Vout	Not possible		
Left unconnected (or connected to a E0=0 high impedance)		ОК	ОК		

We can see that the correct way to design an application accepting either M24LRxx-R or M24LRxxE-R is to define E0=0 for the M24LRxx-R.

Conditions applying to pin7:

The M24LRxx-R pin7 is the E1 input. Its logical value is internally read as:

- either E1=1 when directly connected to V_{CC},
- or E1=0 when directly connected to V_{ss},
- or E1=0 when left unconnected (HiZ).

Comparing this with the M24LRxxE-R requirements, we can see that, consequently:

- If pin7 is directly connected to V_{cc}:
 - OK for the M24LRxx-R,
 - not compatible with the M24LRxxE-R: this would create a short-circuit when WIP/Busy outputs a 0.
- If pin7 is directly connected to V_{ss}:
 - OK for the M24LRxx-R,
 - not compatible with the M24LRxxE-R: this would force WIP/Busy signal to V_{ss} and therefore inhibit the WIP/Busy information.
- If pin7 is left unconnected (HiZ):
 - OK for the M24LRxx-R,
 - OK for the M24LRxxE-R.



		<u>, ,</u>		
Pin7	M24LRxxx-R	M24LRxxE-R	Result	
Connected to V _{cc}	E1=1	Conflict on WIP/Busy	Not possible	
Connected to V _{ss} E1=0		WIP/Busy = 0 (always)	WIP/Busy info inhibited	
Left unconnected (or connected to a high impedance)	E1=0	ОК	ОК	

 Table 2.
 Compatibility overview (Pin7)

One can see that the correct way to design an application accepting either M24LRxx-R or M24xxxE-R is to define E1=0.



3 Summary

When designing an application board that will accept either M24LRxx-R or M24LRxxE-R, the following rules should be kept in mind:

M24LRxx-R

The Device Select byte (first byte transmitted by the I²C-bus master selecting the device to be accessed) is defined as shown in *Table 3*.

Table 3. M24LRxx-R Device Select byte

	De	vice type	identifie	r ⁽¹⁾	Chip Enable address ⁽²⁾			R₩
	b7	b6	b5	b4	b3	b2	b1	b0
Device select code	1	0	1	0	E2 ⁽³⁾	E1	E0	RW

1. The most significant bit, b7, is sent first.

- 2. E0 and E1 are compared against the respective external pins on the memory device.
- 3. E2 selects either the memory of the system sector.

The inputs E0,E1 have to be defined as 0,0 (which is the case when the E0,E1 pins are left unconnected). The Device Select byte is therefore:

- either 1.0.1.0. 0.0.0.RW (where RW is the Read/Write bit) when addressing data in the memory array,
- or 1.0.1.0. 1.0.0.RW (where RW is the Read/Write bit) when addressing the system parameter sector.

M24LRxxE-R

In this case of PCB implementation, the E0 and E1 inputs are connected to the power supply management block and the WIP/Busy output is connected to a high impedance input, as shown in *Figure 2*.

The Device Select byte (first byte transmitted by the l²C-bus master) defines the device to be selected. The Device Select byte is defined as shown in the following table.

Table 4.M24LRxxE-R Device Select byte

	De	vice type	identifie	r ⁽¹⁾	Chip Enable address			RW
	b7	b6	b5	b4	b3	b2	b1	b0
Device select code	1	0	1	0	E2 ⁽²⁾	1	1	RW

1. The most significant bit, b7, is sent first.

2. E2 selects either the memory of the system sector.

The Device Select byte is therefore:

- either 1.0.1.0. 0.1.1.RW (where RW is the Read/Write bit) when addressing data in the memory array,
- or 1.0.1.0. 1.1.1.RW (where RW is the Read/Write bit) when addressing the system parameter sector.



Doc ID 018544 Rev 2

4 Revision history

Table 5.Document revision history

Date	Revision	Changes			
29-Mar-2011	1	Initial release.			
24-May-2011	2	Updated Section 3: Summary.			



Please Read Carefully:

Information in this document is provided solely in connection with ST products. STMicroelectronics NV and its subsidiaries ("ST") reserve the right to make changes, corrections, modifications or improvements, to this document, and the products and services described herein at any time, without notice.

All ST products are sold pursuant to ST's terms and conditions of sale.

Purchasers are solely responsible for the choice, selection and use of the ST products and services described herein, and ST assumes no liability whatsoever relating to the choice, selection or use of the ST products and services described herein.

No license, express or implied, by estoppel or otherwise, to any intellectual property rights is granted under this document. If any part of this document refers to any third party products or services it shall not be deemed a license grant by ST for the use of such third party products or services, or any intellectual property contained therein or considered as a warranty covering the use in any manner whatsoever of such third party products or services or any intellectual property contained therein.

UNLESS OTHERWISE SET FORTH IN ST'S TERMS AND CONDITIONS OF SALE ST DISCLAIMS ANY EXPRESS OR IMPLIED WARRANTY WITH RESPECT TO THE USE AND/OR SALE OF ST PRODUCTS INCLUDING WITHOUT LIMITATION IMPLIED WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE (AND THEIR EQUIVALENTS UNDER THE LAWS OF ANY JURISDICTION), OR INFRINGEMENT OF ANY PATENT, COPYRIGHT OR OTHER INTELLECTUAL PROPERTY RIGHT.

UNLESS EXPRESSLY APPROVED IN WRITING BY AN AUTHORIZED ST REPRESENTATIVE, ST PRODUCTS ARE NOT RECOMMENDED, AUTHORIZED OR WARRANTED FOR USE IN MILITARY, AIR CRAFT, SPACE, LIFE SAVING, OR LIFE SUSTAINING APPLICATIONS, NOR IN PRODUCTS OR SYSTEMS WHERE FAILURE OR MALFUNCTION MAY RESULT IN PERSONAL INJURY, DEATH, OR SEVERE PROPERTY OR ENVIRONMENTAL DAMAGE. ST PRODUCTS WHICH ARE NOT SPECIFIED AS "AUTOMOTIVE GRADE" MAY ONLY BE USED IN AUTOMOTIVE APPLICATIONS AT USER'S OWN RISK.

Resale of ST products with provisions different from the statements and/or technical features set forth in this document shall immediately void any warranty granted by ST for the ST product or service described herein and shall not create or extend in any manner whatsoever, any liability of ST.

ST and the ST logo are trademarks or registered trademarks of ST in various countries.

Information in this document supersedes and replaces all information previously supplied.

The ST logo is a registered trademark of STMicroelectronics. All other names are the property of their respective owners.

© 2011 STMicroelectronics - All rights reserved

STMicroelectronics group of companies

Australia - Belgium - Brazil - Canada - China - Czech Republic - Finland - France - Germany - Hong Kong - India - Israel - Italy - Japan -Malaysia - Malta - Morocco - Philippines - Singapore - Spain - Sweden - Switzerland - United Kingdom - United States of America

www.st.com



Doc ID 018544 Rev 2