



STZ150NF55T

N-CHANNEL TEMPERATURE SENSING 55V - P²PAK
SAFeFET™ MOSFET


DATA BRIEF

General features

Type	V _{DSSS}	R _{DS(on)}	I _D
STZ150NF55T	55 V	<9 mΩ	40 A(1)


- INTEGRATED ESD PROTECTION
- INTEGRATED TEMPERATURE SENSING
- STANDARD VGS(th) LEVEL
- 175°C JUNCTION TEMPERATURE

Package



P²PAK

Internal schematic diagram



Applications

- HIGH CURRENT SWITCHING

Order codes

Sales Type	Marking	Package	Packaging
STZ150NF55T	Z150NF55T	P ² PAK	TAPE & REEL

1 Absolute maximum ratings

Table 1. Absolute maximum ratings

Symbol	Parameter	Value	Unit
V_{DS}	Drain-Source Voltage ($V_{GS} = 0$)	55	V
V_{GS}	Gate-Source Voltage	± 18	V
I_D Note 1	Drain Current (continuous) at $T_C = 25^\circ\text{C}$	40	A
I_D Note 1	Drain Current (continuous) at $T_C = 100^\circ\text{C}$	40	A
I_{DM}	Drain Current (pulsed)	160	A
P_{TOT}	Total Dissipation at $T_C = 25^\circ\text{C}$	250	W
	Derating Factor	1.67	W/ $^\circ\text{C}$
Vesd(G-S)	G-S ESD (HBM C=100pF, R=1.5k Ω)	>4	kV
E_{AS}	Single Pulse Avalanche Energy	TBD	mJ
T_j T_{stg}	Operating Junction Temperature Storage Temperature	-55 to 175	$^\circ\text{C}$

2 Electrical characteristics

(T_{CASE} = 25 °C unless otherwise specified)

Table 2. On/Off

Symbol	Parameter	Test Conditions	Min.	Typ.	Max.	Unit
V _{(BR)DSS}	Drain-Source Breakdown Voltage	I _D = 250μA, V _{GS} = 0	55			V
I _{DSS}	Zero Gate Voltage Drain Current (V _{GS} = 0)	V _{DS} = Max Rating,			10	μA
I _{GSS}	Gate Body Leakage Current (V _{DS} = 0)	V _{GS} = ±15V, V _{DS} = 0			10	μA
V _{GS(th)}	Gate Threshold Voltage	V _{DS} = V _{GS} , I _D = 250 μA	2		4	V
R _{DS(on)}	Static Drain-Source On Resistance	V _{GS} = 10 V, I _D = 20 A			9	mΩ
V _F	Temperature Sense diode forward voltage	I _F = 250μA		3.5		V


(1) Limited by wire bonding

3 Package mechanical data

In order to meet environmental requirements, ST offers these devices in ECOPACK® packages. These packages have a Lead-free second level interconnect . The category of second level interconnect is marked on the package and on the inner box label, in compliance with JEDEC Standard JESD97. The maximum ratings related to soldering conditions are also marked on the inner box label. ECOPACK is an ST trademark. ECOPACK specifications are available at: www.st.com

PENTAWATT SMD (P2PAK) MECHANICAL DATA

DIM.	mm			inch		
	MIN.	TYP.	MAX.	MIN.	TYP.	MAX.
A	4.30		4.80	0.169		0.188
A2	0.03		0.23	0.001		0.009
C	1.17		1.37	0.046		0.053
D	2.40		2.80	0.094		0.110
D1	8.95		9.35	0.352		0.368
E	0.35		0.55	0.013		0.021
F	0.80		1.05	0.031		0.041
G	3.20		3.60	0.125		0.141
G1	6.60		7.00	0.259		0.275
H2			10.40			0.409
L	13.59		14.39	0.535		0.566
L2	1.27		1.40	0.05		0.055
L3	1.30		1.70	0.051		0.066
R		0.30				
V2	0 d		8 d			



4 Revision History

Date	Revision	Changes
22-Jul-2005	1	Initial release.

Information furnished is believed to be accurate and reliable. However, STMicroelectronics assumes no responsibility for the consequences of use of such information nor for any infringement of patents or other rights of third parties which may result from its use. No license is granted by implication or otherwise under any patent or patent rights of STMicroelectronics. Specifications mentioned in this publication are subject to change without notice. This publication supersedes and replaces all information previously supplied. STMicroelectronics products are not authorized for use as critical components in life support devices or systems without express written approval of STMicroelectronics.

The ST logo is a registered trademark of STMicroelectronics.
All other names are the property of their respective owners

© 2005 STMicroelectronics - All rights reserved

STMicroelectronics group of companies

Australia - Belgium - Brazil - Canada - China - Czech Republic - Finland - France - Germany - Hong Kong - India - Israel - Italy - Japan -
Malaysia - Malta - Morocco - Singapore - Spain - Sweden - Switzerland - United Kingdom - United States of America

www.st.com

