


49956A Molded Cable Assemblies - D-Subminiature Assembly



For more information please call

1-800-Belden1

See Put-ups and Colors

Description:

37-position shielded D-Sub, for RS-449 applications where assembly is exposed to high noise environment, S-R PVC insulation, foil plus braid shield (super shield), PVC jacket.

PHYSICAL CHARACTERISTICS:

CONDUCTOR:

| | |
|----------------------------|--------------------|
| Number of Conductors | 36 |
| Total Number of Conductors | 36 |
| Number of Pins | 37 |
| AWG | 24 |
| Stranding | 7x32 |
| Conductor Diameter | .024 in. |
| Conductor Material | TC - Tinned Copper |

INSULATION:

| | |
|--------------------------------|---|
| Insulation Material | S-R PVC - Semi-Rigid Polyvinyl Chloride |
| Nom. Insulation Wall Thickness | 0.01 in. |

OUTER SHIELD:

| | |
|-------------------------|------------|
| Outer Shield Trade Name | Beldfoil® |
| Outer Shield Type | Tape/Braid |

Outer Shield Material :

| Layer Number | Trade Name | Type | Material | % Coverage (%) |
|--------------|------------|-------|------------------------------|----------------|
| 1 | Beldfoil® | Tape | Aluminum Foil-Polyester Tape | 100 |
| 2 | | Braid | TC - Tinned Copper | 65 |

| | |
|-------------------------|-------|
| Outer Shield % Coverage | 100 % |
|-------------------------|-------|

OUTER JACKET:

| | |
|-------------------------------------|--------------------------|
| Outer Jacket Material | PVC - Polyvinyl Chloride |
| Outer Jacket Nominal Wall Thickness | 0.045 in. |

OVERALL NOMINAL DIAMETER:

| | |
|--------------------------|----------|
| Overall Nominal Diameter | .480 in. |
|--------------------------|----------|

ASSEMBLY DIMENSIONAL CHARACTERISTICS:

| | |
|-----------------------------|--------|
| Assembly Dimensional Length | 10 ft. |
|-----------------------------|--------|

49956A Molded Cable Assemblies - D-Subminiature Assembly

CONNECTOR CHARACTERISTICS:

| FIRST END : | |
|--|--|
| Connector Characteristics - First End Connector Type | D-Sub |
| Connector Characteristics - First End # of Connector Contacts/positions | 37 |
| Connector Characteristics - First End Connector Gender | Male |
| Connector Characteristics - First End Connector Shielding Type | Metal Backshells |
| Connector Characteristics - First End Overmold Type | 37 Position D-Sub |
| Connector Characteristics - First End Overmold Compound Material | PVC |
| Connector Characteristics - First End Overmold Color | Chrome |
| Connector Characteristics - First End Retention Hardware | Thumbscrew |
| SECOND END : | |
| Connector Characteristics - Second End Connector Type | D-Sub |
| Connector Characteristics - Second End # of Connector Contacts/positions | 37 |
| Connector Characteristics - Second End Connector Gender | Female |
| Connector Characteristics - Second End Connector Shielding Type | Metal Backshells |
| Connector Characteristics - Second End Overmold Type | 37 Position D-Sub |
| Connector Characteristics - Second End Overmold Compound Material | PVC |
| Connector Characteristics - Second End Overmold Color | Chrome |
| Connector Characteristics - Second End Retention Hardware | Thumbscrew |
| Wiring | Point to Point. Pin #1 on End 1 to Pin #1 on End 2, Pin #2 to Pin #2, etc. Cable Shield Connected to Connector Shell and Pin #1. |

MECHANICAL CHARACTERISTICS:

| | |
|-----------------------|--------------------------|
| UL Temperature Rating | 80°C (UL AWM Style 2464) |
|-----------------------|--------------------------|

APPLICABLE SPECIFICATIONS AND AGENCY COMPLIANCE:

| | |
|------------------------|---|
| NEC/(UL) Specification | CM (cable only) |
| AWM Specification | UL Style 2464 (300 V 80°C) (cable only) |

APPLICABLE STANDARDS:

| | |
|---------------------------------------|------------|
| EU RoHS Compliant (Y/N) | Yes |
| EU RoHS Compliance Date (mm/dd/yyyy): | 04/01/2005 |

PLENUM/NON-PLENUM:

49956A Molded Cable Assemblies - D-Subminiature Assembly

Plenum (Y/N) N

ELECTRICAL CHARACTERISTICS:

Max. Operating Voltage - UL 300 V RMS (UL AWM Style 2464)

NOTES:

Notes Molded handles are 100% shielded to guard against EMI/RFI and assist in FCC compliance. All connectors tin-plated and male connectors have detents to allow for a positive shield to ground connection.

Notes (cont'd) Wiring is point-to-point with the shield to connector shell and pin #1. Jack screw retention on both connectors.

PUT-UPS AND COLORS:

| Item | Description | Put-Up (ft.) | Ship Weight (lbs.) | Jacket Color | Notes |
|--------------|--------------------------|--------------|--------------------|--------------|-------|
| 49956A 060S2 | 37 POS SHD D-SUB 8348 | S2 | 3.74 | CHROME | |

Revision Number: 1 Revision Date: 05-13-2005

© Copyright 2006 Belden, Inc
All Rights Reserved.

Although Belden ("Belden") makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described herein are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "AS IS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with the following environmental regulations: California Proposition 65 Consent Judgment For Wire & Cable Mfgs.(San Francisco Superior Court Nos. 312962 And 320342); EU RoHS (Directive 2002/95/EC, 27-Jan-2003);Material manufactured prior to the compliance date may still be in stock at Belden facilities and in our Distributor's inventory. EU ELV (Directive 2000/53/EC, 18-Sept-2000); EU WEEE (Directive 2002/96/EC, 27-Jan-2003); And EU BFR (Directive 2003/11/EC, 6-Feb-2003). The information provided in this Product Disclosure, and the identification of materials listed as reportable or restricted within the Product Disclosure, is correct to the best of Belden's knowledge, information and belief at the date of its publication. The information provided in the Product Disclosure is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. This Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.