

Design according to brochure: MD10.1

Ordering Data **2LC0100-5AG99-0AB0**
L1D +M0X



Client-Order-No:

Item-No: **100**

Order-No:

Consignment-No:

Quotation-No:

Project:

Coupling - Basic data

Product selection

[10]	Series:	N-EUPEX
[AG]	Type:	H
[05]	Size:	125
[AG]	Scope of supply:	Complete coupling

Connection 1 Part 1

[L1D]	Hub execution:	55 mm
[L40]	Keyway acc. to:	DIN 6885-1 (JS9)
[STD]	No. of keyways, offset:	one parallel keyway
[L10]	Bore tolerance:	ISO H7
[STD]	Balancing principle:	Balancing in accordance with half parallel key
[L48]	Axial:	with set screw

Product specific options

[B]	DBSE:	S=140MM
[STD]	Flexible element:	flexible elements NBR 80 Shore A

Corrosion protection

[STD]	Conservation:	Cleaning emulsion - Indoor storage up to 3 months
[STD]	Paint coat:	No coating

Connection 2 Part 5

[M0X]	Hub execution:	42 mm
[M40]	Keyway acc. to:	DIN 6885-1 (JS9)
[STD]	No. of keyways, offset:	one parallel keyway
[M10]	Bore tolerance:	ISO H7
[STD]	Balancing principle:	Balancing in accordance with half parallel key
[M48]	Axial:	with set screw

Balancing

[STD]	Balancing quality:	Standard balancing
-------	--------------------	--------------------

Certificates