

## SCSI (SMALL COMPUTER SYSTEM INTERFACE) CABLES

More powerful computers and faster speeds have given rise to the tremendous growth in the SCSI peripheral devices. The first SCSI standard was adopted in 1986. It supports seven devices on an 8-bit bus at speeds up to 5 Mbps. The most common connectors to be used were DB25, CEN50, and DB50.

- SCSI cables use twisted pair wires
- Cables are double shielded
- Cable is 28 AWG with mylar foil and 85% Braid (SCSI 1 cables have foil shield only)



CEN50 (M)

### SCSI 1

- SCSI 1 cable use a CEN50 connector
- Heavy duty mylar foil shield
- Molded connectors
- Supports speed up to 5 Mbps
- Can daisy-chain up to (7) devices

SCSI 1 Cable CEN50 (M)/  
CEN50 (M) (25 wire) 3'  
**Cat. No. 45-0853-0000**


SCSI 1 Cable CEN50 (M)/  
CEN50 (M) (25 wire) 6'  
**Cat. No. 45-0856-0000**

SCSI 1 Cable CEN50 (M)/  
CEN50 (M) (50 wire) 3'  
**Cat. No. 45-0854-0000**

SCSI 1 Cable CEN50 (M)/  
CEN50 (M) (50 wire) 6'  
**Cat. No. 45-0855-0000**

SCSI 1 Cable CEN50 (M)/  
CEN50 (F) 3'  
**Cat. No. 45-0873-0000**

SCSI 1 Cable CEN50 (M)/  
CEN50 (F) 6'  
**Cat. No. 45-0876-0000**



CEN50 (F)

### SCSI 2

- SCSI 2 cables use a H.P. DB50 connector
- Band width of 16 or 32 bits
- Maximum transfer rate of up to 40 Mbps
- Cables are double shielded with mylar foil and 85% braided shield
- Connectors have spring clip catches for easy installation

SCSI 2 Cable, H.P. DB50 (M)/  
H.P. DB50 (M) 1.5'  
**Cat. No. 45-1813-0000**

SCSI 2 Cable, H.P. DB50 (M)/  
H.P. DB50 (M) 3'  
**Cat. No. 45-0813-0000**

SCSI 2 Cable, H.P. DB50 (M)/  
H.P. DB50 (M) 6'  
**Cat. No. 45-0890-0000**

SCSI 2 Cable, H.P. DB50 (M)/  
H.P. DB50 (M) 10'  
**Cat. No. 45-8310-0000**

SCSI 2 to SCSI 1 Adapter

SCSI 2 to SCSI 1 Cable,  
H.P. DB50 (M)/CEN50 (M) 3'  
**Cat. No. 45-0905-0000**

SCSI 2 to SCSI 1 Cable,  
H.P. DB50 (M)/CEN50 (M) 6'  
**Cat. No. 45-0896-0000**

SCSI 2 to SCSI 1 Cable,  
H.P. DB50 (M)/CEN50 (M) 10'  
**Cat. No. 45-8210-0000**



H.P. DB50 (M)



H.P. DB68 (M)

### SCSI 3

- SCSI 3 cables have a H.P. DB68 connector
- Cables are double shielded with mylar foil and 85% braided shield
- Connectors have spring clip catches for easy installation
- Band width of 16 or 32 bits
- Maximum transfer rate of up to 40 mbps

SCSI 3 Cable, H.P. DB68 (M)/  
H.P. DB68 (M) 3'  
**Cat. No. 45-0803-0000**

SCSI 3 Cable, H.P. DB68 (M)/  
H.P. DB68 (M) 6'  
**Cat. No. 45-0806-0000**

SCSI 3 to SCSI 2 & SCSI 1  
Adapter Cables

SCSI 3 to SCSI 1 Cable,  
H.P. DB68 (M)/CEN50 (M) 3'  
**Cat. No. 45-0875-0000**

SCSI 3 to SCSI 1 Cable,  
H.P. DB68 (M)/CEN50 (M) 6'  
**Cat. No. 45-0877-0000**

SCSI 3 to SCSI 2 Cable,  
H.P. DB68 (M)/DB50 (M) 3'  
**Cat. No. 45-0906-0000**

SCSI 3 to SCSI 2 Cable,  
H.P. DB68 (M)/H.P. DB68 (M) 6'  
**Cat. No. 45-0907-0000**

### IBM® RS6000

- Adapts IBM® RS6000 SCSI port to an external SCSI device
- RS6000 cables have a H.P. CEN60 connector

RS6000 to SCSI 1 Cable,  
H.P. CEN60 (M)/CEN50 (M) 3'  
**Cat. No. 45-0833-0000**

RS6000 to SCSI 1 Cable,  
H.P. CEN60 (M)/CEN50 (M) 5'  
**Cat. No. 45-0884-0000**



H.P. CEN60 (M)