ΡΗΟΤΟΙΟ

Photo IC for optical link **S7727**



Receiver for 156 Mbps POF communications

S7726 is designed for high-speed POF (Plastic Optical Fiber) communications. Both devices are molded into miniature plastic packages with lenses, allowing easy and efficient coupling to a POF. S7727 uses a monolithic photo IC that ensures high resistance to external noise and high reliability, and provides P-ECL voltage conversion output.

Features

- Photo IC receiver for POF data link
- Monolithic structure immune from external noise
- Data rates from 4 Mbps to 156 Mbps
- P-ECL voltage conversion output (Note: Unlike normal P-ECL output, S7727 output cannot be terminated with 50 Ω.)
- Designed to be used with L9534 or L7726

■ Absolute maximum ratings (Ta=25 °C)

Applications

- Plastic optical fiber communications (FA, office machine, home automation, LAN)
- Data transmission in locations subject to high electromagnetic noise

	10-20 0)		
Parameter	Symbol	Value	Unit
Supply voltage	Vcc	-0.5 to +7.0	V
Output voltage	Vo	-0.5 to Vcc + 0.5	V
Output current	lo	8	mA
Power dissipation	Pmax	250 * ¹	mW
Operating temperature	Topr	-20 to +70	°C
Storage temperature	Tstg	-40 to +85	°C
Soldering	-	230 °C, 5 s, at least 1.5 mm away from package surface	-

*1: Derate power dissipation at a rate of 1.7 mW/°C above Ta=25 °C

■ Electrical and optical characteristics (Ta=25 °C, Vcc=5.0 V)

Parameter	Symbol	Condition	Min.	Тур.	Max.	Unit
Data rate	fD	Bi-phase signal NRZ conversion	4	-	156	Mbps
Current consumption	lcc	*2, *3, *6	-	-	40	mA
High level output voltage	Voh	loh= -1 mA *2, *3, *6	3.9	-	4.3	V
Low level output voltage	Vol	lol= -0.5 µA * ^{2, *3, *6}	2.9	-	3.4	V
Minimum overload	Pimax	*2, *3, *4, *5, *6	-2	-	-	dBm
Minimum receiver input power	Pimin	*2, *3, *4, *5, *6	-	-	-22	dBm
Rise time	tr	10 to 90 % * ^{2, *3, *6}	-	-	3	ns
Fall time	tf		-	-	3	ns
Pulse width distortion	ΔT	*2, *3, *4, *6	-3	-	3	ns
Jitter	∆tj	*2, *3, *4, *6	-	-	3	ns

*2: Measured with 156 Mbps input signal (Bi-phase signal)

*3: A 3 pF capacitor is connected to GND as a capacitive load (including parasitic capacitance such as probes, connectors and evaluation PCB patterns)

*4: An optical input waveform is generated with a Hamamatsu standard transmitter.

*5: A detectable signal level is an average value, measured using a plastic fiber (GH4001 made by Mitsubishi Rayon).

*6: A 3 k Ω resistor is externally connected between Q and GND and also between QB and GND.

Note)

- A bypass capacitor (0.1 μF) connected at a position within 2 mm from the lead, and a 4.7 μF capacitor is also connected to the power supply line nearby.
- The optical axis of the package lens is exactly aligned with the center axis of the optical plug, and the gap between the lens surface and the optical reference plane of the plug is 0.1 mm.
- If modulated light at 4 Mbps or less (including DC light and no light input) is input to S7727, the high and low levels cannot be discerned.



HAMAMATSU

Photo IC for optical link S7727

■ Dimensional outline (unit: mm)





(SPECIFIED AT THE LEAD ROOT)



① QB Q GND
Q
Q
Vcc

Tolerance unless otherwise noted: ±0.1, ±2° Shaded area indicates burr. Values in parentheses indicate reference value.

KPICA0029EC



MAMATSU Information furnished by HAMAMATSU is believed to be reliable. However, no responsibility is assumed for possible inaccuracies or omissions. Specifications are subject to change without notice. No patent rights are granted to any of the circuits described herein. ©2006 Hamamatsu Photonics K.K.

HAMAMATSU PHOTONICS K.K., Solid State Division

HAMAMAI SU PHOTONICS K.K., Solid State Division 1126-1 Ichino-cho, Higashi-ku, Hamamatsu City, 435-8558 Japan, Telephone: (81) 53-434-3311, Fax: (81) 53-434-5184, www.hamamatsu.com U.S.A: Hamamatsu Corporation: 360 Foothill Road, P.O.Box 6910, Bridgewater, N.J. 08807-0910, U.S.A., Telephone: (1) 908-231-0960, Fax: (1) 908-231-1218 Germany: Hamamatsu Photonics Deutschland GmbH: Arzbergerstr. 10, D-82211 Herrsching am Ammersee, Germany, Telephone: (49) 08152-3750, Fax: (49) 08152-2658 France: Hamamatsu Photonics France S.A.R.L.: 19, Rue du Saule Trapu, Parc du Moulin de Massy, 91882 Massy Cedex, France, Telephone: 33-(1) 69 53 71 10, Fax: 33-(1) 69 53 71 10 United Kingdom: Hamamatsu Photonics UK Limited: 2 Howard Court, 10 Tewin Road, Welwyn Garden City, Hertfordshire AL7 1BW, United Kingdom, Telephone: (44) 1707-294888, Fax: (44) 1707-325777 North Europe: Hamamatsu Photonics Ivalia S.R.L.: Strada della Moia, 1/E, 20020 Arese, (Milano), Italy, Telephone: (39) 02-935-81-733, Fax: (39) 02-935-81-741