




HIRSCHMANN

A BELDEN BRAND

Product information BAT-ANT-N-8G-DS-IP65

Industrial Ethernet:Industrial Wireless LAN:Accessories:Antenna:BAT-ANT-N-8G-DS-IP65

<http://e-catalog.hirschmann.com/link/57078-24455-49859-24498-24499-65278/en/conf/uistate>

Name		BAT-ANT-N-8G-DS-IP65
		
		directional diversity antenna linear for 2.4 GHz
Delivery informations		
Availability		available
Product description		
Description		directional diversity antenna linear for 2.4 GHz
Type		BAT-ANT-N-8G-DS-IP65
Order No.		943 981-009
Cable length		1 m
Cable specification		N male to N male
Radio technology		
Range		Please refer to the Antenna Distance Calculator.
Frequency band		2300 MHz - 2500 MHz
Polarisation		dual linear, +/- 45° slant
Elevation, Azimuth		3 dB beam width 70° / 80°
VSWR		1.5
Gain		8.5 dBi
Antenna connector		N female
Ambient conditions		
Operating temperature		-40 °C to +80 °C
Storage/transport temperature		-40 °C to +80 °C
Wind load		15 N at 160 km/h
Mechanical construction		
Dimensions (W x H x D)		101 mm x 95 mm x 32 mm
Mounting		wall, mast
Protection class		IP65
Material		LEXAN EXL 9330
Weight		0.11 kg
Scope of delivery and accessories		
Scope of delivery		antenna, 2x 1 m cable, mounting material, 2x Pigtail N to RP-SMA

For more information please contact:

Hirschmann Automation and Control GmbH

Stuttgarter Strasse 45-51

72654 Neckartenzlingen

Germany

Phone: +49 7127/14-1809

E-Mail: inet-sales@belden.com

The information published in the websites has been compiled as carefully as possible. It is subject to alteration without notice in technical as well as in price-related/commercial respect.
The complete information and data were available on user documentation. Mandatory information can only be obtained by a concrete query.