


Low Voltage Hot Swap Controllers


LTC4232: 5A Integrated Hot Swap™ Controller

- Small Footprint
- 33mΩ MOSFET with R_{SENSE}
- Wide Operating Voltage Range: 2.9V to 15V
- Adjustable, 10% Accurate (5A) Current Limit
- Current and Temperature Monitor Outputs
- Overtemperature Protection
- Adjustable Current Limit Timer Before Fault
- Power Good and Fault Outputs
- Adjustable Inrush Current Control
- 2% Accurate UV and OV Protection




LTC4210: Hot Swap Controller in 6-Lead SOT-23 Package

- Adjustable Analog Current Limit with Circuit Breaker
- Fast Response Limits Peak Fault Current
- Adjustable Supply Voltage Power-Up Rate
- High Side Drive for External N-Channel MOSFET
- Controls Supply Voltages from 2.7V to 16.5V
- Undervoltage Lockout
- Adjustable Overvoltage Protection Using Timer Pin
- LTC4210-1: Automatic Retry After Fault
- LTC4210-2: Latchoff After Fault
- Low Profile (1mm) SOT-23 (ThinSOT™) Package



LTC4280/LTC4215: Hot Swap Controllers with I²C Interface and ADC


- 8-Bit ADC Monitors Current and Voltage
- I²C/SMBus Interface
- Wide Operating Voltage Range: 2.9V to 15V
- Inrush Current Limit with Foldback
- LTC4280 Has Adjustable Overcurrent Filter Time
- LTC4215 Has Fixed Overcurrent (20μs/420μs), Optional Soft-Start for Inrush Current (Controlled di/dt)
- High Side Drive for External N-Channel MOSFET
- No External Gate Capacitor Required
- Input Overvoltage/Undervoltage Protection
- Optional Latchoff or Auto-Retry After Faults
- Alerts Host After Faults



LT, LT, LTC, LTM, Linear Technology and the Linear logo are registered trademarks and Hot Swap and ThinSOT are trademarks of Linear Technology Corporation. All other trademarks are the property of their respective owners.


LTC4224: Compact Dual Low Voltage Hot Swap Controller

- Controls Load Voltages from 1V to 6V
- No Gate Components Required
- Adjustable Current Limit with Circuit Breaker
- Limits Peak Fault Current in $\leq 1\mu\text{s}$
- No External Timing Capacitor Required
- Adjustable Supply Voltage Power-Up Rate
- Gate Drive for External N-Channel MOSFET
- LTC4224-1: Latchoff After Fault
- LTC4224-2: Automatic Retry After Fault



LTC4223: Dual Supply Hot Swap Controller for AMC and MicroTCA

- Controls 12V and 3.3V Auxiliary Supplies
- Integrated 0.3Ω Auxiliary Switch
- Fast Response Limits Peak Fault Current
- Adjustable Current Limit Circuit Breaker for 12V Supply
- Analog Current Limiting for 3.3V Auxiliary Supply
- Adjustable 12V Power-Up Rate with External Capacitor
- High Side Current Sense Monitor for 12V Output
- Thermal Shutdown Protection
- LTC4223-1: Latchoff After Fault
- LTC4223-2: Automatic Retry After Fault
- MicroTCA and AdvancedMC Applications



Low Voltage Hot Swap Controller Selection Guide

Part Number	# of Channels	V_{IN} Range	Active Limiting	Fold-back	Soft-Start	Power Good	Fault	I^2C ADC	Internal MOSFET	Extra Features	Packages
LTC4210	1	2.7V to 16.5V	•							Adjustable Overvoltage Protection	SOT-23
LTC4211	1	2.5V to 16.5V					•			Reset Output	SO-8, MSOP-8, MSOP-10
LTC4215	1	2.9V to 15V	•	•	•	•	•	8-Bit		Fixed Overcurrent Filter Time GPIO, Up to 27 I^2C Addresses	4mm x 5mm QFN-24, SSOP-16
LTC4280	1	2.9V to 15V	•	•		•	•	8-Bit		Adj. Overcurrent Filter Time	4mm x 5mm QFN-24
LTC4218/ LTC4218-12	1	2.9V to 26.5V 12V Preset	•	•		•	•			Current and Temperature Monitor Outputs	5mm x 3mm DFN-16, SSOP-16
LTC4217/ LTC4217-12	1	2.9V to 26.5V 12V Preset	•	•		•	•		2A	Current and Temperature Monitor Outputs	5mm x 3mm DFN-16, TSSOP-20
LTC4219-5/ LTC4219-12	1	5V/12V Preset	•	•		•	•		5A	Current and Temperature Monitor Outputs	5mm x 3mm DFN-16
LTC4232	1	2.9V to 15V	•	•		•	•		5A	Current and Temperature Monitor Output	5mm x 3mm DFN-16
LTC4221	2	1V to 13.5V	•	•		•	•			Supply Sequencing	Narrow SSOP-16
LTC4222	2	2.9V to 29V	•	•	•	•	•	10-Bit		Dual Version of LTC4215 with 10-Bit ADC and Wide Input Range	5mm x 5mm QFN-32, SSOP-36
LTC4223	2	12V and 3.3V Auxiliary	•			•	•			MicroTCA Compliant Current Monitor Output	5mm x 4mm DFN-16, SSOP-16
LTC4224	2	1V to 6V	•				•			Small Solution Size	3mm x 2mm DFN-10, MSOP-10