

Serial High-Speed WAN Interface Cards for Cisco 1861 Router

Cisco® integrated services routers offer a wide variety of WAN connectivity modules to accommodate the range of application needs in customer networks. The new Cisco 1-Port and 2-Port Serial High-Speed WAN Interface Cards (HWICs) provide serial WAN connectivity services for the Cisco 1861 Integrated Services Router deployed in small and medium-sized businesses (SMBs) and enterprise branch offices.

Product Overview

Cisco serial HWICs provide serial WAN connectivity to remote sites using Cisco High-Level Data Link Control (HDLC), Point-to-Point Protocol (PPP), or Frame Relay encapsulation. These HWICs also support older protocol transport such as Systems Network Architecture (SNA), Synchronous Data Link Control (SDLC) Protocol, Binary Synchronous Communications Protocol (Bisync), and X.25.

Cisco offers two serial HWICs for the Cisco 1861:

- 1-Port Serial High-Speed WAN Interface Card
- 2-Port Serial High-Speed WAN Interface Card

Figure 1. Cisco Serial HWICs



Feature Summary

- 1 or 2 serial ports
- Maximum data rate of 8 Mbps per port on the 2-port serial HWIC
- Support for serial protocols: EIA-232, EIA-449, EIA-530, EIA-530A, V.35, X.21
- Support for Lead Manipulation
- Capability to measure the incoming clock rate of synchronous ports in data terminal equipment (DTE) mode

Product Specifications

Table 1 lists the product specifications of the new serial HWICs and compares them with specifications for the Cisco 1-Port and 2-Port Serial WAN Interface Cards (WICs).

Table 1. Cisco Serial HWIC and WIC Specifications

Specification	1-Port HWIC (HWIC-1SER)	2-Port HWIC (HWIC-2SER)	1-Port WIC (WIC-1T)	2-Port WIC (WIC-2T)
Synchronous Support	Yes	Yes	Yes	Yes
Synchronous Maximum Speed (per Port)	2 Mbps	8 Mbps	2.048 Mbps	8 Mbps
Asynchronous Support	No	No	Yes	Yes
Asynchronous Maximum Speed (per Port)	—	—	115.2 Kbps	115.2 Kbps
Bisync Support	Yes	Yes	Yes	Yes
Serial Protocols	<ul style="list-style-type: none"> • EIA-232, EIA-449, • EIA-530, EIA-530A, • V.35, X.21 	<ul style="list-style-type: none"> • EIA-232, EIA-449, • EIA-530, EIA-530A, • V.35, X.21 	<ul style="list-style-type: none"> • EIA-232 • EIA-449 • EIA-530 • V.35 • X.21 	<ul style="list-style-type: none"> • EIA-232 • EIA-449 • EIA-530 • EIA-530A • V.35 • X.21
Lead Manipulation	Yes	Yes	No	No
Network Clock Synchronization	Yes	Yes	No	No

Connectors and Cabling

The Cisco serial HWICs have connectors and cabling that allow high port densities in the compact HWIC form factor. Tables 2 and 3 list connector and cabling specifications.

Table 2. Connectors and Cabling

HWIC	Connectors	Available Cables
1-Port HWIC 2-Port HWIC	Smart Serial	See Table 3

Smart Serial Cabling

The Cisco 2-Port Serial HWIC and 1-Port Serial HWIC each have two Smart Serial ports and one Smart Serial port respectively. These ports use the same connectors and cabling as the Cisco 4-Port Serial HWIC.

Table 3. Smart Serial Cabling for Cisco Serial HWICs

Product Number	Cable Type	Length	Connector Type
CAB-SS-V35MT	V.35 DTE	10 ft (3m)	Male
CAB-SS-V35FC	V.35 DCE	10 ft (3m)	Female
CAB-SS-232MT	EIA/TIA-232 DTE	10 ft (3m)	Male
CAB-SS-232FC	EIA/TIA-232 DCE	10 ft (3m)	Female
CAB-SS-449MT	EIA/TIA-449 DTE	10 ft (3m)	Male
CAB-SS-449FC	EIA/TIA-449 DCE	10 ft (3m)	Female
CAB-SS-X21MT	X.21 DTE	10 ft (3m)	Male
CAB-SS-X21FC	X.21 DCE	10 ft (3m)	Female
CAB-SS-530MT	EIA/TIA-530 DTE	10 ft (3m)	Male
CAB-SS-530AMT	EIA/TIA-530A DTE	10 ft (3m)	Male

Compliance and Hardware Specifications

Agency Approvals

- UL 1950 (United States)
- CSA-C22.2 #950 (Canada)
- EN60950 (Europe)
- TUV GS (Germany)
- IEC 950 (International)

Immunity

- EN300386
- EN55024/CISPR24
- EN50082-1

Emissions

- FCC Part 15 Class A
- ICES-003 Class A
- EN55022 Class A
- CISPR22 Class A
- AS/NZS 3548 Class A
- VCCI Class A
- EN 300386
- EN61000-3-3
- EN61000-3-2

Physical Specifications

- Single-width HWIC, no slot restrictions
- Dimensions (H x W x D) 0.8 x 3.1 x 5.6 in. (2.1 x 7.9 x 14.2 cm)

Environmental Specifications

- Operating temperature: 32 to 104°F (0 to 40°C)
- Storage temperature: -4 to 149°F (-20 to 65°C)
- Relative humidity: 10 to 90 percent, noncondensing

Platform Support

The Cisco serial HWICs are supported on the onboard HWIC slot of the Cisco 1861 Integrated Services Router. The minimum Cisco IOS® Software Release is 12.4(11)XW.

Ordering Information

The Cisco serial HWICs are currently available for order from the Cisco Ordering Tool.

Table 4 lists the product numbers of the Cisco serial HWICs.

Table 4. Product Numbers

Product Number	Description
HWIC-1SER	1-Port Serial High-Speed WAN Interface Card
HWIC-2SER	2-Port Serial High-Speed WAN Interface Card

Service and Support

Using the Cisco Lifecycle Services approach, Cisco and its partners provide a broad portfolio of end-to-end services and support that can help increase your network's business value and return on investment. This approach defines the minimum set of activities needed, by technology and by network complexity, to help you successfully deploy and operate Cisco technologies and optimize their performance throughout the lifecycle of your network.

For More Information

For more information about the Cisco 1-Port and 2-Port Serial High-Speed WAN Interface Cards and the Cisco 1861 Integrated Services Router, please visit

http://www.cisco.com/en/US/products/ps5949/products_data_sheets_list.html or contact your local account representative.



Americas Headquarters
Cisco Systems, Inc.
170 West Tasman Drive
San Jose, CA 95134-1706
USA
www.cisco.com
Tel: 408 526-4000
800 553-NETS (6387)
Fax: 408 527-0883

Asia Pacific Headquarters
Cisco Systems (USA) Pte. Ltd.
168 Robinson Road
#28-01 Capital Tower
Singapore 068912
www.cisco.com
Tel: +65 6317 7777
Fax: +65 6317 7799

Europe Headquarters
Cisco Systems International BV
Haarlerbergpark
Haarlerbergweg 13-19
1101 CH Amsterdam
The Netherlands
www-europe.cisco.com
Tel: +31 0 800 020 0791
Fax: +31 0 20 357 1100

Cisco has more than 200 offices worldwide. Addresses, phone numbers, and fax numbers are listed on the Cisco Website at www.cisco.com/go/offices.

CCVP, the Cisco logo, and Welcome to the Human Network are trademarks of Cisco Systems, Inc.; Changing the Way We Work, Live, Play, and Learn is a service mark of Cisco Systems, Inc.; and Access Registrar, Aironet, Catalyst, CCDA, CCDP, CCIE, CCIP, CCNA, CCNP, CCSP, Cisco, the Cisco Certified Internetwork Expert logo, Cisco IOS, Cisco Press, Cisco Systems, Cisco Systems Capital, the Cisco Systems logo, Cisco Unity, Enterprise/Solver, EtherChannel, EtherFast, EtherSwitch, Fast Step, Follow Me Browsing, FormShare, GigaDrive, HomeLink, Internet Quotient, IOS, iPhone, IP/TV, iQ Expertise, the iQ logo, iQ Net Readiness Scorecard, iQuick Study, LightStream, Linksys, MeetingPlace, MGX, Networkers, Networking Academy, Network Registrar, PIX, ProConnect, ScriptShare, SMARTnet, StackWise, The Fastest Way to Increase Your Internet Quotient, and TransPath are registered trademarks of Cisco Systems, Inc. and/or its affiliates in the United States and certain other countries.

All other trademarks mentioned in this document or Website are the property of their respective owners. The use of the word partner does not imply a partnership relationship between Cisco and any other company. (0711R)