

User's Guide of Motherboard


(694 V1.0)

CONTENTS

The installation of motherboard's chip driver.....	1
The installation of on-board audio driver.....	2

The installation of motherboard's chip driver

If you have reinstalled Windows98 or Windows2000 OS, you may install the motherboard's chip driver in the driver's CD enclosed with the machine. Since the installation process of Windows98 and Windows2000 are basically the same, We shall illustrate to you how to install by Windows98 (the "X" hereunder means the disk mark of your CD-ROM).

Motherboard

1. Install Windows98;
2. Insert the CD of "Legend computer driver" into CD-ROM drive;
3. Enter the directory: " X:\Lx-chip\VIA4in1";
4. Run the process of Setup.exe and select the options as the system prompted in the course of installation. Single click "Next" or "OK" until the very end without any alterations;
5. Reboot the computer and the installation finishes.

Notice:

- 1) Because of our upgrade of the drivers, the actual display of screen when you operate the machine may not be the same as described here.

The installation of on-board audio driver

The motherboard we use here integrates audio chip which can be installed after loading motherboard's chip driver and display adapter driver. You can install it with the driver CD supplied with the machine and the steps are as follows:

1. Insert the CD of "Legend computer driver" into the CD driver;
2. Open the "control panel" and double click the "system" icon;
3. Choose the "Device manager";
4. Remove "PCI Multimedia Audio Device", click "refresh" and the dialogue of "Adding New Hardware Wizard" pops up, Click "Next" and select "search for the best driver for your device (Recommended) ", single click "Next"
5. Specify a location at "X:\LX_SOUND\686Asound\win98SE";
6. Click "Next" and duplicate the file;
7. After installing the driver, you need to reboot the system to make the audio drive work properly.