

iQ Pro R210L

Barco's Network Centric LCD projector with SXGA+ resolution and a brightness level of 2,200 ANSI lumens.



Barco's iQ™ Pro R210L is designed for intensive use applications where the projector runs most of the day, i.e. reception areas. The iQ Pro projector is the first projector on the market which includes a powerful computer processing server for full networking capability and truly wireless presentations.

Display up to 3 source windows simultaneously, thanks to its advanced picture-in-picture functionality.

Its built-in switcher makes seamless source switching a snap.

Barco's innovative dual-lamp system guarantees optimal reliability: the light will never go out during your presentation. This revolutionary networked LCD projector with SXGA+ resolution delivers a brightness level of 2,200 ANSI lumens.

BARCO

Visibly yours

技术规格

光输出	2,200 ANSI lumen
亮度均匀性	>95% for the total screen
对比度	> 800:1 (full white/full black)
LCD面板	3 active matrix 1.4" diagonal SXGA+ polysilicon LCD panels with Micro Lens Arrays and a resolution of 1400 x 1050 pixels (aspect ratio 4:3).
分辨率	1400 x 1050 (native)
网络连接	<ul style="list-style-type: none"> PCMCIA slot for Wireless LAN cards, memory cards, Bluetooth, input extensions ... RJ45 connector for Ethernet (10Mb/s) and Fast Ethernet (100Mb/s) 4 USB connectors Audio: 3,5 mm jacks for Microphone in, Line in and Line out
特性	Advanced picture-in-picture Seamless switching with effects Standard cable basket Standard light shutter Advanced digital zoom
兼容性	<ul style="list-style-type: none"> All current video sources (PAL, SECAM, NTSC) in Composite, S-VHS, Component or RGB formats All currently proposed HDTV, extended and improved television standards (1080i, 720p) All computer graphics formats from VGA, SVGA, XGA, SXGA to UXGA Most Macintosh computers Electronic workstations with a resolution up to 1600 x 1200 pixels at 75 Hz Most computer sources with a pixel clock up to 160 MHz DVI sources up to SXGA
屏幕尺寸	From 1-6m/3-20 ft.
输出	<ul style="list-style-type: none"> 1x Configurable 5-Wire (BNC) for: Composite Video, S-Video, Component Video, RGBHV, RGBS, RGsB. 1 x Composite Video (BNC) (up to 7 Composite Video's when using all connectors on top input board) 1x S-Video (4-pin mini-DIN) (up to 3 S-Video's when combining BNC's) 1x VGA (D15 connector) 1x DVI (Digital Visual Interface)
灯泡	2x 120 Watt UHP lamp, in lamp housing Typical lifetime: 6000 h/lamp. 6000 hours in Dual Lamp Mode or max. 12000 hours/set in Single Lamp Mode
镜头	Fixed focal length lenses are available with a throw ratio of 0.85:1 (very short throw ratio, specially designed for rear screen on-axis projection) or 7.0:1 (long throw). Variable focus lenses with a throw distance of 1.3-1.8, 1.9-2.6, 3.0-6.0 times the screen width
扫描频率	Horizontal 15 kHz - 110 kHz Vertical 25 Hz - 150 Hz
镜头移动	V shift: -30% +110%
尺寸(宽x长x高)	Projector body with cable basket: 415 mm (Max W) x 195 mm (Max H) x 565 mm Projector body without cable basket: 415 mm (Max W) x 195 mm (Max H) x 487 mm (Max D)
重量	Net weight, body only: 12.9kg/28.5 lbs.
通信	<ul style="list-style-type: none"> 1x D9 connectors for RS232 In/Out 1x spherical IR receiver
噪音级别	<37dB
电源	Power factor pre-regulated SMPS, 90-254 VAC / 50-60Hz
功率消耗	Max 380 Watt
功率消耗	Max 1297 BTU/h
安全级别	Compliant with UL1950 and EN60950

电磁干扰	BARCO's iQ Pro R210L complies with FCC rules & regulations, part 15 Class B and CE EN55022 Class B
无缝切换	standard