

DLA-AIOL0 1400 Series IP Video Storage Array



- ▶ **All-in-one recording solution for up to 64 channels**
- ▶ **Pre-installed, pre-configured IP storage solution**
- ▶ **4 TB (4 x 1 TB) storage capacity**
- ▶ **Redundant dual Gigabit Ethernet network interface ports**
- ▶ **RAID-5 hardware redundancy**
- ▶ **Dedicated storage operating system delivers robust , secure operation**
- ▶ **Hot-swappable hard drives**
- ▶ **Remote monitoring via desktop application or browser**

The 1400 Series IP Video Storage Appliance is an affordable, simple and reliable all-in-one recording management solution for network surveillance systems of up to 64 cameras. Powered by Bosch VRM (Video Recording Manager) software, the 1400 Series is an intelligent IP storage device that eliminates the need for separate NVR (Network Video Recorder) server and storage hardware, reducing the total cost of ownership by as much as 45%.

DLA-AIOL0 is a 1U rack mount unit that combines advanced recording management and state-of-the-art iSCSI storage into a single cost-effective, plug and play IP recording appliance for IT-minded customers which are seeking for a state-of-the-art “second generation” NVR recording solution.

系统概览

The 1400 Series IP Video Storage Appliance utilizes an energy efficient, embedded design which reduces possible points of failure and boasts Bosch quality through-and-through. Utilizing “surveillance-rated” hard drives in a fault tolerant RAID-5 configuration, redundant Gigabit Ethernet network interfaces, 4 GB system memory and an Intel® Pentium Dual Core Processor, the DLA 1400 Series delivers high-end performance at a very affordable price.

Easy to install, the DLA 1400 Series features wizard-based set-up and centralized configuration to reduce installation times by as much as 50%. All components are pre-installed and pre-configured. Simply connect to the network and power the unit up—the 1400 Series is ready to begin recording straight out of the box.

To create a complete video management solution, just add Bosch VMS (Video Management System) Lite—for up to 64 cameras—or Bosch VMS Professional Edition—for up to 128 cameras. Adding Bosch VMS software turns the 1400 Series into a scalable IP video management solution. Bosch Video Management System (VMS) 可以管理您的所有 IP 和数字视频和音频以及通过 IP 网络传输的所有安全数据。Bosch VMS seamlessly combines IP cameras and encoders, provides system-wide event and alarm management, system health monitoring, user and priority management.

基本功能

The 1400 Series features a single-socket-system, server-class motherboard, highly energy-efficient hot-swap redundant power supplies, as well as hot-swap SATA-II hard drives providing 4 TB of gross storage capacity. All system software is pre-installed and pre-activated—creating an out-of-the-box ready-to-use recording appliance. The DLA 1400 Series utilizes Microsoft

Windows Storage Server 2008. Windows Storage Server is a proven operating system platform that has been specifically optimized for storage applications. The Microsoft implementation of iSCSI is a reference in the industry. It delivers the highest possible quality and reliability, and is a field-proven technology installed on millions of servers worldwide.

This next generation of Windows Storage Server is focused on providing a secure platform:

- Hardened platform with reduced high risk layers
- Prevent abnormal activity in the file system and registry
- Re-architected platform to reduce corruption and compromise of the system
- Windows Service Hardening
- Windows Firewall with Advanced Security
- Enhanced and improved TCP/IP Stack

Windows Storage Server is a **dedicated OS** for Storage that has a significantly reduced attack surface than a normal Windows Server. It does not run any exposed applications like email, browser or media player and has a reduced set of services.

管理

Microsoft Windows Storage Server 2008 provides a simple, intuitive user interface for system configuration and unified storage appliance management. Administrators and IT professionals will appreciate the ability to manage the Bosch 1400 Series using the built-in Microsoft System Center Suite. The ability to use one central tool for configuration and operations management reduces installation and training requirements, and helps keep ongoing system management costs low.

监控

The 1400 Series provide SNMP, Remote Desktop and HTTP monitoring support for the Bosch VRM recording management application and the system's hardware.

Increased reliability of high-availability hardware, embedded design as well system-wide monitoring and management ensure maximum uptime.

Bosch Quality

Bosch subjects all its products to the most comprehensive and rigorous battery of quality endurance tests in the industry. Our recording products are subjected to extreme temperatures, voltages and vibrations to determine true operating limits, so you can be assured of years of reliable operation. And Bosch firmly stands behind every product it sells with an end-to-end 3 year warranty backed by 24/7 technical support.

证书与认可

| 地区 | 认证 |
|----|-------------------------|
| 欧洲 | CE DLA-AIOL 1400 Series |

安装/配置

The 1400 Series comes pre-configured in a RAID-5 standard configuration with 4 LUNs and provides the following specifications:

| Gross Capacity | 净容量 | 带宽 | iSCSI Sessions |
|----------------|---------|------------|----------------|
| 4 x 1 TB | 2690 GB | 200 Mbit/s | 64+ |

These values refer to the Bosch recording applications; Net capacity for a RAID-5 configuration without hot spare; 64+ concurrent iSCSI sessions indicate the number of concurrent recording sessions plus 8 sessions for replay. The 1400 Series may be upgraded either once with an additional 64 channel license or twice with a 32 channel license. The respective upgrade licenses have to be purchased. The upgrade allows for a maximum of 128+ sessions: 128 sessions for recording, 8 sessions for replay.

注解 Bosch is not liable for system failures of DLA 1400 Series units without internal hard drives (available in the Asia-Pacific-Region only).

附件

| | |
|-----------------------|----------------------------------------------------|
| 处理器 | |
| 处理器 | Intel® Pentium G6950 Dual Core (3M Cache, 2.8 GHz) |
| 槽口 | 1 |
| Cache memory | 1 x 3 MB Level 2 cache |
| Memory protection | ECC Unbuffered |
| Max front side bus | 1333 MHz |
| 内存 | |
| Memory Installed | 4 GB, DDR3-1333 ECC UNB (2 x 2 GB) |
| 存储 | |
| 存储类型 | 4 Trays: 3.5-inch SATA |
| Hard Drives Installed | 4 TB, WD 1.0 TB 7.200 RPM 32 M 3.5" |
| SAS RAID Card | AOC-SASLP-H8iR (8-Ports LSI 1078 SAS Controller) |

技术规格

电气指标

120 VAC Input

| | |
|-----------------------------------------|----------|
| Actual output wattage from power supply | 202.72 W |
|-----------------------------------------|----------|

| | |
|----------------------------|-----|
| Efficiency of power supply | 88% |
|----------------------------|-----|

| | |
|--------------------------------|----------|
| Total system power consumption | 230.37 W |
|--------------------------------|----------|

| | |
|-------------|--------|
| Total BTU/h | 786.24 |
|-------------|--------|

| | |
|--------------|----|
| Power Factor | 95 |
|--------------|----|

| | |
|--------------------------------|-----------|
| System AC input VA requirement | 242.49 VA |
|--------------------------------|-----------|

| | |
|------|--------|
| 输入电流 | 2.02 A |
|------|--------|

240 VAC Input

| | |
|-----------------------------------------|----------|
| Actual output wattage from power supply | 256.44 W |
|-----------------------------------------|----------|

| | |
|----------------------------|-----|
| Efficiency of power supply | 90% |
|----------------------------|-----|

| | |
|--------------------------------|----------|
| Total system power consumption | 225.25 W |
|--------------------------------|----------|

| | |
|-------------|--------|
| Total BTU/h | 768.77 |
|-------------|--------|

| | |
|--------------|----|
| Power Factor | 92 |
|--------------|----|

| | |
|--------------------------------|-----------|
| System AC input VA requirement | 244.83 VA |
|--------------------------------|-----------|

| | |
|------|--------|
| 输入电流 | 1.02 A |
|------|--------|

The 1400 Series comes fully loaded and fully functional with Microsoft Operating System and Bosch recording application pre-installed

机械指标

| | |
|----|-----------------------------|
| 小型 | 1 U Rack Mount (815TQ-R700) |
|----|-----------------------------|

| | |
|----|----------------------------|
| 电源 | 700 W Gold Level Redundant |
|----|----------------------------|

| | |
|--------|------------------------------------------------------|
| USB 端口 | 4 USB 2.0: 2 in rear, 2 in front, (1 Type-A Onboard) |
|--------|------------------------------------------------------|

| | |
|--------------|-------------------------------|
| Network (网络) | Dual Intel® 82573 Gigabit LAN |
|--------------|-------------------------------|

| | |
|----------------|--------------------------------------------|
| 尺寸 (高 x 宽 x 厚) | 437 x 44.5 x 648 mm (17.2 x 1.7 x 25.5 in) |
|----------------|--------------------------------------------|

| | |
|----|-----------------|
| 重量 | 16.3 kg (36 lb) |
|----|-----------------|

环境

| | |
|------|-------------------------------------|
| 操作温度 | +10 °C to +35 °C (+50 °F to +95 °F) |
|------|-------------------------------------|

| | |
|-------|----------------------------------|
| 非操作温度 | -25°C 至 +70°C (-13°F 至 +158°F) |
|-------|----------------------------------|

| | |
|-----------------------------|---------------|
| Operating Relative Humidity | 10% 至 90% 无冷凝 |
|-----------------------------|---------------|

| | |
|---------------------------------|--------------|
| Non-Operating Relative Humidity | 5% 至 95% 无冷凝 |
|---------------------------------|--------------|

订购信息

DLA-AIOL0-04AT

1400 Series IP Video Storage Array, 4 x 1 TB

DLA-AIOL0-04AT

DLA-AIOL0-000N

1400 Series IP Video Storage Array, Empty Chassis (Asia-Pacific-Region only)

DLA-AIOL0-000N

DLA-XVRM-032

AIO-upgrade license for 32 cameras (e-license)

DLA-XVRM-032

DLA-XVRM-064

AIO-upgrade license for 64 cameras (e-license)

DLA-XVRM-064

硬件附件

DLA-LDTK-100A

1000 GB HDD

DLA-LDTK-100A

DLA-AIOL0-DOM

Disk on Module

DLA-AIOL0-DOM

中国大陆联络方式:
上海
中国上海天目西路 218 号
办公楼第一座 3105-3110 室
邮编: 200070
电话: +86 21 63172155
传真: +86 21 63173023
www.boschsecurity.com.cn

中国香港联络方式:
香港
香港 沙田安心街 11 号 5 楼
华顺广场 506-509 室
电话: +852 2635 2815
传真: +852 2648 7986
www.boschsecurity.com.cn

Represented by