

17 x **20**
、

MCL-Designer

30 **9.1**

123Scan **ADF**

MCL-Designer

12 **336**

□□□□ □

□□ 7.0 x 9.2 x 3.5 □□ □ 17.8 x 23.1 x 9.0 □□□□x□x□

□□□□

□□□□ 1D, □□□□□□□□□□□□□□□□□□□□

□□ □□□□□

□□□□□□□ 100% UPC□□ 1.5 □ 16.5 □□ □ 3.81 □ 41.91 □□□

□□□□ □□

□□□□□□□□□, RS-232, Synapse, USB

□□□□□□□

□□□□□□□ □□□□□。

□□□□

EN 300 328

UL 60950-1, C22.2 No. 60950-1, EN 60950-1, IEC 60950-1

RoHS 2002/95/EEC

EMC EN 301 489-17, ICES 003 B, EN 55024, EN 61000-3-3, EN 301 489-1, FCC 15 B, EN 6

RF EN 50360, EN 50361, FCC Part 2, OET Bulletin 65, RSS102

² EN 60825-1, IEC 60825-1, 21CFR1040.10

-40° 158° F -40° 70° C

10,000 107,644 lux 450 (4,844 Lux)

5 1.5

32° 104° F 0° 40° C
