



[1] EC-TYPE EXAMINATION CERTIFICATE

[2] Equipment Intended for use in Potentially Explosive Atmospheres Directive 94/9/EC

[3] Type Examination Certificate Number:

Nemko 04ATEX1448

[4] Equipment:

Asynchronous motors

[5] Applicant:

ABB Automation Technologies AB

LV Motors

[6] Address:

Örjansgränd 10 SE-721 70 Västerås

Sweden

- [7] This equipment and any acceptable variation thereto are specified in the schedule to this certificate and the documents therein referred to.
- [8] Nemko AS, notified body number 0470 in accordance with Article 9 of Council Directive 94/9/EC of 23 March 1994, certifies that this equipment or protective system has been found to comply with the Essential Health and Safety requirements relating to the design and construction of equipment and protective systems intended for use in potentially explosive atmospheres given in Annex II to the Directive.
- [9] The examination and test results are recorded in confidential report no.

22852Ex01-03

[10] Compliance with the Essential Health and Safety Requirements, with the exception of those listed in the schedule of this certificate, has been assessed by reference to:

CENELEC EN 50014: 1997 +A1:1999, A2:1999

CENELEC EN 50281-1-1: 1998

IEC 61241-0:2004

IEC 61241-1:2004

CENELEC EN 61241-1:2004

- [11] If the sign "X" is placed after the certificate number, it indicates that the equipment is subject to special conditions for safe use specified in the schedule to this certificate.
- [12] This EC-TYPE EXAMINATION CERTIFICATE relates only to the design, examination and tests of the specified equipment or protective system in accordance to the directive 94/9/EC.

 Further requirements of the Directive apply to the manufacturing process and supply of this equipment or protective system. These are not covered by this certificate.
- [13] The marking of the equipment shall include the following:

 $\langle E_{\mathsf{X}} \rangle$ II 2 D T125°C

Ex tD A21 T125°C

Oslo, 2005-02-11

Rolf Hoel

Certification Department

This certificate and its schedules may only be reproduced in its entirety and without any change

+47 22 96 05 50

[16]

Nemko 04ATEX1448



Page 2 of 4

Date: 2005-02-11

[14] Schedule

[15] TYPE EXAMINATION CERTIFICATE No Nemko 04ATEX1448

Description of Equipment

This Certificate covers a series of IP65 dust tight asynchronous motors with aluminium housing. Duty type: S1.

Motors at intermitted duty: S2 ... S8, S10 according to the specification stated in the descriptive documents are accepted.

Ambient temperature is between -20° C and 40° C, but operation at 40 to 60° C is permissible provided that documented tests are carried out to ensure conformity as described in the descriptive documents.

Motors with frequency converter must be supplied and loaded according to the manufacturers Technical Description, 3GZV100054 clause 9.2.5.

A second rating plate will be mounted on the motor, mentioning the voltage, current and load conditioning in function of the frequency range, as well as the relevant converter characteristic.

Ingress Protection Code

IP65 according to EN 60529.

| Туре | Pole | Speed | Output | Voltage | Freq. | | |
|-------------|------|-----------|---------|-------------|-------|--|--|
| designation | | r/min | kW | V | Hz | | |
| M3AA112M | 2 | 2860-3460 | 4-4.6 | 380-420-440 | 50-60 | | |
| M3AA112MB | 2 | 2855-3455 | 5.5-6.4 | 380-420-440 | 50-60 | | |
| M3AA112M | 4 | 1455-1760 | 4-4.6 | 380-420-440 | 50-60 | | |
| M3AA112M | 6 | 940-1140 | 2.2-2.5 | 380-420-440 | 50-60 | | |
| M3AA112M | 8 | 695-850 | 1.5-1.7 | 380-420-440 | 50-60 | | |
| M3AA132SA | 2 | 2900-3500 | 5.5-6.4 | 380-420-440 | 50-60 | | |
| M3AA132SB | 2 | 2915-3515 | 7.5-8.6 | 380-420-440 | 50-60 | | |
| M3AA132S | 4 | 1460-1760 | 5.5-6.4 | 380-420-440 | 50-60 | | |
| M3AA132M | 4 | 1450-1750 | 7.5-8.6 | 380-420-440 | 50-60 | | |
| M3AA132S | 6 | 960-1160 | 3-3.5 | 380-420-440 | 50-60 | | |
| M3AA132MA | 6 | 960-1160 | 4-4.6 | 380-420-440 | 50-60 | | |
| M3AA132MB | 6 | 955-1155 | 5.5-6.4 | 380-420-440 | 50-60 | | |
| M3AA132S | 8 | 720-870 | 2.2-2.5 | 380-420-440 | 50-60 | | |
| M3AA132M | 8 | 720-870 | 3-3.5 | 380-420-440 | 50-60 | | |
| M3AA160MA | 2 | 2930-3530 | 11-12.5 | 380-415-440 | 50-60 | | |
| M3AA160M | 2 | 2920-3520 | 15-17.5 | 380-415-440 | 50-60 | | |
| M3AA160L | 2 | 2920-3520 | 18.5-21 | 380-415-440 | 50-60 | | |
| M3AA160M | 4 | 1465-1750 | 11-12.5 | 380-415-440 | 50-60 | | |
| M3AA160L | 4 | 1455-1755 | 15-18 | 380-415-440 | 50-60 | | |
| M3AA160M | 6 | 970-1170 | 7.5-8.6 | 380-415-440 | 50-60 | | |
| M3AA160L | 6 | 970-1170 | 11-12.5 | 380-415-440 | 50-60 | | |
| M3AA160MA | 8 | 715-865 | 4-4.6 | 380-415-440 | 50-60 | | |
| M3AA160M | 8 | 710-865 | 5.5-6.3 | 380-415-440 | 50-60 | | |
| M3AA160L | 8 | 715-860 | 7.5-8.6 | 380-415-440 | 50-60 | | |
| M3AA180M | 2 | 2930-3530 | 22-26.5 | 380-415-440 | 50-60 | | |
| M3AA180M | 4 | 1470-1770 | 18.5-22 | 380-415-440 | 50-60 | | |
| M3AA180L | 4 | 1470-1765 | 22-26 | 380-415-440 | 50-60 | | |
| M3AA180L | 6 | 970-1175 | 15-17 | 380-415-440 | 50-60 | | |
| M3AA180L | 8 | 720-870 | 11-13 | 380-415-440 | 50-60 | | |
| M3AA200MLA | 2 | 2955-3555 | 30-35 | 380-415-440 | 50-60 | | |
| M3AA200MLB | 2 | 2950-3550 | 37-43 | 380-415-440 | 50-60 | | |
| M3AA200MLC | 2 | 2950-3550 | 45-52 | 380-415-440 | 50-60 | | |
| M3AA200MLB | 4 | 1475-1775 | 30-35 | 380-415-440 | 50-60 | | |
| M3AA200MLA | 6 | 985-1185 | 18.5-21 | 380-415-440 | 50-60 | | |

This certificate and its schedules may only be reproduced in its entirety and without any change

Enterprise number: NO 974404532



Nemko 04ATEX1448



Date: 2005-02-11

Page 3 of 4

| Type designation | Pole | Speed | Output | Voltage | Freq. |
|-----------------------|---------------|-----------|---------|-------------|-------|
| | | r/min | kW | V | Hz |
| M3AA200MLA | 8 | 740-890 | 15-17 | 380-415-440 | 50-60 |
| M3AA200MLB | 8 | 735-885 | 18.5-21 | 380-415-440 | 50-60 |
| M3AA225SMB | 2 | 2960-3560 | 45-52 | 380-415-440 | 50-60 |
| M3AA225SMC | 2 | 2960-3565 | 55-63 | 380-415-440 | 50-60 |
| M3AA225SMA | 4 | 1480-1785 | 37-42 | 380-415-440 | 50-60 |
| M3AA225SMB | 4 | 1480-1785 | 45-52 | 380-415-440 | 50-60 |
| M3AA225SMC | 4 | 1480-1785 | 55-63 | 380-415-440 | 50-60 |
| M3AA225SMB | 6 | 985-1185 | 30-34 | 380-415-440 | 50-60 |
| M3AA225SMC | 6 | 985-1185 | 37-42 | 380-415-440 | 50-60 |
| M3AA225SMA | 8 | 730-880 | 18.5-21 | 380-415-440 | 50-60 |
| M3AA225SMB | 8 | 730-880 | 22-25 | 380-415-440 | 50-60 |
| M3AA250SMA | 2 | 2970-3570 | 55-63 | 380-415-440 | 50-60 |
| M3AA250SMB | 2 | 2970-3570 | 75-86 | 380-415-440 | 50-60 |
| M3AA250SMA | 4 | 1480-1780 | 55-63 | 380-415-440 | 50-60 |
| M3AA250SMB | 4 | 1480-1780 | 72-82 | 380-415-440 | 50-60 |
| M3AA250SMA | 6 | 985-1185 | 37-42 | 380-415-440 | 50-60 |
| M3AA250SMB | 6 | 985-1185 | 45-52 | 380-415-440 | 50-60 |
| M3AA250SMA | 8 | 735-885 | 30-34 | 380-415-440 | 50-60 |
| M3AA250SMB | 8 | 735-885 | 37-42 | 380-415-440 | 50-60 |
| M3AA280SMA | 2 | 2970-3570 | 75-86 | 380-415-440 | 50-60 |
| M3AA280SMA | 4 | 1480-1780 | 72-82 | 380-415-440 | 50-60 |
| M3AA280SMA | 6 | 985-1185 | 45-52 | 380-415-440 | 50-60 |
| M3AA280SMA | 8 | 735-885 | 37-42 | 380-415-440 | 50-60 |
| M2AA112M | 2 | 2850-3450 | 4-4.6 | 380-420-440 | 50-60 |
| M2AA112M M2AA112M | 4 | 1435-1740 | 4-4.6 | 380-420-440 | 50-60 |
| M2AA132SA | 2 | 2855-3465 | 5.5-6.4 | 380-420-440 | 50-60 |
| M2AA132SB | 2 | 2855-3455 | 7.5-8.6 | 380-420-440 | 50-60 |
| M2AA132S | 4 | 1450-1750 | 5.5-6.4 | 380-420-440 | 50-60 |
| M2AA132M | 4 | 1450-1750 | 7.5-8.6 | 380-420-440 | 50-60 |
| M2AA160MA | 2 | 2915-3510 | 11-13 | 380-415-440 | 50-60 |
| M2AA160M | 2 | 2900-3505 | 15-17.5 | 380-415-440 | 50-60 |
| M2AA160L | 2 | 2915-3515 | 18.5-21 | 380-415-440 | 50-60 |
| M2AA160M | 4 | 1460-1765 | 11-13 | 380-415-440 | 50-60 |
| M2AA160L | 4 | 1460-1760 | 15-17.5 | 380-415-440 | 50-60 |
| M2AA180M | 2 | 2925-3525 | 22-25.5 | 380-415-440 | 50-60 |
| M2AA180M | 4 | 1460-1760 | 18.5-21 | 380-415-440 | 50-60 |
| M2AA180L | 4 | 1460-1760 | 22-25.5 | 380-415-440 | 50-60 |
| | 2 | 2945-3545 | 30-35 | 380-415-440 | 50-60 |
| M2AA200LA M2AA200L | $\frac{2}{2}$ | 2945-3545 | 37-42 | 380-415-440 | 50-60 |
| M2AA200L M2AA200L | 4 | 1470-1770 | 30-35 | 380-415-440 | 50-60 |
| M2AA200L M2AA225M | 2 | 2940-3550 | 45-52 | 380-415-440 | 50-60 |
| M2AA225N M2AA225S | 4 | 1475-1775 | 37-43 | 380-415-440 | 50-60 |
| M2AA225M | 4 | 1475-1775 | 45-52 | 380-415-440 | 50-60 |
| M2AA225M M2AA250M | 2 | 2960-3565 | 55-63 | 380-415-440 | 50-60 |
| M2AA250M M2AA250M | 4 | 1475-1775 | 55-63 | 380-415-440 | 50-60 |



Nemko 04ATEX1448



Date: 2005-02-11

[17] Report No. 22852Ex01-03

Descriptive Documents

| Name/Title | Drawing No. | Rev. | Date | Sheets |
|--|----------------|------|------------|--------|
| | | | | |
| Technical file for ATEX Certification M2AA 112 | 3GZV 100055-9 | 0 | 2004.07.08 | 1 |
| Technical file for ATEX Certification M2AA 132 | 3GZV 100055-10 | 0 | 2004.07.08 | 1 |
| Technical file for ATEX Certification M2AA 160 | 3GZV 100055-11 | 0 | 2004.07.08 | 1 |
| Technical file for ATEX Certification M2AA 180 | 3GZV 100055-12 | 0 | 2004.07.08 | 1 |
| Technical file for ATEX Certification M2AA 200 | 3GZV 100055-13 | 0 | 2004.07.08 | 1 |
| Technical file for ATEX Certification M2AA 225 | 3GZV 100055-14 | 0 | 2004.07.08 | 1 |
| Technical file for ATEX Certification M2AA 250 | 3GZV 100055-15 | 0 | 2004.07.08 | 1 |
| Technical file for ATEX Certification M3AA 112 | 3GZV 100055-1 | 0 | 2004.07.08 | 1 |
| Technical file for ATEX Certification M3AA 132 | 3GZV 100055-2 | 0 | 2004.07.08 | 1 |
| Technical file for ATEX Certification M3AA 160 | 3GZV 100055-3 | 0 | 2004.07.08 | 1 |
| Technical file for ATEX Certification M3AA 180 | 3GZV 100055-4 | 0 | 2004.07.08 | 1 |
| Technical file for ATEX Certification M3AA 200 | 3GZV 100055-5 | 0 | 2004.07.08 | 1 |
| Technical file for ATEX Certification M3AA 225 | 3GZV 100055-6 | 0 | 2004.07.08 | 1 |
| Technical file for ATEX Certification M3AA 250 | 3GZV 100055-7 | 0 | 2004.07.08 | 1 |
| Technical file for ATEX Certification M3AA 280 | 3GZV 100055-8 | 0 | 2004.07.08 | 1 |

- [18] Special Conditions for Safe Use None
- [19] Essential Health and Safety Requirements See item 10





SUPPLEMENT 1 TO EC-TYPE EXAMINATION CERTIFICATE

[15] EC-TYPE EXAMINATION CERTIFICATE No Nemko 04ATEX1448

[16] Description of Equipment or Protective System

This Certificate is extended to include the used of three new Frequency converters, a new alternative Grounding device, and a new IP code.

Frequency Converters

The following frequency converters has been type tested according to the derating curve in the Technical files, and can be used with these motors:

ABB ACS 800

ABB ACS 550

ABB ACS 350

Ingress Protection Code

The use of Protection class **IP 56** or **IP 66** for frame size 112-180 is allowed if the design for IP65 acc. to the assembly drawings 3GZV100056-3GZV100067 is used

For frame size 200-280 **IP65** apply

Grounding

A new alternative External grounding device, size M20 is added.

Type Designation

M2AA112-250 / M3AA112-280

[17] Report No. 67153

Descriptive Documents

| Name/Title | Drawing No. | Rev. | Date | Sheets |
|--|------------------|------|------------|--------|
| Technical Description ATEX M2AA112 – 250 and M3AA112 - 280 | 3GZV100054 | 1 | 2006-05-19 | 11 |
| Grounding Base | 3GZV 334 001-178 | 0 | 06 week 20 | 1 |

[18] Special Conditions for Safe Use

None

[19] Essential Health and Safety Requirements

See item 10

Oslo, 2006-05-23

p.p. Rolf Hoel

Certification Department

This certificate may only be reproduced in its entirety and without any change, schedule included.