CRYPTOGRAPHIC RF SMART CARD ICS

BDTIC www.bdtic.com/Semiconductor

AT88SC0104CRF to AT88SC6416CRF

FAMILY OF CRYPTORF[™] SECURITY CHIPS

The AT88SC0104CRF to AT88SC6416CRF is a family of contactless secure memory devices with advanced security and cryptography.

Key Features

- A Family of Devices with User Memories from 1 Kbit to 64 Kbits: 1K, 2K, 4K, 8K, 16K, 32K, 64K Bits
- Symmetrical Dynamic Mutual Authentication with 64-bit Cryptographic Keys
- Encrypted Passwords with Attempts Counters
- Stream Encryption Ensures Data Privacy
- Antitearing Recovers Data in Case of Power Loss
- Contactless 13.56-MHz Interface, Compliant with ISO/IEC 14443 Type B
- Integrated 82 pF Tuning Capacitor
- High Reliability Memory, 100K Write Cycles with 10 Year Data Retention

Applications

• Health Care Cards

Security Focus ID Cards

- Drivers Licenses
- E-purses
- (Biometric ID Cards, Passports, etc.) Multi-applications





CRYPTORF™ CRYPTOGRAPHIC RF SMART CARD ICS

Atmel Corporation

2325 Orchard Parkway San Jose, CA 95131 TEL 1(408) 441-0311 FAX 1(408) 487-2600

Regional Headquarters

Europe Atmel Sarl Route des Arsenaux 41 Case Postale 80 CH-1705 Fribourg Switzerland TEL (41) 26-426-5555 FAX (41) 26-426-5500

Asia

Room 1219 Chinachem Golden Plaza 77 Mody Road Tsimshatsui East Kowloon Hong Kong TEL (852) 2721-9778 FAX (852) 2722-1369

Japan

9F, Tonetsu Shinkawa Bldg. 1-24-8 Shinkawa Chuo-ku, Tokyo 104-0033 Japan TEL (81) 3-3523-3551 FAX (81) 3-3523-7581

e-mail

literature@atmel.com

Web Site http://www.atmel.com



 Atmel Corporation 2003. All rights reserved. Atmel[®] and combinations thereof are registered trademarks and CryptoRF™ is a trademark of Atmel Corporation or its subsidiaries. Other terms and product names may be the trademarks of others.

5038A-CRRF-04/03/10k

Atmel's CryptoRF[™] is a new secure RF family of devices with memory densities from 1 Kbit (AT88SC0104CRF) to 64 Kbits (AT88SC6416CRF) for contactless smart card applications. This new family of secure RF circuits makes available to the industry a low cost, high security chip solution that fills the void between simple RFID memories and RF microcontrollers.

Security

This device contains a random number generator and proprietary algorithm that generates new keys for each authentication and encryption activation. Read and Write access requirements for each user zone are programmed by the customer during card personalization. The device's secret keys for mutual authentication and encryption are defined using a customer selected algorithm. Only a computer knowing both the CryptoRF and customer algorithms can provide the required authentication codes.

Product Features

- Contactless 13.56 MHz RF Communications
 Interface
 - ISO/IEC 14443-2: 2001 Type B Compliant
 - ISO/IEC 14443-3: 2001 Type B Compliant Anticollision Protocol
 - Command Set Optimized for Multicard RF Communications
 - Tolerant of Type A Signaling for Multiprotocol Applications
 - Operating Distance Up to 10 cm
- Integrated 82 pF Tuning Capacitor
- User Memory of 1 Kbit to 64 Kbit
 - User Memory Configured as 4, 8, or 16
 User Zones
 - Byte, Page, and Partial Page Write Modes
 - Self-timed Write Cycle
- 2 Kbit (256-byte) Configuration Zone
- User-programmable Application Family Identifier (AFI)
 - User-defined Anticollision Polling Response
 - User-defined Keys and Passwords

Package Options



Wafer Form, Thinned to 6 Mils

Development Tools



RF Smart Card Modules



Prelaminate Sheets

AT88SC6416CRF-EK Evaluation Kit, including RF reader and software AT88SC6416CRF-DK Development Kit, including RF reader and software

Atmel contact: cryptorf@atmel.com

- High-Security Features
 - 64-bit Mutual Authentication Protocol (under exclusive patent license from ELVA)
 - Encrypted Checksum
 - Stream Encryption
 - Four Key Sets for Authentication and Encryption
 - Eight Sets of Two 24-bit Passwords
 - Password and Authentication Attempts Counters
 - Selectable Access Rights by Zone
 - Write Lock Mode
 - Antitearing Function
 - Tamper Sensors
- High Reliability
 - Endurance: 100,000 Write Cycles
 - Data Retention: 10 Years
 - Operating Temperature: -40 to +85°C