Data Sheet

ALCE &

rrG.

July 6, 2006

High Speed, Single Channel, Power MOSFET Driver

intersil

The EL7104 is a matched driver IC that improves the operation of the industry-standard TC-4420/29 clock drivers. The Elantec version is a very high speed driver capable of delivering peak currents of 1A into highly capacitive loads. The high speed performance is achieved by means of a proprietary "Turbo-Driver" circuit that speeds up input stages by tapping the wider voltage swing at the output. Improved speed and drive capability are enhanced by matched rise and fall delay times. These matched delays maintain the integrity of input-to-output pulse-widths to reduce timing errors and clock skew problems. This improved performance is accompanied by a 10-fold reduction in supply currents over bipolar drivers, yet without the delay time problems commonly associated with CMOS drivers.

The EL7104 is available in 8-pin SO and 8-pin PDIP packages and is specified for operation over the full -40°C to +85°C temperature range.

Features

- Industry-standard driver replacement
- Improved response times
- Matched rise and fall times
- Reduced clock skew
- Low output impedance
- Low input capacitance
- High noise immunity
- Improved clocking rate
- · Low supply current
- · Wide operating range
- · Separate drain connections
- Pb-Free available (RoHS compliant)

Applications

- Clock/line drivers
- CCD_drivers
- Ultrasound ranscuopedri rers
- Power MOSFET drivers
- Switch mode power supplies
- · Resonant charging
- · Cascoded drivers

Pinout





NUMBER RE EL **D**WG. # PACLAG EL7104CN 8 Ld PDIP MDP0031 EL7104CN 8 Ld PDIP* EL7104CNZ EL7104CN Z MDP0031 -EL7104CS 7104CS 8 Ld SOIC MDP0027 -EL7104CS-T7 7104CS 8 Ld SOIC 7" MDP0027 EL7104CS-T13 7104CS 8 Ld SOIC 13" MDP0027 EL7104CSZ 7104CSZ 8 Ld SOIC MDP0027 (See Note) (Pb-free) EL7104CSZ-T7 8 Ld SOIC 7104CSZ 7" MDP0027 (See Note) (Pb-free) EL7104CSZ-T13 7104CSZ 8 Ld SOIC MDP0027 13" (Pb-free) (See Note)

NOTE: Intersil Pb-free products employ special Pb-free material sets; molding compounds/die attach materials and 100% matte tin plate termination finish, which are RoHS compliant and compatible with both SnPb and Pb-free soldering operations. Intersil Pb-free products are MSL classified at Pb-free peak reflow temperatures that meet or exceed the Pb-free requirements of IPC/JEDEC J STD-020.

*Pb-free PDIPs can be used for through hole wave solder processing only. They are not intended for use in Reflow solder processing applications.

Ordering Information

PART

Absolute Maximum Ratings (T_A = 25°C)

Supply (V+ to GND)	16.5V
Input Pins0.3V to +0.3V abo	ve V+
Peak Output Current	4A
Ambient Operating Temperature40°C to -	+85°C

Storage Temperature Range	65°C to +150°C
Operating Junction Temperature	+125°C
Power Dissipation	
SO	570mW
PDIP	

CAUTION: Stresses above those listed in "Absolute Maximum Ratings" may cause permanent damage to the device. This is a stress only rating and operation of the device at these or any other conditions above those indicated in the operational sections of this specification is not implied.

IMPORTANT NOTE: All parameters having Min/Max specifications are guaranteed. Typ values are for information purposes only. Unless otherwise noted, all tests are at the specified temperature and are pulsed tests, therefore: $T_J = T_C = T_A$

DC Electrical Specifications V+ = 15V, $T_A = 25^{\circ}C$ unless otherwise specified.

PARAMETER	DESCRIPTION	CONDITIONS	MIN	TYP	MAX	UNIT		
INPUT								
V _{IH}	Logic "1" Input Voltage		2.4			V		
I _Н	Logic "1" Input Current	@V+		0.1	10	μA		
V _{IL}	Logic "0" Input Voltage				0.8	V		
IIL	Logic "0" Input Current	@0V		0.1	10	μA		
V _{HVS}	Input Hysteresis			0.3		V		
OUTPUT								
R _{OH}	Pull-Up Resistance	I _{OUT} = -100mA		1.5	4	Ω		
R _{OL}	Pull-Down Resistance	I _{OUT} = +100mA		2	4	Ω		
IOUT	Output Leakage Current	V+/GND		0.2	10	μA		
I _{PK}	PrakiQuitu Curren	Source/pink m / n t a	rc	4.0		А		
I _{DC}	Continuous Output Current	Source/Smk	200			mA		
POWER SUPPLY								
I _S	Power Supply Current	Input = V+		4.5	7.5	mA		
VS	Operating Voltage		4.5		16	V		

AC Electrical Specifications V = 15V, $T_A = 25^{\circ}C$ unless otherwise specified.

PARAMETER	DESCRIPTION	CONDITIONS	TYP	MAX	UNIT			
SWITCHING CHARACTERISTICS ($V_{DD} = V_H = 12V$; $V_L = -3V$)								
t _R	Rise Time	C _L = 1000pF		7.5		ns		
		C _L = 2000pF		10	20	ns		
t _F	Fall Time	C _L = 1000pF		10		ns		
		C _L = 2000pF		15	20	ns		
t _{D-ON}	Turn-On Delay Time	See Timing Table		18	25	ns		
^t D-OFF	Turn-Off Delay Time	See Timing Table		18	25	ns		

Timing Table



Standard Test Configuration



Simplified Schematic



Typical Performance Curves

MAX POWER/DERATING CURVES

SWITCH THRESHOLD vs SUPPLY VOLTAGE





PEAK DRIVE vs SUPPLY VOLTAGE



QUIESCENT SUPPLY CURRENT

"ON" RESISTANCE vs SUPPLY VOLTAGE



Typical Performance Curves (Continued)





RISE/FALL TIME vs SUPPLY VOLTAGE











FALL TIME VS SUPPLY VOLTAG









MDP0027

SMALL OUTLINE PACKAGE FAMILY (SO)

SYMBOL	sor	\$ D-14	Sc 16 (0.1 j0")	SO 16 (0.300") SOL-16)	SO20 (St)2()	: O24 (S)L-24]	SO28 (SCL-28)		NOTES
A	0.068	0.068	0.068	0.104	0.104	0.104	0.104	MAX	-
A1	0.006	0.006	0.006	0.007	0.007	0.007	0.007	±0.003	-
A2	0.057	0.057	0.057	0.092	0.092	0.092	0.092	±0.002	-
b	0.017	0.017	0.017	0.017	0.017	0.017	0.017	±0.003	-
с	0.009	0.009	0.009	0.011	0.011	0.011	0.011	±0.001	-
D	0.193	0.341	0.390	0.406	0.504	0.606	0.704	±0.004	1, 3
E	0.236	0.236	0.236	0.406	0.406	0.406	0.406	±0.008	-
E1	0.154	0.154	0.154	0.295	0.295	0.295	0.295	±0.004	2, 3
е	0.050	0.050	0.050	0.050	0.050	0.050	0.050	Basic	-
L	0.025	0.025	0.025	0.030	0.030	0.030	0.030	±0.009	-
L1	0.041	0.041	0.041	0.056	0.056	0.056	0.056	Basic	-
h	0.013	0.013	0.013	0.020	0.020	0.020	0.020	Reference	-
N	8	14	16	16	20	24	28	Reference	-
<u>.</u>									Rev. L 2/01

NOTES:

1. Plastic or metal protrusions of 0.006" maximum per side are not included.

2. Plastic interlead protrusions of 0.010" maximum per side are not included.

3. Dimensions "D" and "E1" are measured at Datum Plane "H".

6

4. Dimensioning and tolerancing per ASME Y14.5M-1994

Plastic Dual-In-Line Packages (PDIP)



MDP0031 PLASTIC DUAL-IN-LINE PACKAGE

SYMBOL	PDIP8	PDIP14	PDIP16	PDIP18	PDIP20	TOLERANCE	NOTES
A	0.210	0.210	0.210	0.210	0.210	MAX	
A1	0.015	0.015	0.015	0.015	0.015	MIN	
A2	0.130	0.130	0.130	0.130	0.130	±0.005	
b	0.018	0.018	0.018	0.018	0.018	±0.002	
b2	0.060	0.060	0.060	0.060	0.060	+0.010/-0.015	
с	0.010	0.010	0.010	0.010	0.010	+0.004/-0.002	
D	0.375	0.750	0.750	0.890	1.020	±0.010	1
E	0.310	0.310	0.310	0.310	0.310	+0.015/-0.010	
E1	0.250	0.250	0.250	0.250	0.250	±0.005	2
е	0.100	0.100	0.100	0.100	0.100	Basic	
eA	0.300	D).300	0.300	0.300	0.300	Basic	
eB	VV 0346V	0.345	0 345	0.345	0.345	±0.025	
L	0.125	0.125	0.125	0.125	0.125	±0.010	
N	8	14	16	18	20	Reference	

NOTES:

Plastic or metal protrusions of 0.010" maximum per side are not included.

2. Plastic interlead protrusions of 0.010" maximum per side are not included.

3. Dimensions E and eA are measured with the leads constrained perpendicular to the seating plane.

4. Dimension eB is measured with the lead tips unconstrained.

5. 8 and 16 lead packages have half end-leads as shown.

All Intersil U.S. products are manufactured, assembled and tested utilizing ISO9000 quality systems. Intersil Corporation's quality certifications can be viewed at www.intersil.com/design/quality

Intersil products are sold by description only. Intersil Corporation reserves the right to make changes in circuit design, software and/or specifications at any time without notice. Accordingly, the reader is cautioned to verify that data sheets are current before placing orders. Information furnished by Intersil is believed to be accurate and reliable. However, no responsibility is assumed by Intersil or its subsidiaries for its use; nor for any infringements of patents or other rights of third parties which may result from its use. No license is granted by implication or otherwise under any patent or patent rights of Intersil or its subsidiaries.

For information regarding Intersil Corporation and its products, see www.intersil.com



Rev. B 2/99