

## Dual and Quad, 8MHz, Low Noise Operational Amplifiers

Low noise and high performance are key words describing HA-5102 and HA-5104. These general purpose amplifiers offer an array of dynamic specifications including a  $3\text{V}/\mu\text{s}$  slew rate and 8MHz bandwidth. Complementing these outstanding parameters is a very low noise specification of  $4.3\text{nV}/\sqrt{\text{Hz}}$  at 1kHz.

Fabricated using the Intersil high frequency DI process, these operational amplifiers also offer excellent input specifications such as a 0.5mV offset voltage and 30nA offset current. Complementing these specifications are 108dB open loop gain and 60dB channel separation. Consuming a very modest amount of power (90mW/package for duals and 150mW/package for quads), HA-5102/04 also provide 15mA of output current.

This impressive combination of features make this series of amplifiers ideally suited for designs ranging from audio amplifiers and active filters to the most demanding signal conditioning and instrumentation circuits.

These operational amplifiers are available in dual or quad form with industry standard pinouts allowing for immediate interchangeability with most other dual and quad operational amplifiers.

HA-5102 Dual, Comp. HA-5104 Quad, Comp.

Refer to the /883 data sheet for military product.

## Ordering Information

| PART NUMBER | TEMP. RANGE (°C) | PACKAGE      | PKG. DWG. # |
|-------------|------------------|--------------|-------------|
| HA7-5102-2  | -55 to 125       | 8 Ld Cerdip  | F8.3A       |
| HA1-5104-2  | -55 to 125       | 14 Ld Cerdip | F14.3       |
| HA9P5104-9  | -40 to 85        | 16 Ld SOIC   | M16.3       |

## Features


- Low Noise .....  $4.3\text{nV}/\sqrt{\text{Hz}}$
- Bandwidth ..... 8MHz (Compensated)
- Slew Rate .....  $3\text{V}/\mu\text{s}$  (Compensated)
- Low Offset Voltage ..... 0.5mV
- Available in Duals or Quads

## Applications


- High Q, Active Filters
- Audio Amplifiers
- Instrumentation Amplifiers
- Integrators
- Signal Generators
- For Further Design Ideas, See Application Note AN554

## Pinouts


**HA-5102 (CERDIP)**  
TOP VIEW



**HA-5104 (CERDIP)**  
TOP VIEW



**HA5104 (SOIC)**  
TOP VIEW



## Absolute Maximum Ratings

Supply Voltage Between V+ and V- Terminals. . . . . 40V  
 Differential Input Voltage . . . . . 7V  
 Input Voltage . . . . .  $\pm V_{\text{SUPPLY}}$   
 Output Short Circuit Duration (Note 3). . . . . Indefinite

## Operating Conditions

Temperature Range  
 HA-510X-2 . . . . . -55°C to 125°C  
 HA-5104-9 . . . . . -40°C to 85°C

## Thermal Information

Thermal Resistance (Typical, Note 2)  $\theta_{JA}$  (°C/W)  $\theta_{JC}$  (°C/W)  
 8 Lead Cerdip Package. . . . . 115 28  
 14 Lead Cerdip Package. . . . . 75 20  
 SOIC Package . . . . . 100 N/A  
 Maximum Junction Temperature (Note 1, Hermetic Package) . . 175°C  
 Maximum Junction Temperature (Plastic Package) . . . . . 150°C  
 Maximum Storage Temperature Range. . . . . -65°C to 150°C  
 Maximum Lead Temperature (Soldering 10s) . . . . . 300°C  
 (SOIC - Lead Tips Only)

**CAUTION:** Stresses above those listed in "Absolute Maximum Ratings" may cause permanent damage to the device. This is a stress only rating and operation of the device at these or any other conditions above those indicated in the operational sections of this specification is not implied.

### NOTES:

1. Maximum power dissipation, including output load, must be designed to maintain the maximum junction temperature below 175°C for hermetic packages, and below 150°C for plastic packages.
2.  $\theta_{JA}$  is measured with the component mounted on a low effective thermal conductivity test board in free air. See Tech Brief TB379 for details.
3. Any one amplifier may be shorted to ground indefinitely.

## Electrical Specifications $V_{\text{SUPPLY}} = \pm 15V$ , Unless Otherwise Specified

| PARAMETER                                                                    | TEMP.<br>(°C)          | HA-5102-2 |     |     | HA-5104-2 |     |     | HA-5104-9 |     |     | UNITS |
|------------------------------------------------------------------------------|------------------------|-----------|-----|-----|-----------|-----|-----|-----------|-----|-----|-------|
|                                                                              |                        | MIN       | TYP | MAX | MIN       | TYP | MAX | MIN       | TYP | MAX |       |
| INPUT CHARACTERISTICS                                                        |                        |           |     |     |           |     |     |           |     |     |       |
| Offset Voltage                                                               | 25                     | -         | 0.5 | 2.0 | -         | 0.5 | 2.5 | -         | 0.5 | 2.5 | mV    |
|                                                                              | Full                   | -         | -   | 2.5 | -         | -   | 3.0 | -         | -   | 3.0 | mV    |
| Offset Voltage Average Drift                                                 | Full                   | -         | 3   | -   | -         | 3   | -   | -         | 3   | -   | μV/°C |
| Bias Current                                                                 | 25                     | -         | 110 | 200 | -         | 130 | 200 | -         | 130 | 200 | nA    |
|                                                                              | Full                   | -         | -   | 325 | -         | -   | 325 | -         | -   | 500 | nA    |
| Offset Current                                                               | 25                     | -         | 30  | 75  | -         | 30  | 75  | -         | 30  | 75  | nA    |
|                                                                              | Full                   | -         | -   | 125 | -         | -   | 125 | -         | -   | 125 | nA    |
| Input Resistance                                                             | 25                     | -         | 500 | -   | -         | 500 | -   | -         | 500 | -   | kΩ    |
| Common Mode Range                                                            | Full                   | ±12       | -   | -   | ±12       | -   | -   | ±12       | -   | -   | V     |
| TRANSFER CHARACTERISTICS                                                     |                        |           |     |     |           |     |     |           |     |     |       |
| Large Signal Voltage Gain,<br>(V <sub>OUT</sub> = ±5V, R <sub>L</sub> = 2kΩ) | 25                     | 100       | 250 | -   | 100       | 250 | -   | 80        | 250 | -   | kV/V  |
|                                                                              | Full                   | 100       | -   | -   | 100       | -   | -   | 80        | -   | -   | kV/V  |
| Common Mode Rejection Ratio (V <sub>CM</sub> = ±5.0V)                        | Full                   | 86        | 95  | -   | 86        | 95  | -   | 80        | 95  | -   | dB    |
| Small Signal Bandwidth, (A <sub>V</sub> = 1)                                 | 25                     | -         | 8   | -   | -         | 8   | -   | -         | 8   | -   | MHz   |
| Channel Separation (Note 4)                                                  | 25                     | -         | 60  | -   | -         | 60  | -   | -         | 60  | -   | dB    |
| OUTPUT CHARACTERISTICS                                                       |                        |           |     |     |           |     |     |           |     |     |       |
| Output Voltage Swing<br>(R <sub>L</sub> = 10kΩ)                              | Full                   | ±12       | ±13 | -   | ±12       | ±13 | -   | ±12       | ±13 | -   | V     |
|                                                                              | (R <sub>L</sub> = 2kΩ) | Full      | ±10 | ±12 | -         | ±10 | ±12 | -         | ±10 | ±12 | -     |
| Output Current, (V <sub>OUT</sub> = ±5V)                                     | Full                   | ±10       | ±15 | -   | ±10       | ±15 | -   | ±7        | ±15 | -   | mA    |
| Full Power Bandwidth (Note 5)                                                | 25                     | 16        | 47  | -   | 16        | 47  | -   | 16        | 47  | -   | kHz   |
| Output Resistance                                                            | 25                     | -         | 110 | -   | -         | 110 | -   | -         | 110 | -   | Ω     |
| STABILITY                                                                    |                        |           |     |     |           |     |     |           |     |     |       |
| Minimum Stable Closed Loop Gain                                              | Full                   | 1         | -   | -   | 1         | -   | -   | 1         | -   | -   | V/V   |
| TRANSIENT RESPONSE (Note 6)                                                  |                        |           |     |     |           |     |     |           |     |     |       |

# HA-5102, HA-5104

## Electrical Specifications $V_{SUPPLY} = \pm 15V$ , Unless Otherwise Specified (Continued)



| PARAMETER                                             | TEMP.<br>(°C)   | HA-5102-2 |     |      | HA-5104-2 |     |      | HA-5104-9 |     |      | UNITS |                   |
|-------------------------------------------------------|-----------------|-----------|-----|------|-----------|-----|------|-----------|-----|------|-------|-------------------|
|                                                       |                 | MIN       | TYP | MAX  | MIN       | TYP | MAX  | MIN       | TYP | MAX  |       |                   |
| Rise Time                                             | 25              | -         | 108 | 200  | -         | 108 | 200  | -         | 108 | 200  | ns    |                   |
| Overshoot                                             | 25              | -         | 20  | 35   | -         | 20  | 35   | -         | 20  | 35   | %     |                   |
| Slew Rate                                             | 25              | 1         | 3   | -    | 1         | 3   | -    | 1         | 3   | -    | V/μs  |                   |
| Settling Time (Note 7)                                | 25              | -         | 4.5 | -    | -         | 4.5 | -    | -         | 4.5 | -    | μs    |                   |
| NOISE CHARACTERISTICS (Note 8)                        |                 |           |     |      |           |     |      |           |     |      |       |                   |
| Input Noise Voltage                                   | f = 10Hz        | 25        | -   | 9    | 25        | -   | 9    | 25        | -   | 9    | 25    | nV/√Hz            |
|                                                       | f = 1kHz        | 25        | -   | 4.3  | 6.0       | -   | 4.3  | 6.0       | -   | 4.3  | 6.0   | nV/√Hz            |
| Input Noise Current                                   | f = 10Hz        | 25        | -   | 5.1  | 15        | -   | 5.1  | 15        | -   | 5.1  | 15    | pA/√Hz            |
|                                                       | f = 1kHz        | 25        | -   | 0.57 | 3         | -   | 0.57 | 3         | -   | 0.57 | 3     | pA/√Hz            |
| Broadband Noise Voltage                               | f = DC to 30kHz | 25        | -   | 870  | -         | -   | 870  | -         | -   | 870  | -     | nV <sub>RMS</sub> |
| POWER SUPPLY CHARACTERISTICS                          |                 |           |     |      |           |     |      |           |     |      |       |                   |
| Supply Current (All Amps)                             | 25              | -         | 3.0 | 5.0  | -         | 5.0 | 6.5  | -         | 5.0 | 6.5  | mA    |                   |
| Power Supply Rejection Ratio, (ΔV <sub>S</sub> = ±5V) | Full            | 86        | 100 | -    | 86        | 100 | -    | 80        | 100 | -    | dB    |                   |

### NOTES:

- Channel separation value is referred to the input of the amplifier. Input test conditions are: f = 10kHz;  $V_{IN} = 100mV_{PEAK}$ ;  $R_S = 1k\Omega$ .
- Full power bandwidth is guaranteed by equation: Full power bandwidth =  $\frac{Slew\ Rate}{2\pi V_{PEAK}}$ .
- Refer to Test Circuits section of the data sheet.
- Settling time is measured to 0.1% of final value for a 10V input step,  $A_V = -1$ .
- The limits for these parameters are guaranteed based on lab characterization, and reflect lot-to-lot variation.



www.BDTIC.com/Intersil

## Test Circuits and Waveforms




Vertical = 5V/Div., Horizontal = 5μs/Div. ( $A_V = -1$ )

FIGURE 1. LARGE SIGNAL RESPONSE CIRCUIT



Vertical = 40mV/Div., Horizontal = 50ns/Div. ( $A_V = +1$ )

FIGURE 2. SMALL SIGNAL RESPONSE CIRCUIT




### NOTES:

9.  $A_V = -1$ .
10. Feedback and summing resistors should be 0.1% matched.
11. Clipping diodes are optional, HP5082-2810 recommended.

FIGURE 3. SETTLING TIME CIRCUIT

## Simplified Schematic



## Typical Performance Curves




FIGURE 4. INPUT NOISE VOLTAGE DENSITY






FIGURE 5. INPUT NOISE CURRENT DENSITY

## Typical Performance Curves (Continued)







$V_S = \pm 15V$ ,  $T_A = 25^\circ C$ ,  $50\mu V/Div.$ ,  $1s/Div.$ ,  $A_V = 1000V/V$   
Input Noise =  $0.232\mu V_{P-P}$

FIGURE 6. 0.1Hz TO 10Hz NOISE



$V_S = \pm 15V$ ,  $T_A = 25^\circ C$ ,  $500\mu V/Div.$ ,  $1s/Div.$ ,  $A_V = 1000V/V$   
Total Output Noise =  $2.075\mu V_{P-P}$

FIGURE 7. 0.1Hz TO 1MHz NOISE

FIGURE 8.  $V_{IO}$  vs TEMPERATUREFIGURE 9.  $V_{IO}$  vs  $V_S$ FIGURE 10.  $I_{IO}$  vs TEMPERATUREFIGURE 11.  $I_{BIAS}$  vs TEMPERATURE

Typical Performance Curves (Continued)




FIGURE 12.  $I_{CC}$  vs TEMPERATURE (HA-5104)




FIGURE 13.  $I_{CC}$  vs  $V_S$  (HA-5102)




FIGURE 14.  $A_{VOL}$  vs TEMPERATURE




FIGURE 15.  $A_{VOL}$  vs LOAD RESISTANCE




FIGURE 16.  $A_{VOL}$  vs  $V_S$




FIGURE 17.  $V_{OUT}$  vs  $V_S$

## Typical Performance Curves (Continued)




FIGURE 18. OUTPUT SHORT CIRCUIT CURRENT vs TIME




FIGURE 19. CMRR vs FREQUENCY




FIGURE 20. PSRR vs FREQUENCY




FIGURE 21. UNITY GAIN FREQUENCY RESPONSE





FIGURE 22. OPEN LOOP GAIN vs FREQUENCY

FIGURE 23. SMALL SIGNAL OVERSHOOT vs  $C_{LOAD}$

## Typical Performance Curves (Continued)




FIGURE 24. SLEW RATE vs TEMPERATURE




FIGURE 25. RISE TIME vs TEMPERATURE

## Die Characteristics

### DIE DIMENSIONS:

98.4 mils x 67.3 mils x 19 mils  
2500μm x 1710μm x 483μm

### METALLIZATION:

Type: Al, 1% Cu  
Thickness: 16kÅ ±2kÅ

### PASSIVATION:

Type: Nitride (Si<sub>3</sub>N<sub>4</sub>) over Silox (SiO<sub>2</sub>, 5% Phos.)  
Silox Thickness: 12kÅ ±2kÅ  
Nitride Thickness: 3.5kÅ ±1.5kÅ

### SUBSTRATE POTENTIAL (POWERED UP):

Unbiased


### TRANSISTOR COUNT:

93

### PROCESS:

Bipolar Dielectric Isolation

## Metallization Mask Layout



## Die Characteristics

### DIE DIMENSIONS:

95 mils x 99 mils x 19 mils  
2420 $\mu$ m x 2530 $\mu$ m x 483 $\mu$ m

### METALLIZATION:

Type: Al, 1% Cu  
Thickness: 16k $\text{\AA}$   $\pm$  2k $\text{\AA}$

### PASSIVATION:

Type: Nitride ( $\text{Si}_3\text{N}_4$ ) over Silox ( $\text{SiO}_2$ , 5% Phos.)  
Silox Thickness: 12k $\text{\AA}$   $\pm$  2k $\text{\AA}$   
Nitride Thickness: 3.5k $\text{\AA}$   $\pm$  1.5k $\text{\AA}$

### SUBSTRATE POTENTIAL (POWERED UP):

Unbiased


### TRANSISTOR COUNT:

175


### PROCESS:

Bipolar Dielectric Isolation

## Metallization Mask Layout



## Ceramic Dual-In-Line Frit Seal Packages (CERDIP)



## NOTES:


1. Index area: A notch or a pin one identification mark shall be located adjacent to pin one and shall be located within the shaded area shown. The manufacturer's identification shall not be used as a pin one identification mark.
2. The maximum limits of lead dimensions b and c or M shall be measured at the centroid of the finished lead surfaces, when solder dip or tin plate lead finish is applied.
3. Dimensions b1 and c1 apply to lead base metal only. Dimension M applies to lead plating and finish thickness.
4. Corner leads (1, N, N/2, and N/2+1) may be configured with a partial lead paddle. For this configuration dimension b3 replaces dimension b2.
5. This dimension allows for off-center lid, meniscus, and glass overrun.
6. Dimension Q shall be measured from the seating plane to the base plane.
7. Measure dimension S1 at all four corners.
8. N is the maximum number of terminal positions.
9. Dimensioning and tolerancing per ANSI Y14.5M - 1982.
10. Controlling dimension: INCH

F8.3A MIL-STD-1835 GDIP1-T8 (D-4, CONFIGURATION A)  
8 LEAD CERAMIC DUAL-IN-LINE FRIT SEAL PACKAGE

| SYMBOL   | INCHES    |        | MILLIMETERS |       | NOTES |
|----------|-----------|--------|-------------|-------|-------|
|          | MIN       | MAX    | MIN         | MAX   |       |
| A        | -         | 0.200  | -           | 5.08  | -     |
| b        | 0.014     | 0.026  | 0.36        | 0.66  | 2     |
| b1       | 0.014     | 0.023  | 0.36        | 0.58  | 3     |
| b2       | 0.045     | 0.065  | 1.14        | 1.65  | -     |
| b3       | 0.023     | 0.045  | 0.58        | 1.14  | 4     |
| c        | 0.008     | 0.018  | 0.20        | 0.46  | 2     |
| c1       | 0.008     | 0.015  | 0.20        | 0.38  | 3     |
| D        | -         | 0.405  | -           | 10.29 | 5     |
| E        | 0.220     | 0.310  | 5.59        | 7.87  | 5     |
| e        | 0.100 BSC |        | 2.54 BSC    |       | -     |
| eA       | 0.300 BSC |        | 7.62 BSC    |       | -     |
| eA/2     | 0.150 BSC |        | 3.81 BSC    |       | -     |
| L        | 0.125     | 0.200  | 3.18        | 5.08  | -     |
| Q        | 0.015     | 0.060  | 0.38        | 1.52  | 6     |
| S1       | 0.005     | -      | 0.13        | -     | 7     |
| $\alpha$ | 90°       | 105°   | 90°         | 105°  | -     |
| aaa      | -         | 0.015  | -           | 0.38  | -     |
| bbb      | -         | 0.030  | -           | 0.76  | -     |
| ccc      | -         | 0.010  | -           | 0.25  | -     |
| M        | -         | 0.0015 | -           | 0.038 | 2, 3  |
| N        | 8         |        | 8           |       | 8     |

Rev. 0 4/94

## Ceramic Dual-In-Line Frit Seal Packages (CERDIP)



## NOTES:


1. Index area: A notch or a pin one identification mark shall be located adjacent to pin one and shall be located within the shaded area shown. The manufacturer's identification shall not be used as a pin one identification mark.
2. The maximum limits of lead dimensions b and c or M shall be measured at the centroid of the finished lead surfaces, when solder dip or tin plate lead finish is applied.
3. Dimensions b1 and c1 apply to lead base metal only. Dimension M applies to lead plating and finish thickness.
4. Corner leads (1/N, 1/2, and N/2+1) may be configured with a partial lead paddle. For this configuration dimension b3 replaces dimension b2.
5. This dimension allows for off-center lid, meniscus, and glass overrun.
6. Dimension Q shall be measured from the seating plane to the base plane.
7. Measure dimension S1 at all four corners.
8. N is the maximum number of terminal positions.
9. Dimensioning and tolerancing per ANSI Y14.5M - 1982.
10. Controlling dimension: INCH.

F14.3 MIL-STD-1835 GDIP1-T14 (D-1, CONFIGURATION A)  
14 LEAD CERAMIC DUAL-IN-LINE FRIT SEAL PACKAGE

| SYMBOL   | INCHES    |        | MILLIMETERS |       | NOTES |
|----------|-----------|--------|-------------|-------|-------|
|          | MIN       | MAX    | MIN         | MAX   |       |
| A        | -         | 0.200  | -           | 5.08  | -     |
| b        | 0.014     | 0.026  | 0.36        | 0.66  | 2     |
| b1       | 0.014     | 0.023  | 0.36        | 0.58  | 3     |
| b2       | 0.045     | 0.065  | 1.14        | 1.65  | -     |
| b3       | 0.023     | 0.045  | 0.58        | 1.14  | 4     |
| c        | 0.008     | 0.018  | 0.20        | 0.46  | 2     |
| c1       | 0.008     | 0.015  | 0.20        | 0.38  | 3     |
| D        | -         | 0.785  | -           | 19.94 | 5     |
| E        | 0.220     | 0.310  | 5.59        | 7.87  | 5     |
| e        | 0.100 BSC |        | 2.54 BSC    |       | -     |
| eA       | 0.300 BSC |        | 7.62 BSC    |       | -     |
| eA/2     | 0.150 BSC |        | 3.81 BSC    |       | -     |
| L        | 0.125     | 0.200  | 3.18        | 5.08  | -     |
| Q        | 0.015     | 0.060  | 0.38        | 1.52  | 6     |
| S1       | 0.005     | -      | 0.13        | -     | 7     |
| $\alpha$ | 90°       | 105°   | 90°         | 105°  | -     |
| aaa      | -         | 0.015  | -           | 0.38  | -     |
| bbb      | -         | 0.030  | -           | 0.76  | -     |
| ccc      | -         | 0.010  | -           | 0.25  | -     |
| M        | -         | 0.0015 | -           | 0.038 | 2, 3  |
| N        | 14        |        | 14          |       | 8     |

Rev. 0 4/94

## Small Outline Plastic Packages (SOIC)



## NOTES:

1. Symbols are defined in the "MO Series Symbol List" in Section 2.2 of Publication Number 95.
2. Dimensioning and tolerancing per ANSI Y14.5M-1982.
3. Dimension "D" does not include mold flash, protrusions or gate burrs. Mold flash, protrusion and gate burrs shall not exceed 0.15mm (0.006 inch) per side.
4. Dimension "E" does not include interlead flash or protrusions. Interlead flash and protrusions shall not exceed 0.25mm (0.010 inch) per side.
5. The chamfer on the body is optional. If it is not present a visual index feature must be located within the crosshatched area.
6. "L" is the length of terminal for soldering to a substrate.
7. "N" is the number of terminal positions.
8. Terminal numbers are shown for reference only.
9. The lead width "B", as measured 0.36mm (0.014 inch) or greater above the seating plane, shall not exceed a maximum value of 0.61mm (0.024 inch)
10. Controlling dimension: MILLIMETER. Converted inch dimensions are not necessarily exact.

## M16.3 (JEDEC MS-013-AA ISSUE C)

## 16 LEAD WIDE BODY SMALL OUTLINE PLASTIC PACKAGE

| SYMBOL   | INCHES    |        | MILLIMETERS |       | NOTES |
|----------|-----------|--------|-------------|-------|-------|
|          | MIN       | MAX    | MIN         | MAX   |       |
| A        | 0.0926    | 0.1043 | 2.35        | 2.65  | -     |
| A1       | 0.0040    | 0.0118 | 0.10        | 0.30  | -     |
| B        | 0.013     | 0.0200 | 0.33        | 0.51  | 9     |
| C        | 0.0091    | 0.0125 | 0.23        | 0.32  | -     |
| D        | 0.3977    | 0.4133 | 10.10       | 10.50 | 3     |
| E        | 0.2914    | 0.2992 | 7.40        | 7.60  | 4     |
| e        | 0.050 BSC |        | 1.27 BSC    |       | -     |
| H        | 0.394     | 0.419  | 10.00       | 10.65 | -     |
| h        | 0.010     | 0.029  | 0.25        | 0.75  | 5     |
| L        | 0.016     | 0.050  | 0.40        | 1.27  | 6     |
| N        | 16        |        | 16          |       | 7     |
| $\alpha$ | 0°        | 8°     | 0°          | 8°    | -     |

Rev. 0 12/93

All Intersil U.S. products are manufactured, assembled and tested utilizing ISO9000 quality systems.

Intersil Corporation's quality certifications can be viewed at [www.intersil.com/design/quality](http://www.intersil.com/design/quality)

Intersil products are sold by description only. Intersil Corporation reserves the right to make changes in circuit design, software and/or specifications at any time without notice. Accordingly, the reader is cautioned to verify that data sheets are current before placing orders. Information furnished by Intersil is believed to be accurate and reliable. However, no responsibility is assumed by Intersil or its subsidiaries for its use; nor for any infringements of patents or other rights of third parties which may result from its use. No license is granted by implication or otherwise under any patent or patent rights of Intersil or its subsidiaries.

For information regarding Intersil Corporation and its products, see [www.intersil.com](http://www.intersil.com)