

Data Sheet

#### December 20, 2006

## FN6382.0

# 55V, 1A Peak Current H-Bridge FET Driver

intercil

The ISL83202 is a medium-frequency H-Bridge FET driver capable of 1A (typ) of peak drive current that is designed to drive high- and low-side N-Channel MOSFETs in mediumvoltage applications. Optimized for PWM motor control and uninterruptible power supply systems, the ISL83202 enables simple and flexible bridge-based design. With typical inputto-output propagation delays as low as 25ns and with a userprogrammable dead-time range of 0.1µs to 4.5µs, the ISL83202 is ideal for switching frequencies up to 200kHz.

The dead-time of the ISL83202 is programmable via a single resistor. The ISL83202's four independent driver control inputs (ALI, AHI, BLI, and BHI) allow driving of every possible switch combination except those that would cause a shoot-through condition. A global disable input, DIS, overrides input control and causes the ISL83202 to refresh the bootstrap capacitor when pulled low. Integrated undervoltage protection and shoot-through protection ensure reliable system operation.

The ISL83202 is available in compact 16 Ld SOIC and 16 Ld PDIP packages and operates over the range of -55°C to +125°C.

### Features

- Independently Drives 4 N-Channel FETs in Half Bridge or Full Bridge Configurations
- Bootstrap Supply Max Voltage: 70VDC
- Drives a 1000pF Load in Free Air at +50°C with Rise and Fall Times of 15ns (typ)
- User-Programmable Dead Time from 0.1 to 4.5μs
- DIS (Disable) Overrides Input Control and Refreshes Bootstrap Capacitor when Pulled Low
- Input Logic Thresholds Compatible with 5V to 15V Logic Levels
- Shoot-Through Protection
- Undervoltage Protection
- Pb-Free Plus Anneal Available (RoHS Compliant)

## Applications

- · UPS Systems
- · DC Motor Controls

# Ordering Information

PART NUMBER	PART MARKING	TEMP. RANGE (°C)	PACKAGE	PKG. DWG. #		
ISL83202IBZ (Note)	83202IBZ	-55 to +125	16 Ld SOIC (N) (Pb-free)	M16.15		
ISL83202IBZT 16 Ld SOIC (N) Tape and Reel (Note) (Pb-free)						
ISL83202IPZ (Note)	ISL83202IPZ	-55 to +125	16 Ld PDIP** (Pb-free)	E16.3		

NOTE: Intersil Pb-free plus anneal products employ special Pb-free material sets; molding compounds/die attach materials and 100% matte tin plate termination finish, which are RoHS compliant and compatible with both SnPb and Pb-free soldering operations. Intersil Pb-free products are MSL classified at Pb-free peak reflow temperatures that meet or exceed the Pb-free requirements of IPC/ JEDEC J STD-020.

\*\*Pb-free PDIPs can be used for through hole wave solder processing only. They are not intended for use in Reflow solder processing applications.

- Noise Cancellation Systems
- · Battery Powered Vehicles
- Peripherals
- Medium/Large Voice Coil Motors

- Related Literature
  - TB363, Guidelines for Handling and Processing Moisture Sensitive Surface Mount Devices (SMDs)

#### Pinout

	ISL83202 (PDIP, SOIC) TOP VIEW		
внв 1		16	вно
BHI 2		15	внѕ
BLI 3		14	BLO
ALI 4		13	ALO
DEL 5		12	V <sub>DD</sub>
V <sub>SS</sub> 6		11	AHS
AHI 7		10	ано
DIS 8		9	АНВ

# Application Block Diagram



Functional Block Diagram





Typical Application (PWM Mode Switching)

#### **Absolute Maximum Ratings**

Supply Voltage, V <sub>DD</sub> 0.3V to 16V
Logic I/O Voltages
Voltage on AHS, BHS6V (Transient) to 65V (-55°C to+150°C)
Voltage on AHB, BHB $V_{AHS, BHS}$ -0.3V to $V_{AHS, BHS}$ + $V_{DD}$
Voltage on ALO, BLO V <sub>SS</sub> -0.3V to V <sub>DD</sub> +0.3V
Voltage on AHO, BHO V <sub>AHS, BHS</sub> -0.3V to V <sub>AHB, BHB</sub> +0.3V Input
Current, DEL5mA to 0mA
Phase Slew Rate 20V/ns
NOTE: All voltages are relative V <sub>SS</sub> unless otherwise specified.

## **Operating Conditions**

Supply Voltage, V <sub>DD</sub> +8	.5V to +15V
Voltage on V <sub>SS</sub> 1.	0V to +1.0V
Voltage on AHB, BHB	-1V to +55V
Voltage on AHB, BHBVAHS, BHS +7.5V to VAH	IS, BHS +VDD
Input Current, DEL4m	A to -100µA

### **Thermal Information**

processing applications.

Thermal Resistance	θ <sub>JA</sub> (°C/W)
SOIC Package	115
PDIP Package*	90
Maximum Power Dissipation.	. See Curve
Storage Temperature Range65°	C to +150°C
Operating Max. Junction Temperature	+150°C
Lead Temperature (Soldering 10s)	+300°C
(For SOIC - Lead Tips Only))	
*Pb-free PDIPs can be used for through hole w	vave solder
processing only. They are not intended for use in Re	eflow solder

CAUTION: Stresses above those listed in "Absolute Maximum Ratings" may cause permanent damage to the device. This is a stress only rating and operation of the device at these or any other conditions above those indicated in the operational sections of this specification is not implied.

+150°C max junction temperature is intended for short periods of time to prevent shortening the lifetime. Operation close to +150°C junction may trigger the shutdown of the device even before +150°C, since this number is specified as typical.

			T <sub>J</sub> = +25°C			T <sub>J</sub> = -55°C TO +150°C		
PARAMETER	SYMBOL	TEST CONDITIONS	MIN	TYP	MAX	MIN	MAX	UNITS
SUPPLY CURRENTS AND UNDER VOLTA	GE PROTECTIO	N						
V <sub>DD</sub> Quiescent Current	IDD	All inputs = 0V, R <sub>DEL</sub> = 100k	1.2	2.3	3.5	0.85	4	mA
\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\			2.2	4.(	5.5	1.9	6.0	mA
V <sub>DD</sub> Operating Current	I <sub>DDO</sub>	f = 50k⊓z, no load	1.5	2.6	4.0	1.1	4.2	mA
		50kHz, no load, $R_{DEL} = 10k\Omega$	2.5	4.0	6.4	2.1	6.6	mA
AHB, BHB Off Quiescent Current	I <sub>AHBL</sub> , I <sub>BHBL</sub>	AHI = BHI = 0V	0.5	1.0	1.5	0.4	1.6	mA
AHB, BHB On Quiescent Current	I <sub>AHBH</sub> , I <sub>BHBH</sub>	$AHI = BHI = V_{DD}$	65	145	240	40	250	μΑ
AHB, BHB Operating Current	I <sub>AHBO</sub> , I <sub>BHBO</sub>	f = 50kHz, CL = 1000pF	.65	1.1	1.8	.45	2.0	mA
AHS, BHS Leakage Current	I <sub>HLK</sub>	$V_{AHS} = V_{BHS} = 55V$ $V_{AHB} = V_{BHB} = 70V$ $V_{DD} = Not Connected$	-	-	1.0	-	-	μA
V <sub>DD</sub> Rising Undervoltage Threshold	V <sub>DDUV+</sub>		6.8	7.6	8.25	6.5	8.5	V
V <sub>DD</sub> Falling Undervoltage Threshold	V <sub>DDUV-</sub>		6.5	7.1	7.8	6.25	8.1	V
Undervoltage Hysteresis	UVHYS		0.17	0.4	0.75	0.15	0.90	V
AHB, BHB Undervoltage Threshold	VHBUV	Referenced to AHS and BHS	5	6.0	7	4.5	7.5	V
INPUT PINS: ALI, BLI, AHI, BHI, and DIS								
Low Level Input Voltage	V <sub>IL</sub>	Full Operating Conditions	-	-	1.0	-	0.8	V
High Level Input Voltage	V <sub>IH</sub>	Full Operating Conditions	2.5	-	-	2.7		V
Input Voltage Hysteresis			-	35	-	-	-	mV
Low Level Input Current	۱ <sub>IL</sub>	$V_{IN} = 0V$ , Full Operating Conditions	-145	-100	-60	-150	-50	μΑ
High Level Input Current	I <sub>IH</sub>	$V_{IN}$ = 5V, Full Operating Conditions	-1	-	+1	-10	+10	μΑ
TURN-ON DELAY PIN DEL								
Dead Time	T <sub>DEAD</sub>	R <sub>DEL</sub> = 100k	2.5	4.5	8.0	2.0	8.5	μs
		R <sub>DEL</sub> = 10k	0.27	0.5	0.75	0.2	0.85	μS

# ISL83202

Electrical Specifications V <sub>DD</sub> = V	AHB = V <sub>BHB</sub> = 12	2V, V <sub>SS</sub> = V <sub>AHS</sub> = V <sub>BHS</sub> = 0V, R <sub>DEL</sub> = 100	k <b>(Co</b> r	ntinued	I)			
			T <sub>J</sub> = +25°C		T <sub>J</sub> = -55°C TO +150°C			
PARAMETER	SYMBOL	TEST CONDITIONS	MIN	ТҮР	MAX	MIN	MAX	UNITS
GATE DRIVER OUTPUT PINS: ALO, BLO,	AHO, and BHC	)						
Low Level Output Voltage	V <sub>OL</sub>	I <sub>OUT</sub> = 50mA	0.65		1.1	0.5	1.2	V
High Level Output Voltage	V <sub>DD</sub> -V <sub>OH</sub>	I <sub>OUT</sub> = -50mA	0.7		1.2	0.5	1.3	V
Peak Pullup Current	I <sub>O</sub> +	V <sub>OUT</sub> = 0V		1.0		0.6	2.0	А
Peak Pulldown Current	I <sub>O</sub> -	V <sub>OUT</sub> = 12V		1.0		0.6	2.0	А

# $\label{eq:stable} \textbf{Switching Specifications} \quad V_{DD} = V_{AHB} = V_{BHB} = 12 \text{V}, \ V_{SS} = V_{AHS} = V_{BHS} = 0 \text{V}, \ \text{R}_{DEL} = 100 \text{k}, \ \text{C}_{L} = 1000 \text{pF}.$

			Т <sub>Ј</sub> = +25°С		T <sub>J</sub> = -55°C TO +150°C			
PARAMETER	SYMBOL	TEST CONDITIONS	MIN	TYP	MAX	MIN	MAX	UNITS
Lower Turn-off Propagation Delay (ALI-ALO, BLI-BLO)	T <sub>LPHL</sub>		-	25	50	-	70	ns
Upper Turn-off Propagation Delay (AHI-AHO, BHI-BHO)	T <sub>HPHL</sub>		-	55	80	-	100	ns
Lower Turn-on Propagation Delay (ALI-ALO, BLI-BLO)	T <sub>LPLH</sub>		-	40	85	-	100	ns
Upper Turn-on Propagation Delay (AHI-AHO, BHI-BHO)	T <sub>HPLH</sub>		-	75	110	-	150	ns
Rise Time	T <sub>R</sub>		-	9	20	-	25	ns
Fall Time	Ţ	/ •	-	9	20	-	25	ns
Minimum Input Pulse Ainth	T <sub>WIN-ON/OFF</sub>	COM/Ir	50	<u>e</u> r	S	50	-	ns
Output Pulse Response to 50ns Input Pulse	T <sub>PWOUT</sub>			63			80	ns
Disable Turn-off Propagation Delay (DIS - Lower Outputs)	T <sub>DISLOW</sub>		-	50	80	-	90	ns
Disable Turn-off Propagation Delay (DIS - Upper Outputs)	T <sub>DISHIGH</sub>		-	75	100	-	125	ns
Disable Turn-on Propagation Delay (DIS - ALO and BLO)	T <sub>DLPLH</sub>		-	40	70	-	100	ns
Disable Turn-on Propagation Delay (DIS- AHO and BHO)	T <sub>DHPLH</sub>	R <sub>DEL</sub> = 10k	-	1.2	2	-	3	μS
Refresh Pulse Width (ALO and BLO)	T <sub>REF-PW</sub>		375	580	900	350	950	ns

#### TRUTH TABLE

	INPUT					PUT
ALI, BLI	AHI, BHI	VDDUV	VHBUV	DIS	ALO, BLO	AHO, BHO
Х	Х	X	х	1	0	0
х	x	1	х	х	0	0
0	Х	0	1	0	0	0
1	Х	0	Х	0	1	0
0	1	0	0	0	0	1
0	0	0	0	0	0	0

NOTE: X signifies that input can be either a "1" or "0".

# **Pin Descriptions**

PIN		
R	SYMBOL	DESCRIPTION
1	BHB	B High-side Bootstrap supply. External bootstrap diode and capacitor are required. Connect cathode of bootstrap diode and positive side of bootstrap capacitor to this pin.
2	BHI	B High-side Input. Logic level input that controls BHO driver (Pin 16). BLI (Pin 3) high level input overrides BHI high level input to prevent half-bridge shoot-through, see Truth Table. DIS (Pin 8) high level input overrides BHI high level input. The pin can be driven by signal levels of 0V to 15V (no greater than V <sub>DD</sub> ).
3	BLI	B Low-side Input. Logic level input that controls BLO driver (Pin 14). If BHI (Pin 2) is driven high or not connected externally then BLI controls both BLO and BHO drivers, with dead time set by delay currents at DEL (Pin 5). DIS (Pin 8) high level input overrides BLI high level input. The pin can be driven by signal levels of 0V to 15V (no greater than $V_{DD}$ ).
4	ALI	A Low-side Input. Logic level input that controls ALO driver (Pin 13). If AHI (Pin 7) is driven high or not connected externally then ALI controls both ALO and AHO drivers, with dead time set by delay currents at DEL (Pin 5). DIS (Pin 8) high level input overrides ALI high level input. The pin can be driven by signal levels of 0V to 15V (no greater than $V_{DD}$ ).
5	DEL	Turn-on DELay. Connect resistor from this pin to $V_{SS}$ to set timing current that defines the dead time between drivers. All drivers turn-off with no adjustable delay, so the DEL resistor guarantees no shoot-through by delaying the turn-on of all drivers. The voltage across the DEL resistor is approximately $V_{DD}$ -2V.
6	V <sub>SS</sub>	Chip negative supply, generally will be ground.
7	AHI	A High-side Input. Logic level input that controls AHO driver (Pin 10). ALI (Pin 4) high level input overrides AHI high level input to prevent half-bridge shoot-through, see Truth Table. DIS (Pin 8) high level input overrides AHI high level input. The pin can be driven by signal levels of 0V to 15V (no greater than V <sub>DD</sub> ).
8	DIS	DISable input. Logic level input that when taken high sets all four outputs low. DIS high overrides all other inputs. When DIS is taken low the outputs are controlled by the other inputs. The pin can be driven by signal levels of 0V to 15V (no greater than $V_{DD}$ ).
9	АНВ	A High-side Bootstrap supply. External bootstrap diode and capacitor are required. Connect cathode of bootstrap diode and positive s de o boots rap apacitor to this pin
10	AHQ V	A High side Output Connect to gate of A High side power MOSFET.
11	AHS	A High-side Source connection. Connect to source of A High-side power MOSFET. Connect negative side of bootstrap capacitor to this pin.
12	V <sub>DD</sub>	Positive supply to control logic and lower gate drivers. De-couple this pin to V <sub>SS</sub> (Pin 6).
13	ALO	A Low-side Output. Connect to gate of A Low-side power MOSFET.
14	BLO	B Low-side Output. Connect to gate of B Low-side power MOSFET.
15	BHS	B High-side Source connection. Connect to source of B High-side power MOSFET. Connect negative side of bootstrap capacitor to this pin.
16	BHO	B High-side Output. Connect to gate of B High-side power MOSFET.

# **Timing Diagrams**



## **Performance Curves**







FIGURE 5. V<sub>DD</sub> SUPPLY CURRENT vs TEMPERATURE AND SWITCHING FREQUENCY (1000pF LOAD)













## Performance Curves (Continued)



9

## Performance Curves (Continued)



FIGURE 16. DEAD-TIME vs DEL RESISTANCE AND BIAS SUPPLY ( $V_{DD}$ ) VOLTAGE

# www.BDTIC.com/Intersil

# Dual-In-Line Plastic Packages (PDIP)



#### NOTES:

- 1. Controlling Dimensions: INCH. In case of conflict between English and Metric dimensions, the inch dimensions control.
- 2. Dimensioning and tolerancing per ANSI Y14.5M-1982.
- 3. Symbols are defined in the "MO Series Symbol List" in Section 2.2 of Publication No. 95.
- 4. Dimensions A, A1 and L are measured with the package seated in JE-DEC seating plane gauge GS-3.
- 5. D, D1, and E1 dimensions do not include mold flash or protrusions. Mold flash or protrusions shall not exceed 0.010 inch (0.25mm).
- 6. E and e<sub>A</sub> are measured with the leads constrained to be perpendicular to datum -C-.
- 7. e<sub>B</sub> and e<sub>C</sub> are in astred antile lead ins with the leads inconstrained OM / Intersi
- 8. B1 maximum dimensions do not include dambar protrusions. Dambar protrusions shall not exceed 0.010 inch (0.25mm).
- 9. N is the maximum number of terminal positions.
- 10. Corner leads (1, N, N/2 and N/2 + 1) for E8.3, E16.3, E18.3, E28.3, E42.6 will have a B1 dimension of 0.030 0.045 inch (0.76 1.14mm).

#### E16.3 (JEDEC MS-001-BB ISSUE D) 16 LEAD DUAL-IN-LINE PLASTIC PACKAGE

	INC	HES	MILLIM		
SYMBOL	MIN	MAX	MIN	MAX	NOTES
A	-	0.210	-	5.33	4
A1	0.015	-	0.39	-	4
A2	0.115	0.195	2.93	4.95	-
В	0.014	0.022	0.356	0.558	-
B1	0.045	0.070	1.15	1.77	8, 10
С	0.008	0.014	0.204	0.355	-
D	0.735	0.775	18.66	19.68	5
D1	0.005	-	0.13	-	5
E	0.300	0.325	7.62	8.25	6
E1	0.240	0.280	6.10	7.11	5
е	0.100	BSC	2.54	BSC	-
e <sub>A</sub>	0.300	BSC	7.62 BSC		6
e <sub>B</sub>	-	0.430	-	10.92	7
L	0.115	0.150	2.93	3.81	4
Ν	1	6	1	9	

Rev. 0 12/93

# Small Outline Plastic Packages (SOIC)



#### NOTES:

- 1. Symbols are defined in the "MO Series Symbol List" in Section 2.2 of Publication Number 95.
- 2. Dimensioning and tolerancing per ANSI Y14.5M-1982.
- 3. Dimension "D" does not include mold flash, protrusions or gate burrs. Mold flash, protrusion and gate burrs shall not exceed 0.15mm (0.006 inch) per side.
- 4. Dimension "E" does not include interlead flash or protrusions. Interlead flash and protrusions shall not excree (1.25nm (0.010 noh) per side.
- nt a visual ide OM / Intersi 5. The chamfer on the bory is optional. If it is not present feature must be located within the crossnatched area.
- 6. "L" is the length of terminal for soldering to a substrate.
- 7. "N" is the number of terminal positions.
- 8. Terminal numbers are shown for reference only.
- 9. The lead width "B", as measured 0.36mm (0.014 inch) or greater above the seating plane, shall not exceed a maximum value of 0.61mm (0.024 inch).
- 10. Controlling dimension: MILLIMETER. Converted inch dimensions are not necessarily exact.

All Intersil U.S. products are manufactured, assembled and tested utilizing ISO9000 quality systems. Intersil Corporation's quality certifications can be viewed at www.intersil.com/design/quality

Intersil products are sold by description only. Intersil Corporation reserves the right to make changes in circuit design, software and/or specifications at any time without notice. Accordingly, the reader is cautioned to verify that data sheets are current before placing orders. Information furnished by Intersil is believed to be accurate and reliable. However, no responsibility is assumed by Intersil or its subsidiaries for its use; nor for any infringements of patents or other rights of third parties which may result from its use. No license is granted by implication or otherwise under any patent or patent rights of Intersil or its subsidiaries.

For information regarding Intersil Corporation and its products, see www.intersil.com

M16.15 (JEDEC MS-012-AC ISSUE C) 16 LEAD NARROW BODY SMALL OUTLINE PLASTIC PACKAGE

	INC	HES	MILLIN	IETERS	
SYMBOL	MIN	MAX	MIN	MAX	NOTES
A	0.0532	0.0688	1.35	1.75	-
A1	0.0040	0.0098	0.10	0.25	-
В	0.013	0.020	0.33	0.51	9
С	0.0075	0.0098	0.19	0.25	-
D	0.3859	0.3937	9.80	10.00	3
Е	0.1497	0.1574	3.80	4.00	4
е	0.050	BSC	1.27 BSC		-
Н	0.2284	0.2440	5.80	6.20	-
h	0.0099	0.0196	0.25	0.50	5
L	0.016	0.050	0.40	1.27	6
Ν	1	6	1	6	7
α	0°	8°	0°	8°	-

Rev. 1 6/05