

SYS72601VEE

Socket 370 ISA CPU Card with Dual Ethernet



FEATURES

NEW

- Socket 370 for Tualatin™ and VIA® C3 processor
- Supports CRT / LCD (TFT/STN/DSTN)
- Supports Gigabit Ethernet and Fast Ethernet

SPECIFICATIONS

Processor	Socket 370 for Intel® Celeron® /Pentium® III and VIA® C3 processor; 533~1.4GHz
System Memory	1×168-pin SDRAM, max. up to 512MB
Chipset	VIA® VT8606 (Twist-T) + VT82C686B
Graphics	VIA® Twister chip with integrated S3 Pro Savage4 2D/3D/Vedio accelerator
BIOS	Phoenix-Award 4Mbit with RPL/PXE LAN boot ROM, SmartView and customer CMOS backup
MIO	1×ATA-100 IDE, 1×FDD, 1×K/B + M/S, 1×RS232,1×RS232/422/485, 1×LPT, 1×IrDA
Ethernet	RTL8100C, 10/100Base-T with WOL and boot ROM features
USB	2×USB ports; USB 1.1 compliant
SSD	DiskOnChip®
Watchdog Timer	System rest and NMI; 64 Levels, 0.5~8 / 5~80 / 50~800 / 100~1600 Seconds
Extension Interface	PC/104 and ISA Golden Finger expansion interface
Battery	Lithium 3V/196 mAH
Size/Weight	185mm×122mm / 0.3 kg
Operation Temperature	0°C to 60°C
Operation Humidity	10% ~ 95% relative humidity, non-condensing

PACKING LIST

1×SYS72601 SBC

Quick installation guide
Manual, driver & utility CD
I/O Cable Kit (1×40-pin IDE, 1×34pin FDD, 1×COM+LPT with bracket)

ORDERING INFORMATION

Standard

SYS72601VEE	With integrated VGA for CRT/LCD output, 2 RTL8100C for fast Ethernet
SYS72601VE	With CRT/LCD and fast Ethernet

Optional

SYS72601VGE	With integrated VGA for CRT/LCD output,RTL8110S for Gigabit and RTL8100C for fast Ethernet
--------------------	---