

SYS73620VEA

Socket 370 Embedded SBC with 4 COM and Audio



FEATURES

NEW

- Socket 370 for Tualatin™ and VIA® C3 processor
- Supports CRT / LCD (TFT/STN/DSTN)
- Supports 10/100Base-T Fast Ethernet
- AC'97 Audio CODEC
- Four COM ports
- DiskOnChip® and CompactFlash™

SPECIFICATIONS

Processor	Socket 370 for Intel® Celeron® /Pentium® III and VIA® C3 processor; 533~1.4GHz
System Memory	1 x 168-pin SDRAM, max. up to 512MB
Chipset	VIA® VT8606 (Twist-T) + VT82C686B
Graphics	VIA® Twister chip with integrated S3 Pro Savage4 2D/3D/Vedio accelerator
BIOS	Phoenix-Award 4Mbit with RPL/PXE LAN boot ROM, SmartView and customer CMOS backup
MIO	2×ATA-100 IDE, 1×FDD, 1 x K/B + M/S, 3×RS232, 1×RS232/422/485, 1×LPT, 1×IrDA
Ethernet	RTL8100C, 10/100Base-T with WOL
Audio	AC'97 Audio codec with amplify
USB	2 x USB ports; USB 1.1 compliant
DIO	4-channel input and output
SSD	DiskOnChip® and CompactFlash™
Watchdog Timer	System rest and NMI; 64 Levels, 0.5~8 / 5~80 / 50~800/ 100~1600 Seconds
Extension Interface	PC/104 and EISA
Battery	Lithium 3V/196 mAH
Size/Weight	203mm x 146mm / 0.32 kg
Operation Temperature	0°C to 60°C
Operation Humidity	10% ~ 95% relative humidity, non-condensing

PACKING LIST

1×SYS73620 SBC

Quick installation guide
Manual, driver & utility CD
1×8-pin power input adapter cable

ORDERING INFORMATION

Standard

SYS73620VEA

With integrated VGA for CRT/LCD output,
RTL8100C fast Ethernet and AC'97 Audio